

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







TDS # 1668

CHEMTRONICS Technical Data Sheet

Static Free[™] Plast-N-Glas[®]

PRODUCT DESCRIPTION

Static Free[™] Plast-N-Glas[®] effectively cleans, polishes and eliminates static charges. A single application dissipates electrostatic buildup while also removing dirt, grease, ink, fingerprints and nicotine stains. Static Free Plast-N-Glas[®] will not streak, smear, scratch, or abrade. Leaves surfaces thoroughly clean for improved optical clarity and distortion-free reading.

- For use on nonporous transparent surfaces
- Cleans and controls static in one application
- Reduces attraction of dust, dirt and other airborne contaminants
- Nonstreaking foaming spray will not "run" or drip
- Controls buildup of potentially harmful electrostatic charges
- Noncorrosive
- Nonabrasive, nonflammable

TYPICAL APPLICATIONS

Static Free[™] Plast-N-Glas[®] effectively cleans and polishes:

- Control panels, Computer Housings, Oscilloscopes
- Laboratory, Engineering and Office Equipment
- Medical Equipment
- Photographic Processing Equipment, Graphic Arts Tables

TYPICAL PRODUCT DATA AND PHYSICAL PROPERTIES

| Specifications and Physical | | | | | |
|-------------------------------|-------------------------|--|--|--|--|
| Properties | | | | | |
| Appearance | Foamy White Spray | | | | |
| Odor | Clean Fresh Scent | | | | |
| Spray Type | Dense Non-Dripping Foam | | | | |
| Can Pressure @ 77°F (25°C) | 55 PSIG | | | | |
| pH (Liquid On | ly) 9.0 | | | | |
| Flame Projection | on Test Nonflammable | | | | |
| Shelflife | 5 years | | | | |
| RoHS/WEEE Status | ROHS | | | | |

COMPATIBILITY

Static Free[™] Plast-N-Glas[®] is excellent for use on glass and most plastics. As with any cleaning product, compatibility with substrate must be determined on a non-critical area prior to use.

| <u>Material</u> | Compatibility |
|---------------------|----------------------|
| ABS | Excellent |
| Buna-N | Excellent |
| EPDM | Excellent |
| Graphite | Excellent |
| HDPE | Excellent |
| Kynar TM | Excellent |
| LDPE | Excellent |
| Lexan TM | Excellent |
| Neoprene | Excellent |
| Nylon™ 66 | Excellent |
| Cross-Linked PE | Excellent |
| Polypropylene | Excellent |
| Polystyrene | Excellent |
| PVC | Excellent |
| Silicone Rubber | Excellent |
| Teflon™ | Excellent |
| Viton TM | Excellent |

USAGE INSTRUCTIONS

For industrial use only.
Read MSDS carefully prior to use.
Shake well before using. Spray lightly 8-12 inches from surface. Wipe and polish with clean lint-free cloth such as Chemtronics®
ControlwipesTM.

AVAILABILITY

ES1668 14 oz. Aerosol (EU)

TECHNICAL & APPLICATION ASSISTANCE

Chemtronics provides a technical hotline to answer your technical and application related questions. The toll free number is:

1-800-TECH-401.

ENVIRONMENTAL IMPACT DATA

| ENVIRONMENTAL IMPACT DATA | | | | |
|---------------------------|------|-----|------|--|
| CFC | 0.0% | VOC | 6.0% | |
| HCFC | 0.0% | HFC | 0.0% | |
| CL Solv. | 0.0% | ODP | 0.0 | |

CFC, HCFC, CL. SOLV., VOC, and HFC numbers shown are the content by weight. Ozone depletion potential (ODP) is determined in accordance with the Montreal Protocol and U.S. Clean Air Act of 1990. The ODP of this product is 0.0. It is the sum of the ODP of the substances that may contribute to the depletion of stratospheric ozone, based upon the weight of each substance in the product's formulation.

Chemtronics® is registered trademarks of Chemtronics. All rights reserved. Static FreeTM is a trademark of Chemtronics. All rights reserved. All other trademarks herein are trademarks or registered trademarks of their respective owners.

NOTE:

This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly. CHEMTRONICS does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

CHEMTRONICS 8125 COBB CENTER DRIVE KENNESAW, GA 30152 1-770-424-4888 REV. H (11/16)

| DISTRIBUTED BY: |
|-----------------|
| |
| |
| |