imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



HellermannTyton

Specification Sheet

Part Number: ETCW660



Electrical Tape, .75" x 66' Roll, 8.0 mil Thick, PVC, Black, 10 rolls/pkg

Article Number	904-00010
Туре	ETCW66
Color	Black (BK)
Features & Benefits	 Heavy duty PVC tape is ideal for cold weather installations and is "weather resistant" for outdoor applications.
Quantity Per	reel
Product Description	Heavy duty vinyl tapes are ideal for outdoor applications. Tape provides fast, easy and economical cable splicing, terminating, wire insulating, and more. These comformable high quality tapes have exceptional surface and adhesive characteristics. Tape is applied by overlapping each layer 50% and using tension. After the tape is adhered, the memory of the tape returns, tightening the seal and making the taped area even more waterproof.
Short Description	Electrical Tape, .75" x 66' Roll, 8.0 mil Thick, PVC, Black, 10 rolls/pkg

Minimum Tensile Strength (Imperial)	20.0
Length L (Imperial)	66.0
Length L (Metric)	20.12
Width W (Imperial)	0.75
Width W (Metric)	19.05
Thickness T (Imperial)	8.0

Material	Flexible Polyvinyl Chloride (PVC)
Material Shortcut	PVC
US MIL SPEC	MIL-1-24391-A Operating Temperature (Metric)
0 °F to +194 °F (-17.8 °C to +90 °C)	UL Recognized (US)
Yes	
Package Quantity(Imperial)	10
Package Quantity (Metric)	10

3919905030

© 2018 HellermannTyton. All rights reserved. Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions