



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



rfid as a feature



BENEFITS:

- » Fast integration and time-to-market
- » Unparalleled investment protection
- » Cost-effective and highly scalable
- » Common Blade technology: common size, connection method, and software interface with the SkyeModule™ M2, M7, M9 and M10 readers for maximum design and solution flexibility

FEATURES:

- » Miniscule footprint – about the size of a matchbook
- » Greatest tag compatibility with Tagnostic® and TagIQ™
- » Minimal power consumption and maximum read range
- » Software Adjustable Host Interfaces: UART (TTL), SPI, USB, I2C
- » 4 General Purpose I/O Pins
- » Simple and intuitive API

SkyeModule Nova



Product Overview

The **SkyeModule™ Nova** marks the next generation of Skyetek UHF reader modules. The Nova is an ultra-small, power efficient, EPC Class 1 Gen 2 reader/writer module. A cutting edge ARM Cortex microcontroller and latest UHF transceiver technology coupled with the reader's intelligent operating system make this module the most feature rich UHF reader module. Manufactured in accordance with ISO 9001 and ISO 13485, quality is a top priority for all Skyetek modules.

The SkyeModule Nova adheres to the PCI Express Mini half card form factor, a widely popular format which allows the Nova to be used quickly and easily in mobile computing applications, such as tablets and handhelds. At about the size of a matchbook, this module can also be fit into almost any new or existing OEM design. The Nova module is also well suited for battery powered and other power sensitive applications because of the low power features including software stand-by mode and deep sleep mode. In addition, the wide input voltage range and highly efficient switching power design make this module perfect for battery powered applications right off the shelf.

The Nova utilizes 2 antenna ports that can be selected via software control, making this module suited for mobile or fixed applications. It is also the first product to use Skyetek's Adaptive Antenna Tuning, meaning the Nova can automatically detect and correct for impedance mismatches between the reader and antenna. Using this technology, the Nova will always deliver the maximum power to the antenna while reducing noise in the system.

The Nova uses the same Skyetek Protocol as the M7, M9 and M10, so existing users can easily migrate to the next generation product without needed to rewrite communication software. Skyetek also provides an interface board in the same form factor as the M9-MH, providing the absolute shortest path for integration into existing applications.

Features:

- 860-960MHz UHF RFID
- Reads and writes to transponders based on EPC Class 1 Gen 2
- Wide and efficient power supply with input from 2.0 – 5.5V
- 2 antenna ports with Skyetek Adaptive Antenna Tuning
- 500mW output power, up to 10m read range
- RSSI and DRM (coming soon!)
- Sleep mode current down to 10uA
- Easy migration from M7, M9 and M10
- Supported host interfaces include USB, TTL level RS232, SPI, I2C
- Modularly certified (coming soon!)



About SkyeTek:

SkyeTek, Inc continually strives to enable the pervasive adoption of RFID technology. SkyeTek's Tagnostic™ RFID readers work with most industry standard tags and smart labels; their low power requirements and small form factor make them the optimal choice for embedding into new or existing products. SkyeTek's RFID reader technology is available in several formats including reader modules, finished readers and hardware reference designs. SkyeTek markets to OEM customers in targeted vertical markets with several high-volume licensing options available.

For more information:

1732 Wazee St., STE 202
Denver, Colorado 80202 USA
ph: 720.328.3425

www.skyetek.com



Copyright © 2014 SkyeTek, Inc.

SkyeTek®, Tagnostic®, SkyeWare™, Physical made Digital™, TagIQ™, ReaderDNA™, SkyeModule™ and AURA™ are trademarks or registered trademarks of SkyeTek, Inc. All other trademarks or brand names are the properties of their respective holders. Features and specifications are subject to change without notice. ver. 111313

Software and Security

Software
SkyeAPI C/.NET API
SkyeTek Protocol v3
SkyeWare 4 developer interface
Demonstration applications

SkyeOS™ Embedded
TagIQ™
Field upgradeable firmware bootloader

Tag Support

Air Interface	Manufacturer	Product Family	Tags
ISO 18000-6C	NXP	UCODE	G2XM, G2XL, G2iM, G2iL
ISO 18000-6C	Impinj	Monza	Monza3, Monza4, Monza5
ISO 18000-6C	Alien	Higgs	Higgs3, Higgs4

[†]Select Only

Specifications

Frequency
860-960MHz

Peripheral I/O Connection
4 programmable GPIO pins

Current Consumption
Sleep Mode: 10µA
Idle Mode: 150 mA
Scan Mode: 500 mA

Physical
Length: 30mm
Width: 25mm
Height: 5 mm

Supply Voltage
2.0-5.5V

Antenna Options
2 antenna ports, 50 Ω impedance

Host Interfaces/Data Rates
UART (TTL): 9.6-115.2 kbps
SPI: Mode 1 up to 4 Mb/s
USB: 2.0 Full Speed 12 Mb/s
I²C: 100/400 kHz

Transponder Communication Rate
ISO 18000-6C
FMO
Miller 4
Miller 8

Effective Range
Passive Tags: up to 6m
Battery Assisted Passive tags: up to 10m

Environment
Storage Temperature: -20°C to 85°C
Operating Temperature: -10°C to 70°C

Air-interface Protocols
ISO 18000-6C (EPC Class 1 Gen 2)

Compliance
FCC Part 15.247¹
FCC Part 15 Modular Approval¹
EN 302-208¹

¹ Planned, pending final testing

SkyeTek Reader Technology

SkyeTek provides a variety of reader technology at both 13.56 MHz (HF) and 860- 960 MHz (UHF). ReaderDNA, a comprehensive reference design, is available for component level integration of the technology including complete design files, BOM, and test fixture. All SkyeTek readers leverage powerful firmware that drastically reduce hardware costs and are delivered in conjunction with ReaderDNA. SkyeModules are controlled via the SkyeTek Protocol, a powerful but simple communication protocol that grants the user access to all features of an RFID transponder. Further, they have been designed with flexible and modular embedded software that allows one to select only the features desired.