imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



2 THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. DIMENSIONS in. [mm] MAX. WIRE RANGE PANDUIT WIRE HOUSING AWG TOOLS COLOR B± .01 PART # INSUL. .03 .02 TERMINAL [mm²]

[0,3]

.49 [12,4] .15 [3,8]

.49 [12,4] .17 [4,3]

D DIA

.55 [14,0] .25 [6,35] CT-2500 (CT-2550CH)

 $C \pm$

[0,3]

.07 [1,8]

.07 [1,8]

В

* EV10-P55 NOT UL LISTED, BRAZED SEAM, 300V MAX VOLTAGE **PANDUIT APPROVED TOOL

RED

BLUE

L±

[0,8]

.97 [24,6]

.97 [24,6]

YELLOW 1.10 [27,9] .10 [2,5]

NOTES:

EV18-P47B

EV14-P47B

EV10-P55*

- 1. UL LISTED FOR:
 - A. SOILD OR STRANDED COPPER WIRE ONLY
 - B. 221°F [105°C] MAX. OPERATING TEMPERATURE
 - C. 600V. MAX. VOLTAGE RATING

DIA.

.15 [3,8]

.17 [4,3]

.25 [6,4]

#22-18

[0,5-1,0]

#16-14

[1,5-2,5]

#12-10

[4,0-6,0]

- 2. MATERIAL: A. STAMPING: .03" [0,8] THK COPPER, TIN PLATED B. HOUSING: VINYL, COLOR CODED
- 3. WIRE STRIP LENGTH: 5/16" +1/32 [7,9mm ^{+0,8}]
- 4. SEE www.panduit.com FOR PACKAGE QUANTITIES
- 5. DIMENSIONS IN BRACKETS ARE METRIC EQUIVALENT

- B DIA.

BUTTED

SEAM

HOUSING

MAX. WIRE INSUL.

DIA "D"

В



CT-100A **CT-260

CT-600A (CT-550CH)

CT-1550

CT-1551

	I							TITLE	
A								STRONGHOLD PIN TERMINAL VINYL INSULATED #22-10 AWG	A
								CUSTOMER DRAWING	
								DO123STB/00	
								UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]	
								.X ± .XXX ± SEE NOTES	
0A/16	00	2/18	JHNU	TMR	RGB	RELEASED	00123SH	THIRD ANGLE PROJECTION SH41335	
D10100[REV	DATE	BY	СНК	APR	DESCRIPTION	ECN	DRAWN BY DATE CHK SCALE SIZE JHNU 2/18 TMR N.T.S. SHT 1 0F 1 A	
						2		1	