

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China















EXC400

Today's work and lifestyles require us to communicate anytime, anywhere whether on the move or sitting still. Bluetooth and 802.11 standards make wireless connections to computer networks and other devices possible, while at the same time enabling freedom of movement.

Laird's practical and rugged external wireless device antennas are designed to fit into the portable devices used in office, industrial and home environments. The antennas feature flexible elements and many are $\frac{1}{2}$ wave coaxial dipole design for reduced ground dependence and improved performance.

FEATURES

- Injection molded ¼ wave flexible cable antenna
- · High durability, high efficiency
- · Textured finish with strain-relief base
- · Available in various standard connectors
- · An original 'Tuf Duck' antenna

MARKETS

• For Bluetooth & IEEE 802.11b/g devices

PARAMETER	SPECIFICATION
Frequency Range	UHF Trunking/Cellular
VSWR	1.5:1 max at resonance
Polarization	Vertical
Nominal Impedance	50 ohms
Temperature Range	-40°C to +85°C
Power Rating	50 Watts
Drop Test	1 M

The EXC model antenna is available in the following frequencies and connectors.

Order by antenna model, frequency and connector. For example: EXC450MX.

Length of each antenna will vary according to the connector chosen.

PART#	FREQUENCY BAND	CONNECTORS	AVERAGE LENGTH
EXC400	400-420 MHz	BN, BNX, KR, MD, MX, MXI, SF, SFU, SM, SMV, TN $\&$ TNX	6.75" – 7.0"
EXC410		SMI	
EXC420	420-450 MHz	BN, BNX, KR, MD, MX, SF, SFU, SM, SMV, TN & TNX	6.75" – 7.0"
EXC440		SMI	
EXC450	450-470 MHz	BN, BNX, KR, MD, MX, MXI, SF, SFU, SM, SMV, TN $\& {\sf TNX}$	6.39" – 6.9"
EXC470	470-512 MHz	BN, BNX, KR, MD, MX, MXI, SF, SFU, SM, SMV, TN $\&$ TNX	6.13" – 6.7"
EXC806	806-866 MHz	BN, BNX, KR, MD, MX, SF, SFU, SM, SMV, TN & TNX	3.7" – 4.6"
EXC902	902-960 MHz	BN, BNX, KR, MD, MX, SF, SFU, SM, SMV, TN & TNX	3.5" – 3.65"

Specifications subject to change without notice.according to the connector chosen.

Americas: +1.847 839.6907

IAS-Americas East Sales@lair dtech.com

Europe: +44.1628.858941 IAS-EUSales@lairdtech.com Asia: +86.21.5855.0827.127 IAS-AsiaSales@lairdtech.com