



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China






Triad Magnetics
 460 Harley Knox Blvd
 Perris CA 92571

Tel: 951.277.0757 • **Fax:** 951.277.2757

Email: info@triadmagnetics.com • **Website:** www.triadmagnetics.com

Item # F-1000U (End of Life), Single Secondary Chassis Mount Power Transformers

Triad offers a full choice of power supply transformers for direct use or in transformer, rectifier, or filter circuits. Other available secondary voltages include control, filament and low level signaling in standard values. The transformers are single primary with single and multiple secondaries in standard size and weight configurations.



Specifications

Secondary Voltage	24.0 V
Secondary Current	21.000 A
Transformer Contact Type	Center Tap
Primary Voltage	115 V 230 V
Primary Frequency	50 Hz 60 Hz
Secondary RMS Test Voltage	1,500 V
Case Type	U

Connections	Leads
Height (H)	5 1/4 in
Width (W)	4 3/8 in
Depth (D)	3 1/2 in
Mounting Width	3 1/2 in
Mounting Depth	23/4 in
Mounting Hole Size	13/64 x 3/8 in
Weight	14.00 lb