# mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





### **POWER TRANSFORMER PC Mount: Dual Primary**

### **F-333P**

#### **Electrical Specifications (@25C)**

1. Maximum Power: 1.5 VA					
2. Primary:	Series:230V@50/60 Hz				
-	Parallel: 115V@50/60Hz				
3. Secondary:	Series: 30.0V CT @ 0.050 Amps				
-	Parallel: 15.0V CT @ 0.100 Amps				

#### **Description:**

The F-333P is part of a wide selection of plug-in types that meet the needs of PC boards and solid state power supply design. This transformer can satisfy power as well as control and instrumentation applications.

#### **Construction:**

Wound on a single channel nylon bobbin. Materials are UL recognized, Class B (130° C) rated.

#### Safety:

These products are 100% hipot tested with an insulation of 1500V between primary and secondary windings.


Units: In inches

#### **Dimensions:**

А	В	С	D	Е
1.125	1.375	1.125	0.203	1.00

Pin length: 0.187 in. Pin size: 0.20 x .041 in. Weight: 4.0 oz

#### Schematic:



Primary:Series - 1 to 4, Jumper 2 to 3<br/>Parallel - 1 to 4, Jumper 1 to 3 and 2 to 4Secondary:Series - 5 to 8, Jumper 6 to 7<br/>Parallel - 5 to 8, Jumper 5 to 7 and 6 to 8


**RoHS Compliance:** As of manufacturing date February 2005, all standard products meet the requirements of 2011/65/EU, known as the RoHS initiative.


\*Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics website for the most current version. For soldering and washing information please see http://www.triadmagnetics.com/faq.html


Web: www.TriadMagnetics.com Phone 951-277-0757 Fax 951-277-2757

460 Harley Knox Blvd. Perris, California 92571









Publish Date: June 7, 2016