



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



LINNEA-90-B

~90° 90° wide beam optimized for 0.5 mm metal sheet or profile

TECHNICAL SPECIFICATIONS:

Dimensions	285x40 mm
Height	9.5 mm
Fastening	clips
Colour	clear
Box size	578 x 378 x 295 mm
Box weight	7.1 kg
Quantity in Box	180 pcs
ROHS compliant	yes ⓘ





MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour
LINNEA-90-B	Lens	PC	clear



PHOTOMETRIC DATA (MEASURED):




LED Tridino 1ft 1100lm xxxHE 1R HV
 FWHM 103.0 + 89.0°
 Efficiency 82 %
 Peak intensity 0.390 cd/lm
 Required components:





LED XP-E
 FWHM 104.0 + 88.0°
 Efficiency 81 %
 Peak intensity 0.390 cd/lm
 Required components:



LED NF2x757D
 FWHM 86.0 + 96.0°
 Efficiency 0 %
 Peak intensity 0.480 cd/lm
 Required components:




LED NFSx757G
 FWHM 98.0 + 88.0°
 Efficiency 81 %
 Peak intensity 0.390 cd/lm
 Required components:



PHOTOMETRIC DATA (MEASURED):

OSRAM



LED PrevaLED Linear Slim 3 (2000lm)
 FWHM 103.0 + 89.0°
 Efficiency 81 %
 Peak intensity 0.380 cd/lm
 Required components:



OSRAM

Opto Semiconductors



LED Duris S5 (2 chip)
 FWHM 99.0 + 89.0°
 Efficiency 83 %
 Peak intensity 0.400 cd/lm
 Required components:



OSRAM



Opto Semiconductors

LED Duris S5 (Single chip)
 FWHM 98.0 + 89.0°
 Efficiency 85 %
 Peak intensity 0.410 cd/lm
 Required components:



PHILIPS



LED Fortimo LED Strip 1ft 1100lm FC HV4 & LV
 FWHM 100.0 + 89.0°
 Efficiency 82 %
 Peak intensity 0.400 cd/lm
 Required components:



PHOTOMETRIC DATA (MEASURED):



PHILIPS

LED Fortimo LED Strip 1ft 650lm FC HV4 & LV4
FWHM 102.0 + 90.0°
Efficiency 82 %
Peak intensity 0.380 cd/lm
Required components:





SAMSUNG

LED LM561B Plus
FWHM 89.0 + 104.0°
Efficiency 83 %
Peak intensity 0.380 cd/lm
Required components:





SAMSUNG

LED LT-H282C
FWHM 103.0 + 87.0°
Efficiency 84 %
Peak intensity 0.400 cd/lm
Required components:



SAMSUNG



LED LT-H562C
FWHM 103.0 + 87.0°
Efficiency 84 %
Peak intensity 0.400 cd/lm
Required components:



PHOTOMETRIC DATA (MEASURED):



SAMSUNG

LED LT-Q282B
FWHM 101.0 + 87.0°
Efficiency 84 %
Peak intensity 0.400 cd/lm
Required components:





SAMSUNG

LED LT-S282H
FWHM 104.0 + 86.0°
Efficiency 85 %
Peak intensity 0.400 cd/lm
Required components:





SAMSUNG

LED LT-S562H
FWHM 104.0 + 86.0°
Efficiency 85 %
Peak intensity 0.400 cd/lm
Required components:



SAMSUNG



LED LT-V282E
FWHM 103.0 + 86.0°
Efficiency 85 %
Peak intensity 0.400 cd/lm
Required components:





PHOTOMETRIC DATA (MEASURED):

SAMSUNG

LED LT-V562E
FWHM 103.0 + 86.0°
Efficiency 85 %
Peak intensity 0.400 cd/lm
Required components:





LED SunLike 3030
FWHM 99.0 + 88.0°
Efficiency 85 %
Peak intensity 0.410 cd/lm
Required components:





TRIDONIC

LED LLE G4 24x280mm 1250lm
FWHM 100.0 + 89.0°
Efficiency 83 %
Peak intensity 0.400 cd/lm
Required components:



TRIDONIC

LED LLE G4 24x280mm 2000lm ADV
FWHM 98.0 + 88.0°
Efficiency 83 %
Peak intensity 0.410 cd/lm
Required components:



PHOTOMETRIC DATA (MEASURED):

TRIDONIC


LED LLE G4 24x280mm 650lm

FWHM 99.0 + 89.0°

Efficiency 84 %

Peak intensity 0.410 cd/lm

Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)