

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









## PRODUCT DATASHEET FA10668\_CXP-RS

### **CXP-RS**

 $\sim$ 11° spot beam optimized for CREE XP-E. Assembly with black holder.

### **TECHNICAL SPECIFICATIONS:**

Dimensions 21.6 + 21.6 mm

Height 13.2 mm

Fastening tape

Colour black

Box size

Box weight 11.9 kg

Quantity in Box 2448 pcs

ROHS compliant yes (1)




### **MATERIAL SPECIFICATIONS:**

Component	Type	Material	Colour
ROSE-B-B-RS	Lens	PC	clear
ROSE-HLD-CXP-BLK	Holder	PC	black
ROSE-TAPE	Tane	PU tane	



## PRODUCT DATASHEET FA10668 CXP-RS



Last update: 27/06/2013 Subject to change without prior notice LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.



### PHOTOMETRIC DATA (MEASURED):

## CREE 💠

LED XP-E

FWHM 7.0°

Efficiency 86 %

Peak intensity 24.770 cd/lm

Required components:

### CREE \$

LED XP-G

FWHM 11.0°

Efficiency 85 %

Peak intensity 15.870 cd/lm

Required components:

## CREE \$


LED XP-L

FWHM 16.0° Efficiency 80 %

Peak intensity 8.700 cd/lm

Required components:







LED Z5

FWHM 7.0°

Efficiency 83 %

Peak intensity cd/lm

Required components:

### PHOTOMETRIC DATA (SIMULATED):

20.300 cd/lm


L	K	E,	E,	V

LED XHP35 HD

FWHM 16.0° Efficiency 84 %

Peak intensity 7.080 cd/lm

Required components:



### CREE 💠


Peak intensity

LED XP-G2

FWHM 11.0°

Efficiency 87 %

Required components:





## PRODUCT DATASHEET FA10668 CXP-RS

### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

#### **MATERIALS:**

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

### LEDIL Oy

Joensuunkatu 13 FI-24240 SALO Finland

#### LEDIL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

# Local sales and technical support

www.ledil.com/ where\_to\_buy

#### **Shipping locations**

Salo, Finland Hong Kong, China

### **Distribution Partners**

www.ledil.com/ where to buy