

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









PRODUCT DATASHEET FA11212_TINA-RS

TINA-RS

~13° spot beam optimized for LUXEON Rebel. Assembly with holder and installation tape.

TECHNICAL SPECIFICATIONS:

Dimensions Ø 16.1 mm

Height 9.4 mm

Fastening tape, pin

Colour black

Box size 470 x 240 x 105 mm

Box weight 4.1 kg

Quantity in Box 2016 pcs

ROHS compliant yes 1




MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour
TINA-XP-RS	Lens	PMMA	clear
TINA-H-TAPE-RE-BLK	Holder	PC	black
TINA-TAPE3	Tape	PU tape	black



PRODUCT DATASHEET FA11212 TINA-RS



Last update: 17/05/2018

Subject to change without prior notice


PRODUCT DATASHEET FA11212_TINA-RS

PHOTOMETRIC DATA (MEASURED):

CREE \$

LED XB-H
FWHM 15.0°
Efficiency 88 %
Peak intensity 10.300 cd/lm
Required components:





MUMILEDS

LED LUXEON Rebel

FWHM 10.0° Efficiency 93 % Peak intensity 16.900 cd/lm

Required components:


DESCRIPTION

LED LUXEON TX

FWHM 15.0° Efficiency 88 %

Peak intensity 10.500 cd/lm Required components:





DESCRIPTION LUMILEDS


LED LUXEON Z ES

FWHM 12.0° Efficiency 89 %

Peak intensity 19.800 cd/lm

Required components:






PHOTOMETRIC DATA (SIMULATED):

DESCRIPTION DESCRIPTION

LED LUXEON H50-2

FWHM 16.0°
Efficiency 92 %
Peak intensity 8.500 cd/lm
Required components:



MUMILEDS

LED LUXEON T
FWHM 16.0°
Efficiency 92 %
Peak intensity 8.840 cd/lm

Required components:





PRODUCT DATASHEET FA11212 TINA-RS

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDIL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDIL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Local sales and technical support

www.ledil.com/ where_to_buy

Shipping locations

Salo, Finland Hong Kong, China

Distribution Partners

www.ledil.com/ where_to_buy