



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Specification Sheet

Part Number: FCLC



Connector, Fiber Optic LC Multimode 900µm (Beige) Simplex (BTW)–Epoxy & Polish

Article Number	855-14200
Type	FCLC
Color	Beige (BGE)
Features & Benefits	<ul style="list-style-type: none">• Use with epoxy or anaerobic adhesives for different applications or user preference.• Pre-radiused zirconia ceramic ferrules provide precision installation.• Meet ANSI/TIA/EIA 568-C standards.• Meet ANSI/TIA/EIA 604 (FOCIS) connector interface requirements.
Quantity Per	bag

Product Description

Our epoxy/anaerobic connectors are designed for field or factory installation, using either epoxy or anaerobic adhesives. These connectors are made with pre-radiused zirconia ceramic ferrules to provide precision alignment and installation. Epoxy adhesives provide affordable and reliable connections with lowest losses (less than 0.5dB). The epoxy can be allowed to set overnight or cured in an inexpensive oven. Anaerobic adhesives can be used with accelerators for faster curing

Short Description	Connector, Fiber Optic LC Multimode 900µm (Beige) Simplex (BTW)–Epoxy & Polish
Global Part Name	FCLC
Technical Description	LC Multimode Fiber Connector, Beige
Port Count	1
Package Quantity(Imperial)	1
Package Quantity (Metric)	1
Customs Number	8536700000