imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



AC AXIAL FAN

FDA2-28080-SF Series

RoHS 1




Features:


- Motor: External Rotor Capacitor-Run Induction Motor
- Motor Protection: Thermal Protected
- Bearing Type: Two Ball
- Connection: Terminal Block
- Frame Material: Aluminum Alloy
- Impeller Material: Steel
- Salt Fog Rated GR-487-CORE, ASTM B117-11, ISO 9227 Compliant
- IP56M Certified
- Operating Temp:
 - Two Ball: -20°C~70°C
- Life Expectancy:
- Two Ball: 70,000 Hours

X. 1	
	_
	E

Fan-S Division												
Model No.	Volt.	Freq.	Current	Power	Rated Speed		Maximum Maximum Static AirFlow Pressure		Noise Level	Weight		
	(VAC)	(Hz)	(A)	(W)	(rpm)	(CMM)	(CFM)	(InAq)	(mmAq)	(dB/A)	(g)	
FDA2-28080NBHK4F-SF	115	50/60	0.81/1.20	94.0/136.0	2650/2900	29.15/32.55	1030/1150	0.925/0.807	23.5/20.5	70.0/73.0	3050	
FDA2-28080QBHK4F-SF	230	50/60	0.43/0.63	95.0/138.0	2650/2900	29.15/32.55	1030/1150	0.925/0.807	23.5/20.5	70.0/73.0	3050	

Noise is measured at the distance of one (1) meter from the axis of intake. Rotation direction





Air flow ი 208.9× Ø290 ± 0. aiaiai o \emptyset 4.4 ± 0.2 (8X) Ø5.4 ± 0.2 (4X) Ø295 ± 0.3 80 ± 0.5 Ø320



7

ISO-9001 Company