



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Features:

- Motor: Brushless DC
- Motor Protection: IC
- Bearing Type: Two Ball
- Connection: UL 1007 AWG 22, 360mm Wire Leads
- Frame Material: Aluminum Alloy
- Impeller Material: Steel
- Operating Temp:
Two Ball: -20°C~70°C
- Life Expectancy:
Two Ball: 50,000 Hours
Two Ball: 100,000 Hours (-L)



Fan-S Division



Model No.	Volt.	Current	Power	Rated Speed	Maximum AirFlow		Maximum Static Pressure		Noise Level	Weight
	(VDC)	(A)	(W)	(rpm)	(CMM)	(CFM)	(InAq)	(mmAq)	(dB/A)	(g)
FDD1-17238CBAW4 * #	12	1.10	13.20	2800	5.95	210	0.571	14.5	52.0	880
FDD1-17238CBLW4 * #	12	1.59	19.08	3200	6.94	245	0.732	18.6	56.0	880
FDD1-17238CBMW4 * #	12	2.34	28.08	3600	7.79	275	0.909	23.1	60.0	880
FDD1-17238CBHW4 * #	12	3.33	39.96	4000	8.78	310	1.122	28.5	64.0	880
FDD1-17238DBAW4 * #	24	0.54	12.96	2800	5.95	210	0.571	14.5	52.0	880
FDD1-17238DBLW4 * #	24	0.78	18.72	3200	6.94	245	0.732	18.6	56.0	880
FDD1-17238DBMW4 * #	24	1.08	25.92	3600	7.79	275	0.909	23.1	60.0	880
FDD1-17238DBHW4 * #	24	1.38	33.12	4000	8.78	310	1.122	28.5	64.0	880
FDD1-17238DBJW4 * #	24	1.91	45.84	4400	9.63	340	1.315	33.4	68.0	880
FDD1-17238DBKW4 * #	24	2.34	56.16	4800	10.20	360	1.543	39.2	72.0	880
FDD1-17238EBAW4 * #	48	0.28	13.44	2800	5.95	210	0.571	14.5	52.0	880
FDD1-17238EBLW4 * #	48	0.37	17.76	3200	6.94	245	0.732	18.6	56.0	880
FDD1-17238EBMW4 * #	48	0.52	24.96	3600	7.79	275	0.909	23.1	60.0	880
FDD1-17238EBHW4 * #	48	0.68	32.64	4000	8.78	310	1.122	28.5	64.0	880
FDD1-17238EBJW4 * #	48	0.90	43.20	4400	9.63	340	1.315	33.4	68.0	880
FDD1-17238EBKW4 * #	48	1.13	54.24	4800	10.20	360	1.543	39.2	72.0	880

* Indicates "2" (No Special Function), "3" (Alarm), "4" (Speed Sensor), "9" (PWM), "B" (PWM + Speed Sensor) or "C" (Alarm + Speed Sensor)

Indicates "-L" (100,000 Hours Life Expectancy) or Leave Blank (50,000 Hours Life Expectancy)

Noise is measured at the distance of one (1) meter from the axis of intake.

