

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









## FIT® Shelf Life Guide

Below you will find the shelf lives for all of our FIT Heat-Shrink Tubing products and select Wire Management products.

## Products not listed below do not have a specified or documented shelf life.

Please Note: The storage temperature range for all of these products is 65°F-95°F.

<sup>\*</sup>Shelf lives are based upon manufacturer's recommendations

| Product Type    | Shrink<br>Ratio | Material Type   | Shelf Life (Yrs)  |
|-----------------|-----------------|-----------------|-------------------|
| FIT-105         | 2:1             | PVC             | 1                 |
| FIT-221         | 2:1             | Polyolefin      | 5                 |
| FIT-221B        | 2:1             | Polyolefin      | 5                 |
| FIT-221V        | 2:1             | Polyolefin      | 5                 |
| FIT-260         | 2:1             | Polyolefin      | 25                |
| FIT-295         | 2:1             | Polyolefin      | 5                 |
| FIT-300         | 3:1             | Polyolefin      | 3                 |
| FIT-321         | 3:1             | Polyolefin      | 3                 |
| FIT-321V        | 3:1             | Polyolefin      | 25                |
| FIT-350         | 2:1             | PVDF            | 5                 |
| FIT-375         | 2:01            | PVDF, Modified  | 5                 |
| FIT-400         | 1.2:1           | FEP             | 4                 |
| FIT-500         | 1.5:1           | TFE             | 4                 |
| FIT-600         | 1.75:1          | Neoprene        | 1                 |
| FIT-621         | 6:1             | Polyolefin      | 25                |
| FIT-650         | 2:1             | Fluoroelastomer | 2                 |
| FIT-700         | 3:1             | Polyolefin      | 25                |
| FIT-750         | 2:1             | Polyolefin      | 3                 |
| FIT-CAP         | 2:1             | Polyolefin      | 25                |
| FIT-CRIMP       | 2:1             | Nylon           | 25                |
| FIT-FAB         | 2:1             | Polyester       | 25                |
| FIT-FLEX        | 1.7:1           | Silicone        | 25                |
| FIT-PRINT       | 3:1             | Polyolefin      | 3                 |
| FIT-RP          | 3:1             | Polyolefin      | 25                |
| FIT-SLV-(12-16) |                 | PVDF            | 25                |
| FIT-SLV-(22-26) |                 | PVDF            | 5                 |
| CST*            |                 | Cu & Adhesive   | 2                 |
| Lacing Cords*   |                 | Various         | 1yr after opening |
| TY2001          |                 | Silicon         | 1                 |