



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





# FGA25N120FTD

## 1200 V, 25 A Field Stop Trench IGBT

### Features



- Field Stop Trench Technology
- High Speed Switching
- Low Saturation Voltage:  $V_{CE(sat)} = 1.6\text{ V @ } I_C = 25\text{ A}$
- High Input Impedance
- RoHS Compliant

### Applications

- Induction Heating, Microwave Oven

### General Description

Using advanced field stop trench technology, Fairchild®'s 1200V trench IGBTs offer superior conduction and switching performances for soft switching applications. The device can operate in parallel configuration with exceptional avalanche ruggedness. This device is designed for induction heating and microwave oven.



### Absolute Maximum Ratings

| Symbol      | Description   | Ratings     | Unit             |
|-------------|---|-------------|------------------|
| $V_{CES}$   | Collector to Emitter Voltage  | 1200        | V                |
| $V_{GES}$   | Gate to Emitter Voltage   | $\pm 25$    | V                |
| $I_C$       | Collector Current @ $T_C = 25^\circ\text{C}$                            | 50          | A                |
|             | Collector Current @ $T_C = 100^\circ\text{C}$                           | 25          | A                |
| $I_{CM(1)}$ | Pulsed Collector Current  | 75          | A                |
| $I_F$       | Diode continuous Forward current @ $T_C = 100^\circ\text{C}$            | 25          | A                |
| $P_D$       | Maximum Power Dissipation @ $T_C = 25^\circ\text{C}$                    | 313         | W                |
|             | Maximum Power Dissipation @ $T_C = 100^\circ\text{C}$                   | 125         | W                |
| $T_J$       | Operating Junction Temperature  | -55 to +150 | $^\circ\text{C}$ |
| $T_{stg}$   | Storage Temperature Range   | -55 to +150 | $^\circ\text{C}$ |
| $T_L$       | Maximum Lead Temp. for soldering Purposes, 1/8" from case for 5 seconds | 300         | $^\circ\text{C}$ |

**Notes:**

1: Repetitive: Pulse width limited by max. junction temperature

### Thermal Characteristics

| Symbol                        | Parameter                               | Typ. | Max. | Unit               |
|-------------------------------|---|------|------|--------------------|
| $R_{\theta JC}(\text{IGBT})$  | Thermal Resistance, Junction to Case    | -    | 0.4  | $^\circ\text{C/W}$ |
| $R_{\theta JC}(\text{Diode})$ | Thermal Resistance, Junction to Case    | -    | 1.42 | $^\circ\text{C/W}$ |
| $R_{\theta JA}$               | Thermal Resistance, Junction to Ambient | -    | 40   | $^\circ\text{C/W}$ |

## Package Marking and Ordering Information

| Device Marking | Device         | Package | Packaging Type | Qty per Tube | Max Qty per Box |
|----------------|----------------|---------|----------------|--------------|-----------------|
| FGA25N120FTD   | FGA25N120FTDTU | TO-3PN  | -              | -            | 30              |

## Electrical Characteristics of the IGBT T<sub>C</sub> = 25°C unless otherwise noted

| Symbol                           | Parameter                               | Test Conditions   | Min. | Typ. | Max. | Unit |
|----------------------------------|---|---|------|------|------|------|
| <b>Off Characteristics</b>       |   |   |      |      |      |      |
| V <sub>CES</sub>                 | Collector to Emitter Breakdown Voltage  | V <sub>GE</sub> = 0V, I <sub>C</sub> = 1mA  | 1200 | -    | -    | V    |
| I <sub>CES</sub>                 | Collector Cut-Off Current               | V <sub>CE</sub> = V <sub>CES</sub> , V <sub>GE</sub> = 0V   | -    | -    | 1    | mA   |
| I <sub>GES</sub>                 | G-E Leakage Current                     | V <sub>GE</sub> = V <sub>GES</sub> , V <sub>CE</sub> = 0V   | -    | -    | ±250 | nA   |
| <b>On Characteristics</b>        |   |   |      |      |      |      |
| V <sub>GE(th)</sub>              | G-E Threshold Voltage                   | I <sub>C</sub> = 25mA, V <sub>CE</sub> = V <sub>GE</sub>  | 3.5  | 6    | 7.5  | V    |
| V <sub>CE(sat)</sub>             | Collector to Emitter Saturation Voltage | I <sub>C</sub> = 25A, V <sub>GE</sub> = 15V   | -    | 1.6  | 2    | V    |
|                                  |   | I <sub>C</sub> = 25A, V <sub>GE</sub> = 15V,<br>T <sub>C</sub> = 125°C  | -    | 1.88 | -    | V    |
| <b>Dynamic Characteristics</b>   |   |   |      |      |      |      |
| C <sub>ies</sub>                 | Input Capacitance                       | V <sub>CE</sub> = 30V, V <sub>GE</sub> = 0V,<br>f = 1MHz  | -    | 3830 | -    | pF   |
| C <sub>oes</sub>                 | Output Capacitance                      |   | -    | 130  | -    | pF   |
| C <sub>res</sub>                 | Reverse Transfer Capacitance            |   | -    | 86   | -    | pF   |
| <b>Switching Characteristics</b> |   |   |      |      |      |      |
| t <sub>d(on)</sub>               | Turn-On Delay Time                      | V <sub>CC</sub> = 600V, I <sub>C</sub> = 25A,<br>R <sub>G</sub> = 15Ω, V <sub>GE</sub> = 15V,<br>Inductive Load, T <sub>C</sub> = 25°C  | -    | 48   | -    | ns   |
| t <sub>r</sub>                   | Rise Time                               |   | -    | 96   | -    | ns   |
| t <sub>d(off)</sub>              | Turn-Off Delay Time                     |   | -    | 210  | -    | ns   |
| t <sub>f</sub>                   | Fall Time                               |   | -    | 215  | -    | ns   |
| E <sub>on</sub>                  | Turn-On Switching Loss                  |   | -    | 0.34 | -    | mJ   |
| E <sub>off</sub>                 | Turn-Off Switching Loss                 |   | -    | 0.90 | 1.20 | mJ   |
| E <sub>ts</sub>                  | Total Switching Loss                    | -   | 1.24 | -    | mJ   |      |
| t <sub>d(on)</sub>               | Turn-On Delay Time                      | V <sub>CC</sub> = 600V, I <sub>C</sub> = 25A,<br>R <sub>G</sub> = 15Ω, V <sub>GE</sub> = 15V,<br>Inductive Load, T <sub>C</sub> = 125°C | -    | 44   | -    | ns   |
| t <sub>r</sub>                   | Rise Time                               |   | -    | 113  | -    | ns   |
| t <sub>d(off)</sub>              | Turn-Off Delay Time                     |   | -    | 232  | -    | ns   |
| t <sub>f</sub>                   | Fall Time                               |   | -    | 390  | -    | ns   |
| E <sub>on</sub>                  | Turn-On Switching Loss                  |   | -    | 0.38 | -    | mJ   |
| E <sub>off</sub>                 | Turn-Off Switching Loss                 |   | -    | 1.39 | -    | mJ   |
| E <sub>ts</sub>                  | Total Switching Loss                    | -   | 1.77 | -    | mJ   |      |
| Q <sub>g</sub>                   | Total Gate Charge                       | V <sub>CE</sub> = 600V, I <sub>C</sub> = 25A,<br>V <sub>GE</sub> = 15V  | -    | 160  | -    | nC   |
| Q <sub>ge</sub>                  | Gate to Emitter Charge                  |   | -    | 30   | -    | nC   |
| Q <sub>gc</sub>                  | Gate to Collector Charge                |   | -    | 78   | -    | nC   |

**Electrical Characteristics of the Diode**  $T_C = 25^\circ\text{C}$  unless otherwise noted

| Symbol   | Parameter                     | Test Conditions   | Min.                      | Typ. | Max  | Unit |               |
|----------|-------------------------------|---|---------------------------|------|------|------|---------------|
| $V_{FM}$ | Diode Forward Voltage         | $I_F = 25\text{A}$  | $T_C = 25^\circ\text{C}$  | -    | 1.4  | 1.8  | V             |
|          |                               |   | $T_C = 125^\circ\text{C}$ | -    | 1.42 | -    |               |
| $t_{rr}$ | Diode Reverse Recovery Time   | $I_{ES} = 25\text{A}, dI_{ES}/dt = 200\text{A}/\mu\text{s}$ | $T_C = 25^\circ\text{C}$  | -    | 770  | -    | ns            |
|          |                               |   | $T_C = 125^\circ\text{C}$ | -    | 895  | -    |               |
| $I_{rr}$ | Diode Reverse Recovery Time   | $I_{ES} = 25\text{A}, dI_{ES}/dt = 200\text{A}/\mu\text{s}$ | $T_C = 25^\circ\text{C}$  | -    | 48   | -    | A             |
|          |                               |   | $T_C = 125^\circ\text{C}$ | -    | 50   | -    |               |
| $Q_{rr}$ | Diode Reverse Recovery Charge | $I_{ES} = 25\text{A}, dI_{ES}/dt = 200\text{A}/\mu\text{s}$ | $T_C = 25^\circ\text{C}$  | -    | 18   | -    | $\mu\text{C}$ |
|          |                               |   | $T_C = 125^\circ\text{C}$ | -    | 23   | -    |               |

## Typical Performance Characteristics

Figure 1. Typical Output Characteristics




Figure 2. Typical Output Characteristics




Figure 3. Typical Saturation Voltage Characteristics




Figure 4. Transfer Characteristics




Figure 5. Saturation Voltage vs. Case Temperature at Variant Current Level





Figure 6. Saturation Voltage vs. Vge



## Typical Performance Characteristics

Figure 7. Saturation Voltage vs.  $V_{GE}$




Figure 8. Capacitance Characteristics




Figure 9. Gate charge Characteristics




Figure 10. SOA Characteristics




Figure 11. Turn-on Characteristics vs. Gate Resistance






Figure 12. Turn-off Characteristics vs. Gate Resistance




## Typical Performance Characteristics


**Figure 13. Turn-on Characteristics vs. Collector Current**




**Figure 14. Turn-off Characteristics vs. Collector Current**




**Figure 15. Switching Loss vs. Gate Resistance**




**Figure 16. Switching Loss vs. Collector Current**



**Figure 17. Turn off Switching SOA Characteristics**



**Figure 18. Forward Characteristics**



## Typical Performance Characteristics

Figure 19. Reverse Recovery Current




Figure 20. Stored Charge




Figure 21. Reverse Recovery Time






Figure 22. Transient Thermal Impedance of IGBT



Mechanical Dimensions

TO-3PN



Dimensions in Millimeters



### TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

|  |   |   |  |
|--|---|---|--|
| 2Cool™   | FPS™  |   | Sync-Lock™   |
| AccuPower™   | F-PFS™  |   |  SYSTEM GENERAL®* |
| AX-CAP®*   | FRFET®  | PowerTrench®  | TinyBoost™   |
| BitSiC™  | Global Power Resource <sup>SM</sup>             | PowerXS™  | TinyBuck™  |
| Build it Now™  | Green Bridge™                                   | Programmable Active Droop™  | TinyCalc™  |
| CorePLUS™  | Green FPS™                                      | QFET®   | TinyLogic®   |
| CorePOWER™   | Green FPS™ e-Series™                            | QS™   | TINYOPTO™  |
| CROSSVOLT™   | Gmax™   | Quiet Series™   | TinyPower™   |
| CTL™   | GTO™  | RapidConfigure™   | TinyPWM™   |
| Current Transfer Logic™  | IntelliMAX™                                     |  Saving our world, 1mW/W/kW at a time™ | TinyWire™  |
| DEUXPEED®  | ISOPLANAR™                                      | SignalWise™   | TranSic®   |
| Dual Cool™   | Marking Small Speakers Sound Louder and Better™ | SmartMax™   | TriFault Detect™   |
| EcoSPARK®  | MegaBuck™                                       | SMART START™  | TRUECURRENT®*  |
| EfficientMax™  | MICROCOUPLER™                                   | Solutions for Your Success™   | µSerDes™   |
| ESBC™  | MicroFET™                                       | SPM®  |  SerDes™          |
|  Fairchild® | MicroPak™                                       | STEALTH™  | UHC®   |
| Fairchild Semiconductor®   | MicroPak2™                                      | SuperFET®   | Ultra FRFET™   |
| FACT Quiet Series™   | MillerDrive™                                    | SuperSOT™_3   | UniFET™  |
| FACT®  | MotionMax™                                      | SuperSOT™_6   | VCM™   |
| FAST®  | mWSaver™  | SuperSOT™_8   | VisualMax™   |
| FastvCore™   | OptoHiT™  | SupreMOS®   | VoltagePlus™   |
| FETBench™  | OPTOLOGIC®                                      | SyncFET™  | XS™  |
|  | OPTOPLANAR®                                     |   |  |

\*Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

### DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY A LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

### LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used here in:

- Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
- A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

### ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, [www.fairchildsemi.com](http://www.fairchildsemi.com), under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed application, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address and warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

### PRODUCT STATUS DEFINITIONS

#### Definition of Terms

| Datasheet Identification | Product Status        | Definition  |
|--------------------------|-----------------------|---|
| Advance Information      | Formative / In Design | Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.   |
| Preliminary              | First Production      | Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design. |
| No Identification Needed | Full Production       | Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.   |
| Obsolete                 | Not In Production     | Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.  |

Rev. I64