



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





2 x 18650 Battery Holder with DC2.1 Power Jack

SKU:FIT0538

INTRODUCTION

The 18650 lithium battery is a commonly used lithium battery in electronic products. It is often used in batteries of laptop computers and power banks. 18650, which refers to a battery with a diameter of 18mm and a length of 65mm.

This 2 x 18650 battery holder has inner connection in series, DC 2.1 power jack, standard 7.4V output. You can connect Arduino directly.



FEATURES

- ABS shell
- The spring plate is nickel plated with stainless steel.
- The material structure is firm and durable.

SPECIFICATION

- RoHs Certification
- Battery Model: 18650
- Cell number: 2
- Output Voltage: 7.4 V
- Plug form: DC 2.1 (outer diameter 5.5, inner diameter 2.1)
- Size: 77.9 x 40.11 x 21.41 mm/ 3.07 x 1.58 x 0.84 inches
- Weight: 15.5 g

SHIPPING LIST

2 x 18650 Battery Holder with DC2.1 Power Jack x1