



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



ExStik[®] Waterproof Fluoride Meter

Direct reading of Fluoride down to 0.1ppm

With Automatic Temperature Compensation (ATC)

Features:

- First Fluoride meter with built-in Automatic Temperature Compensation
 - Fastest response Fluoride meter (<1min)
 - Easy use for Field or Laboratory fluoride testing
 - Small sample/TISAB volume required for testing (10mL)
 - In compliance with EPA Method 340.2.(Potentiometric Ion Selective Electrode)
 - Automatic electronic 1 or 2 point calibration with offset adjustment
 - Memory stores 25 labeled readings
 - Waterproof to IP57
 - Large LCD simultaneously displays ppm of Fluoride, Temperature, and analog bargraph indicator
 - Complete with electrode, TISAB reagent tablets, sensor cap, four 3V button batteries, and 48" (1.2m) neckstrap
- Contact Extech or your local lab supply for Fluoride calibration standards



Flat Surface Fluoride electrode with built-in Automatic Temperature Compensation (ATC)



Applications:

- Public Water Fluoridation Control — Fluoride is known to help prevent tooth decay while too much fluoride is known to be bad for the teeth
- The concentration recommended by the American Dental Association is 0.7-1.2 ppm.
- The MCL established by the EPA is 4.0 ppm
- Fluoride is naturally occurring and in some areas in the US the natural level exceeds 4.0 ppm



Accessories:

- FL704** TISAB reagent tablets for FL700 Fluoride Meter (100 tablets)
- CA895** Small case with belt loop for your ExStik Meter

Specifications	Range	Max. Resolution	Basic Accuracy
ppm	0.1 to 10ppm	0.1ppm	±3% rdg
Temperature	32 to 140°F (0 to 60°C)	0.1°F/°C	±1.8°F/1°C
Dimensions	1.4x6.8x1.6" (36x173x41mm)		
Weight	7.4oz (210g)		

Ordering Information:

- FL700**ExStik[®]II Waterproof Fluoride Meter
- FL705**Replacement Fluoride Electrode module for FL700
- FL704**TISAB Reagent Tablets (100 tablets)
- CA895**Small vinyl carrying case with belt loop

