



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



SUMMARY

Wires

| | |
|---------|---|
| Low | 0 |
| High | 0 |
| Coax | 1 |
| Triax | 0 |
| Quad | 0 |
| Fiber | 0 |
| Fluidic | 0 |

| | |
|------------------|----------------|
| Series | 00 |
| Termination type | Male solder |
| IP rating | 50 |
| Cable Ø | 3.10 - 4.00 mm |
| Matching parts | ERA.00.250.CTL |
| Status | |
| Alternative part | |



Image is for illustrative purpose only

Download

[Request a quote](#)

[Catalog](#)

TECHNICAL DETAILS

Mechanics

| | |
|-------------------|---|
| Shell Style/Model | FLA/D*: Elbow plug with oversize cable collet |
| Keying | Circular (can rotate) |
| Housing Material | Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces |
| Cable Fixing | D42: 3.1 - 4 mm |
| Variant | |

Performance

| | |
|---------------|------------------------|
| Configuration | 0.25 : 1 Coax (50 Ohm) |
| Insulator | T: PTFE |
| Rated Current | 4 Amps |

Specifications

| |
|---------------------------------------|
| Contact Type: Coaxial 50 Ohm (Solder) |
| Max. Matings: 5000 |
| Contact Dia.: 0.7 mm (0.028in) |
| Bucket Dia.: 0.6 mm (0.024in) |
| Test voltage: 2.1 kV (rms) |
| R (max): 6.1 mOhm |

Vtest: 2100 V (AC), 3000 V (DC)

□

Impedance: 50 Ohm

VSWR: $1.09 + 0.11 * f/\text{GHz}$

Cable type: RG 195 A/U

Others

Endurance (Shell): 5000 mating cycles

F ret (min): 100 N

IP Rating: 50

DRAWINGS

Draws



Dimensions

| | A | D | H | L | M | S2 | S3 |
|-----|------|------|------|------|------|------|------|
| mm. | 9 | 8.6 | 24 | 17.5 | 9.5 | 7 | 8 |
| in. | 0,35 | 0,34 | 0,94 | 0,69 | 0,37 | 0,28 | 0,31 |

RECOMMENDED BY LEMO

Tools

Spanner wrench: DCD.00.003.PA050

Cables