

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









+

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.






| PANDUIT PART NUMBER | FIBER TYPE |
|---------------------------------------|------------------------|
| FLCSMC5* ¹ ** ² | 50/125um MULTIMODE |
| FLCSMC6*1**2 | 62.5/125um MULTIMODE |
| FLCSMCX* ¹ ** ² | 50/125um OM3 MULTIMODE |
| FLCSSC* ¹ ** ² | 9/125um SINGLEMODE |

* ALPHA KEY DESIGNATOR (SEE TABLE 2, SHEET 2)

** KEY COLOR DESIGNATOR (SEE TABLE 2, SHEET 2)

NOTES:

- 1. SEE CATALOG FOR ADDITIONAL PART NUMBER SUFFIXES TO INDICATE COLOR AND/OR PACKAGE QUANTITY.
- 2. ACCEPTS 50/125um, 62.5/125um, 50/125 OM3
 MULTIMODE OR 9/125um SINGLEMODE 900um
 BUFFERED GLASS OPTICAL FIBER.
- 3. FULLY COMPLIES WITH THE FIBER OPTIC CONNECTOR PERFORMANCE REQUIREMENTS AS SPECIFIED BY TIA/EIA-568-B.3.
- 4. MATERIAL:
 BODY/HARDWARE: PLASTIC
 BOOT: THERMOPLASTIC RUBBER
 FERRULE: ZIRCONIA CERAMIC
- 5. ALL MATERIALS AND COMPONENTS USED MEET THE MATERIAL RESTRICTIONS OF ROHS, (EUROPEAN DIRECTIVE 2002/95/EC ON THE RESTRICTION OF HAZARDOUS SUBSTANCES) AS PROPOSED BY THE ROHS TECHNICAL ADAPTATION COMMITTEE.
- 6. DIMENSIONS IN BRACKETS ARE METRIC [mm].



| | | | | | | | | | | KEYED | KEYED OPTICAM SIMPLEX LC CONNECTOR CUSTOMER DRAWING | | | | |
|-----|----------|----|-----|------------------------|----------|---|------|-----|-----|------------------------|--|---|--|--|--|
| | | | | | | | | | | THIRD ANGLE PROJECTION | UNLESS OTHERWISE SPECIFIED. DIMENSIONAL TOLERANCES ARE: (.XX) (.XXX) 2.010 [0.3] (.XX) 2.03 [0.8] ANGLES | DRAWING FILENAME M02759AB_DC_SIM_00B.prt SCALE NONE | | | |
| | | | | | | | | | | MC | I STATE OF THE PROPERTY OF THE | SEE SHEET 2 | | | |
| 1 | 03-19-08 | МС | | RELEASED TO PRODUCTION | 02759-09 | | | | | 12-04-07 | | 02759-09 SIZE | | | |
| REV | DATE | BY | CHK | DESCRIPTION | ECN - | R | CUST | SUP | отн | CHK,D b7I | | (SHT. 1 of 2) | | | |

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

| TABLE 2 - KEYED LC CONNECTOR PART NUMBER AND HOUSING KEY CONFIGURATIONS | | | | | | | | | | |
|---|---|---|---|---|---|--|--|--|--|--|
| KEY: -A- | KEY: -B- | KEY: -C- | KEY: -D- | KEY: -E- | KEY: -F- | | | | | |
| MULTIMODE CONNECTOR P/N: FLCSMC*ABL | MULTIMODE CONNECTOR P/N: FLCSMC*BRD | MULTIMODE CONNECTOR P/N: FLCSMC*CGR | MULTIMODE CONNECTOR P/N: FLCSMC*DYL | MULTIMODE CONNECTOR P/N: FLCSMC*EOR | MULTIMODE CONNECTOR P/N: FLCSMC*FDB | | | | | |
| SINGLEMODE CONNECTOR P/N: FLCSSCABL | SINGLEMODE CONNECTOR P/N: FLCSSCBRD | SINGLEMODE CONNECTOR P/N: FLCSSCCGR | SINGLEMODE CONNECTOR P/N: FLCSSCDYL | SINGLEMODE CONNECTOR P/N: FLCSSCEOR | SINGLEMODE CONNECTOR P/N: FLCSSCFDB | | | | | |
| COLOR: BLACK | COLOR: RED | COLOR: GREEN | COLOR: YELLOW | COLOR: ORANGE | COLOR: DARK | | | | | |
| | | | | | | | | | | |

* - DESIGNATES MULTIMODE FIBER TYPE (SEE TABLE 1, SHEET 1)

| | | | | | | | | | | KEYED | KEYED OPTICAM SIMPLEX LC CONNECTOR CUSTOMER DRAWING | | | | |
|-----|----------|----|-----|------------------------|----------|---|------|-----|-----|---------------------------|---|---------------|------|--|--|
| | | | | | | | | | | | TINLEY PARK, ILL 60477 ALL DIMENSIONS ARE GIVEN IN INCHES UNLESS OTHERWISE SPECIFIED. DIMENSIONAL TOLERANCES ARE: DIMENSIONAL TOLERANCES ARE: | | | | |
| | | | | | | | | | | THIRD ANGLÉ PROJECTION | (.XX) (.XXX)±.010 (0.3) | NONE | | | |
| | | | | | | | | | | MC MC | REVIEW DRAWING NUMBERS | SEE TAB | LE 2 | | |
| R | 03-19-08 | мС | | RELEASED TO PRODUCTION | 02759-09 | | | | | 12-04-07 | | 02759 - 09 | SIZE | | |
| REV | DATE | BY | СНК | DESCRIPTION | ECN - | R | CUST | SUP | отн | CHK'D PJI | | (SHT. 2 of 2) | A | | |