



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





FLIR C2

Powerful, Compact Thermal Imaging System

The FLIR C2 is the world's first full-featured, pocket-sized thermal camera designed for building industry experts and contractors. Keep it on you so you're ready anytime to find hidden heat patterns that signal energy waste, structural defects, plumbing issues and more. The C2's must-have features include MSX® real time image enhancement, high sensitivity, a wide field of view, and fully radiometric imagery to clearly show where problems are and verify the completion of repairs.

Pocket Portable.

Keep it on you and at your side, ready for immediate use so you don't miss an opportunity

- Light, slim profile fits comfortably in any work pocket
- Brilliant 3" intuitive touch screen with auto orientation for easy viewing
- Built-in LED spotlight you can use as a flashlight and for photo illumination

Fully Radiometric.


Save thermal image JPEGs instantly, then conveniently adjust and analyze them later with FLIR Tools to isolate temperature measurements on any pixel and create convincing reports

- MSX-enhanced thermal images provide stunning detail to help you identify problem areas easier
- Radiometric image stores 4800 pixels capable of capturing thermal measurements from -10°C to 150°C
- A wide FOV frames what pros need to see and high thermal sensitivity detects subtle temperature differences common in building applications

Easily Affordable.

Sub-\$700 MSRP fits everyone's budget to help put this powerful tool into the hands of more people who can really use it


- FLIR Tools professional reporting software included – the industry standard in thermal image post analysis
- Streaming video via FLIR Tools, a feature not usually available on low-cost thermal camera systems
- FLIR's unique 2-10 warranty, covering parts and labor for two years and the detector for ten



Hot Overloaded Dimmer Switch



Warm Drain Pipe in Wall



Uninsulated Outside Wall

Imaging Specifications

Imaging and Optical Data	
IR sensor	80 × 60 (4,800 measurement pixels)
Thermal Sensitivity	<0.10°C
Field of view	41° × 31°
Minimum focus distance	Thermal: 0.15 m (0.49 ft.) MSX: 1.0 m (3.3 ft.)
Image frequency	9 Hz
Focus	Focus free
Spectral range	7.5–14 μm
3" Display (color)	320 × 240 pixels
Auto orientation	Yes
Touch screen	Yes, capacitive
Image presentation modes	
Thermal image	Yes
Visual image	Yes
MSX	Yes
Gallery	Yes
Measurement	
Object temperature range	-10°C to +150°C (14 to 302°F)
Accuracy	±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal
Measurement Analysis	
Spotmeter	On/off
Emissivity correction	Yes; matte/semi/glossy + user set
Measurements correction	Reflected apparent temperature Emissivity
Set-up	
Color palettes	Iron, Rainbow, Rainbow HC, Gray
Storage media	Internal memory stores at least 500 sets of images
Image file format	Standard JPEG, 14-bit measurement data included
Video Streaming	
Non-radiometric IR-video streaming	Yes
Visual video streaming	Yes
Digital Camera	
Digital camera	640 × 480 pixels
Digital camera, focus	Fixed focus
Additional Information	
USB, connector type	USB Micro-B: Data transfer to and from PC, iOS and Android
Battery	3.7 V Rechargeable Li-ion polymer battery
Battery operating time	2 h
Charging system	Charged inside the camera
Charging time	1.5 h
External power operation	AC adapter, 90–260 VAC input 5 V output to camera
Power management	Automatic shut-down
Operating temperature range	-10°C to +50°C (14 to 122°F)
Storage temperature range	-40°C to +70°C (-40 to 158°F)
Weight (incl. Battery)	0.13 kg (0.29 lb.)
Size (L × W × H)	125 × 80 × 24 mm (4.9 × 3.1 × 0.94 in.)
System Includes	
Infrared camera Battery (inside camera) Lanyard Power supply/charger with EU, UK, US, CN and Australian plugs Printed Getting Started Guide USB memory stick with documentation USB cable	



Covers parts and labor for two years and the detector for ten.

USA-NASHUA
FLIR Systems, Inc.
9 Townsend West
Nashua, NH 03063
USA
PH: +1 866.477.3687

USA-PORTLAND
Corporate Headquarters
FLIR Systems, Inc.
27700 SW Parkway Ave.
Wilsonville, OR 97070
USA
PH: +1 866.477.3687

EUROPE
FLIR Systems
Luxemburgstraat 2
2321 Meer
Belgium
PH: +32 (0) 3665 5100

CHINA-SHANGHAI
FLIR Systems Co., Ltd.
K301-302, No 26 Lane
168, Daduhe Road,
Putuo District, Shanghai
200062, P.R.China
PH: +86-21-5169 7628

www.flir.com
NASDAQ: FLIR

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2014 FLIR Systems, Inc. All rights reserved. (Created 11/14)