## imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us


Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## KEMET Part Number: FLLD3075AMHT5



## KEMET, FLLD3-MH, EMI Filters, Three Phase, 530 VAC, 75 A, 240x80x135mm



General Information		
Series:	FLLD3-MH	
Style:	Chassis Mount	
Description:	EMI Filter, Chassis Mount, Motor Drives	
Features:	High Performance	
RoHS:	Yes	
Qualifications:	IEC/EN 60939, UL 1283	

Dimensions		
L	240mm NOM	
W	80mm NOM	
Н	135mm NOM	
L1	255mm NOM	
L2	270mm NOM	
W1	60mm NOM	
J	70mm NOM	
К	6.5mm NOM	
M (Earth)	Threaded Studs M6	

Voltage AC:	530/305 VAC
Rated Frequency:	50-60 Hz
Ripple Current:	75 A (50C)
Rated Temperature:	50C
Temperature Range:	-25/+100C
Climate Category:	25/100/21
Test Voltage DC (P to P):	2250 VDC
Test Voltage DC (P to E):	3000 VDC
Power Loss:	30 W (25C 50 Hz)
Leakage Current:	4.7 mA

**Specifications** 

Packaging Specifications	
Packaging:	Bulk
Packaging Quantity:	1
Weight:	3.2 kg

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

