imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





The Fluke 63 Infrared Thermometer

Non-contact temperature measurement

The professional's diagnostic tool

The Fluke 63 non-contact thermometer is the ideal professional diagnostic tool for quick and accurate temperature measurements. This handheld portable tool enables professionals to research heating and ventilation problems, monitor the status of electrical motors and electrical panels and diagnose car malfunctions with ease.

Features include:


- Expanded measurement range up to 535 °C (999 °F)
- High-resolution optics
- High accuracy: 1 % and repeatability: 0.5 %
- MAX temperature display
- · Laser targeting
- Backlit display

The Fluke 63 thermometer makes troubleshooting quick and easy. The single dot laser sighting system guides measurements to the right target and in less than a second, the large temperature display provides current and MAX surface temperatures. The locking trigger and tripod mount capability allow for continuous temperature monitoring.

Optical resolution

The single dot laser sighting system guides measurements to the right target and indicates the approximate center of the measurement area.

D:S (distance to spot using 90 % encircled energy at focal point.)



Use the Fluke 63 within six feet of the intended target. At greater distances, the measured area will be larger (approximately the distance divided by 12). The Fluke 63 offset single-point laser indicates the approximate center of the measurement area.

Technical Data





Specifications

Temperature range -32 to $535 \ ^{\circ}C$ (-25 to $999 \ ^{\circ}F$)Accuracy (Assumes ambient operating temperature of $23 \ ^{\circ}C$ ($73 \ ^{\circ}F$) $-32 \ ^{\circ}C \ (-25 \ ^{\circ}C \ -15 \ ^{\circ}C \): \pm 3 \ ^{\circ}C \ (\pm 3 \ ^{\circ}F)$ $-26 \ ^{\circ}C \ (-25 \ ^{\circ}C \): \pm 2 \ ^{\circ}C \ (\pm 3 \ ^{\circ}F)$ $-3 \ ^{\circ}C \ (73 \ ^{\circ}F)$: $\pm 1 \ ^{\circ}O \ ^{\circ}C \ (25 \ ^{\circ}F)$ $-3 \ ^{\circ}C \ (73 \ ^{\circ}F)$: $\pm 1 \ ^{\circ}O \ ^{\circ}C \ (25 \ ^{\circ}F)$ $-3 \ ^{\circ}C \ (\pm 2 \ ^{\circ}F)$ whichever is greater Above $510 \ ^{\circ}C \ (250 \ ^{\circ}F)$: $\pm 1.5 \ ^{\circ}O \ ^{\circ}C \ (25 \ ^{\circ}F)$ $\pm 1.5 \ ^{\circ}O \ ^{\circ}C \ (22 \ ^{\circ}F)$ whichever is greater Above $510 \ ^{\circ}C \ (22 \ ^{\circ}F)$ whichever is greater $Above 510 \ ^{\circ}C \ (250 \ ^{\circ}F): \pm 1.5 \ ^{\circ}O \ ^{\circ}C \ (22 \ ^{\circ}F)whichever is greaterAbove 510 \ ^{\circ}C \ (250 \ ^{\circ}F): \pm 1.5 \ ^{\circ}O \ ^{\circ}C \ (22 \ ^{\circ}F)whichever is greaterAbove 510 \ ^{\circ}C \ (25 \ ^{\circ}F)whichever is greaterAbove 510 \ ^{\circ}C \ (22 \ ^{\circ}F)whichever is greaterAbove 510 \ ^{\circ}C \ (22 \ ^{\circ}F)whichever is greaterAbove 510 \ ^{\circ}C \ (22 \ ^{\circ}F)whichever is greaterAbove 510 \ ^{\circ}C \ (22 \ ^{\circ}C) \ (22 \ ^{\circ}C)F)whichever is greaterAmbient operating temp0 \ 0 \ 50 \ ^{\circ}C \ (22 \ 0 \ 120 \ ^{\circ}F)Relative humidity10 to 90 \ ^{\circ}OStorage temperature-20 \ to \ 60 \ ^{\circ}C \ (-13 \ to \ 158 \ ^{\circ}F) without batteryDimensions200 \ x \ 160 \ x \ 55 \ mm \ (8 \ x \ 6 \ x \ 2 \ m.)Weight320 \ g \ (11 \ oz.)Power9 V alkaline or NiCd batteryBatter life (alkaline)10 hours with laser and backlight on40 \ hours with laser and backlight offTypical distance to targetUp to 2 m \ (6 \ ft.)Display hold (7 seconds)\circC \ or \ ^{\circ}F$		
(Assume's ambient operating temperature of 23 °C [73 °F])-26 to -18 °C (-15 to 0 °F): ± 2.5 °C (± 4 °F) -18 to 23 °C (0 to 73 °F): ± 2 °C (± 3 °F) 23 to 510 °C (73 to 950 °F): $\pm 1.\%$ of reading or ± 1 °C (± 2 °F), whichever is greater Above 510 °C (950 °F): $\pm 1.5\%$ of readingRepeatability $\pm 0.5\%$ or $\leq \pm 1$ °C (± 2 °F), whichever is greater Above 510 °C (950 °F): $\pm 1.5\%$ of reading)Spectral response time8 to 14 µmEmissivityPre-set at 0.95Ambient operating temp Dimensions0 to 50 °C (32 to 120 °F)Relative humidity10 to 90 %Storage temperature 200 x 160 x 55 mm (8 x 6 x 2 in.)Weight320 g (11 oz.)Power9 V alkaline or NiCd batteryBatter life (alkaline)10 hours with laser and backlight on 40 hours with laser and backlight offTypical distance to target Display hold (7 seconds)•LCD backlit•Temperature display°C or °F selectableDisplay resolution0.2 °C (0.5 °F)Hard carrying case Tripod mounting•	Temperature range	-32 to 535 °C (-25 to 999 °F)
Response time $\leq 0.5 \text{ second } (95\% \text{ of reading})$ Spectral response8 to 14 µmEmissivityPre-set at 0.95Ambient operating temp0 to 50 °C (32 to 120 °F)Relative humidity10 to 90 %Storage temperature-20 to 60 °C (-13 to 158 °F) without batteryDimensions200 x 160 x 55 mm (8 x 6 x 2 in.)Weight320 g (11 oz.)Power9 V alkaline or NiCd batteryBatter life (alkaline)10 hours with laser and backlight on 40 hours with laser and backlight offTypical distance to targetUp to 2 m (6 ft.)Display hold (7 seconds)•LCD backlit•Temperature display°C or °F selectableDisplay resolution0.2 °C (0.5 °F)Hard carrying case•Tripod mounting•	(Assumes ambient operating temperature	-26 to -18 °C (-15 to 0 °F): ±2.5 °C (±4 °F) -18 to 23 °C (0 to 73 °F): ±2 °C (±3 °F) 23 to 510 °C (73 to 950 °F): ±1 % of reading or ±1 °C (±2 °F), whichever is greater
Spectral response8 to 14 µmEmissivityPre-set at 0.95Ambient operating temp0 to 50 °C (32 to 120 °F)Relative humidity10 to 90 %Storage temperature-20 to 60 °C (-13 to 158 °F) without batteryDimensions200 x 160 x 55 mm (8 x 6 x 2 in.)Weight320 g (11 oz.)Power9 V alkaline or NiCd batteryBatter life (alkaline)10 hours with laser and backlight on 40 hours with laser and backlight offTypical distance to targetUp to 2 m (6 ft.)Display hold (7 seconds)•LCD backlit•Temperature display°C or °F selectableDisplay resolution0.2 °C (0.5 °F)Hard carrying case•Tripod mounting•	Repeatability	± 0.5 % or $\leq \pm 1$ °C (± 2 °F), whichever is greater
EmissivityPre-set at 0.95Ambient operating temp0 to 50 °C (32 to 120 °F)Relative humidity10 to 90 %Storage temperature-20 to 60 °C (-13 to 158 °F) without batteryDimensions200 x 160 x 55 mm (8 x 6 x 2 in.)Weight320 g (11 oz.)Power9 V alkaline or NiCd batteryBatter life (alkaline)10 hours with laser and backlight on 40 hours with laser and backlight offTypical distance to targetUp to 2 m (6 ft.)Display hold (7 seconds)•LCD backlit•Temperature display°C or °F selectableDisplay resolution0.2 °C (0.5 °F)Hard carrying case•Tripod mounting•	Response time	\leq 0.5 second (95 % of reading)
Ambient operating temp0 to 50 °C (32 to 120 °F)Relative humidity10 to 90 %Storage temperature-20 to 60 °C (-13 to 158 °F) without batteryDimensions200 x 160 x 55 mm (8 x 6 x 2 in.)Weight320 g (11 oz.)Power9 V alkaline or NiCd batteryBatter life (alkaline)10 hours with laser and backlight on 40 hours with laser and backlight offTypical distance to targetUp to 2 m (6 ft.)Distance to Spot ratio12:1Max temperature display•LCD backlit•Temperature display°C or °F selectableDisplay resolution0.2 °C (0.5 °F)Hard carrying case•Tripod mounting•	Spectral response	8 to 14 µm
Relative humidity10 to 90 %Storage temperature-20 to 60 °C (-13 to 158 °F) without batteryDimensions200 x 160 x 55 mm (8 x 6 x 2 in.)Weight320 g (11 oz.)Power9 V alkaline or NiCd batteryBatter life (alkaline)10 hours with laser and backlight on 40 hours with laser and backlight offTypical distance to targetUp to 2 m (6 ft.)Distance to Spot ratio12:1Max temperature display•LCD backlit•Temperature display°C or °F selectableDisplay resolution0.2 °C (0.5 °F)Hard carrying case•Tripod mounting•	Emissivity	Pre-set at 0.95
Storage temperature-20 to 60 °C (-13 to 158 °F) without batteryDimensions200 x 160 x 55 mm (8 x 6 x 2 in.)Weight320 g (11 oz.)Power9 V alkaline or NiCd batteryBatter life (alkaline)10 hours with laser and backlight on 40 hours with laser and backlight offTypical distance to targetUp to 2 m (6 ft.)Distance to Spot ratio12:1Max temperature display•Display hold (7 seconds)•LCD backlit•Display resolution0.2 °C (0.5 °F)Hard carrying case•Tripod mounting•	Ambient operating temp	0 to 50 °C (32 to 120 °F)
Dimensions200 x 160 x 55 mm (8 x 6 x 2 in.)Weight320 g (11 oz.)Power9 V alkaline or NiCd batteryBatter life (alkaline)10 hours with laser and backlight on 40 hours with laser and backlight offTypical distance to targetUp to 2 m (6 ft.)Distance to Spot ratio12:1Max temperature display•Display hold (7 seconds)•LCD backlit•Temperature display°C or °F selectableDisplay resolution0.2 °C (0.5 °F)Hard carrying case•Tripod mounting•	Relative humidity	10 to 90 %
Weight320 g (11 oz.)Power9 V alkaline or NiCd batteryBatter life (alkaline)10 hours with laser and backlight on 40 hours with laser and backlight offTypical distance to targetUp to 2 m (6 ft.)Distance to Spot ratio12:1Max temperature display•Display hold (7 seconds)•LCD backlit•Temperature display°C or °F selectableDisplay resolution0.2 °C (0.5 °F)Hard carrying case•Tripod mounting•	Storage temperature	-20 to 60 °C (-13 to 158 °F) without battery
Power9 V alkaline or NiCd batteryBatter life (alkaline)10 hours with laser and backlight on 40 hours with laser and backlight offTypical distance to targetUp to 2 m (6 ft.)Distance to Spot ratio12:1Max temperature display•Display hold (7 seconds)•LCD backlit•Temperature display°C or °F selectableDisplay resolution0.2 °C (0.5 °F)Hard carrying case•Tripod mounting•	Dimensions	200 x 160 x 55 mm (8 x 6 x 2 in.)
PortonO C analysis of Hock EarthsyBatter life (alkaline)10 hours with laser and backlight on 40 hours with laser and backlight offTypical distance to targetUp to 2 m (6 ft.)Distance to Spot ratio12:1Max temperature display•Display hold (7 seconds)•LCD backlit•Temperature display°C or °F selectableDisplay resolution0.2 °C (0.5 °F)Hard carrying case•Tripod mounting•	Weight	320 g (11 oz.)
40 hours with laser and backlight offTypical distance to targetUp to 2 m (6 ft.)Distance to Spot ratio12:1Max temperature display•Display hold (7 seconds)•LCD backlit•Temperature display°C or °F selectableDisplay resolution0.2 °C (0.5 °F)Hard carrying case•Tripod mounting•	Power	9 V alkaline or NiCd battery
Distance to Spot ratio 12:1 Max temperature display • Display hold (7 seconds) • LCD backlit • Temperature display °C or °F selectable Display resolution 0.2 °C (0.5 °F) Hard carrying case • Tripod mounting •	Batter life (alkaline)	
Max temperature display • Display hold (7 seconds) • LCD backlit • Temperature display °C or °F selectable Display resolution 0.2 °C (0.5 °F) Hard carrying case • Tripod mounting •	Typical distance to target	Up to 2 m (6 ft.)
Display hold (7 seconds)•LCD backlit•Temperature display°C or °F selectableDisplay resolution0.2 °C (0.5 °F)Hard carrying case•Tripod mounting•	Distance to Spot ratio	12:1
LCD backlit • Temperature display °C or °F selectable Display resolution 0.2 °C (0.5 °F) Hard carrying case • Tripod mounting •	Max temperature display	•
Temperature display °C or °F selectable Display resolution 0.2 °C (0.5 °F) Hard carrying case • Tripod mounting •	Display hold (7 seconds)	•
Display resolution 0.2 °C (0.5 °F) Hard carrying case • Tripod mounting •	LCD backlit	•
Hard carrying case • Tripod mounting •	Temperature display	°C or °F selectable
Tripod mounting •	Display resolution	0.2 °C (0.5 °F)
	Hard carrying case	•
Warranty 2 years, conditional	Tripod mounting	•
	Warranty	2 years, conditional

Optional accessories:

• Non-contact thermometer holster



Ordering information

Fluke 63

Included



Infrared Thermometer

Fluke. Keeping your world up and running.

Fluke Corporation PO Box 9090, Everett, WA USA 98206 Fluke Europe B.V. PO Box 1186, 5602 BD Eindhoven, The Netherlands For more information call: In the U.S.A. (800) 443-5853 or Fax (425) 446-5116 In Europe/M-East/Africa (31 40) 2 675 200 or Fax (31 40) 2 675 222 In Canada (800) 36-FLUKE or Fax (905) 890-6866 From other countries +1 (425) 446-5500 or Fax +1 (425) 446-5116 Web access: http://www.fluke.com

©2005 Fluke Corporation. All rights reserved. Printed in U.S.A. 4/2005 2150511 D-ENG-N Rev B