



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# Fluke 719Pro Electric Pressure Calibrator

## Technical Data

### Integrated electric pump—now to 300 PSI/20 bar

The 719Pro Electric Pressure Calibrator is the ideal test tool for calibrating high accuracy transmitters, pressure switches and pressure gauges.

The 719Pro includes a full functioning loop calibrator that sources, simulates and measures mA signals and more.

The large backlit screen displays three parameters at once:

- Pressure measurement from internal or external sensor
- Sourced/simulated or measured mA values
- Temperature measured by optional RTD probe



- Unique integrated electric pump for one handed pressure calibration
- Test pressure switches easily with easy-to-use switch test function
- Precision pressure adjust vernier for easy and accurate pressure calibration
- Ideal accuracy and performance (0.025 %) for reference class transmitter calibration
- 30 PSI, 150 PSI and the new 300 PSI pressure ranges
- Programmable pressure calibrator pump limit:
  - eliminates over-pressurization
  - allows the user to program target pressures for pumping
- Extended pressure measurement range with any of 29 700Pxx Pressure Modules
- Pump cleanout ports reduce pump failures from moisture and fluid damage
- Fluid trap included with the unit to mitigate chance of fluid damage in at-risk applications
- Precision temperature measurement with optional RTD probe

## Specifications

Pressure measurement	Range	Resolution	Accuracy	Comment
Fluke-719Pro-30G	-12 to 30 PSI /-0.8 to 2 bar	0.001 PSI, 0.0001 bar	± 0.025 % of full scale, 6 months ± 0.035 % of full scale, 1 year	Dry Air and non-corrosive gas only
Fluke-719Pro-150G	-12 to 150 PSI /-0.8 to 10 bar	0.01 PSI, 0.001 bar		
Fluke-719Pro-300G	-12 to 300 PSI / -0.8 to 20 bar	0.01 PSI, 0.001 bar		
Temperature effect (all ranges)			Add ± 0.002 % F.S./°C for temps outside of 15 °C to 35 °C	No effect on accuracy on all functions from 15 °C to 35 °C
Function	Range	Resolution	Accuracy (1 year)	Comment
mA dc (simulation and measurement)	0-24 mA dc	0.001 mA	± 0.015 % of reading ± 2 counts	1000 ohm maximum load in mA source, 26 V dc maximum voltage in mA simulate
Volts dc (measurement only)	30 V dc	0.001 V	± 0.015 % of reading ± 2 counts	No AC voltage measurement, do not exceed 30 V dc
Temperature (measurement only, Pt100 RTD)	-50 to 150 °C (-50 °F to 302 °F)	0.01 °C 0.01 °F	Temperature ± 0.1 °C (0.2 °F)	± 0.25 °C (± 0.45 °F) combined uncertainty when using 720 RTD probe (optional accessory)
Loop power supply	24 V dc	N/A	24 mA at 24 V	
Temperature effect (all functions)			Add ± 0.002 % F.S./°C for temps outside of 15 °C to 35 °C	No effect on accuracy on all functions from 15 °C to 35 °C
Environmental				
Operating temperature			-10 °C to +50 °C	
Storage with batteries per battery manufacturer's specification within storage specification below				
Storage temperature (without batteries)			-20 °C to +60 °C	
Power requirements				
Battery			Eight (8) standard Alkaline AA batteries	
Battery life			300 pump cycles to 150 PSI minimum; 1000 pump cycles to 30 PSI; 100 pump cycles to 300 PSI minimum	
Physical				
Dimensions (HxWxD)			24.13 cm x 11.18 cm x 7 cm (9.5 in x 4.4 in x 2.8 in)	
Weight			With holster 1.2 kg (2.5 lb)	
Connections				
Pressure			1/8 inch female NPT	
Electrical			Standard banana jacks	
RTD			4 pin miniature circular	
External module			6 pin miniature circular	
Engineering units (configurable)				
psi, bar, mbar, kPa, kg/cm <sup>2</sup> , cmH <sub>2</sub> O@4 °C, cmH <sub>2</sub> O@20 °C, mH <sub>2</sub> O@4 °C, mH <sub>2</sub> O@20 °C, inH <sub>2</sub> O@4 °C, inH <sub>2</sub> O@20 °C, inH <sub>2</sub> O@60 °F, mmHg@0 °C, inHg@0 °C, ftH <sub>2</sub> O@4 °C, ftH <sub>2</sub> O@20 °C, ftH <sub>2</sub> O@60 °F				

### Ordering information

**Fluke-719Pro-30G** Electric Pressure Calibrator, 30 PSIG  
**Fluke-719Pro-150G** Electric Pressure Calibrator, 150 PSIG  
**Fluke-719Pro-300G** Electric Pressure Calibrator, 300 PSIG  
**Fluke-720RTD** RTD Probe for 721 and 719Pro  
**Fluke-720URTDA** Universal RTD adapter for Fluke-721 and 719Pro  
**Fluke-71XTrap** Liquid and dirt trap for 718 and 719Pro

### Included with all models

Test leads with alligator clips, printed users manual and users manual on CD-ROM in 14 languages, fluid trap, carrying case, 1/4 inch NPT to 1/4 inch ISO adapter, accessory hose kit with (2) 1/8 inch quick fit adapters and 1 meter of hose, Traceable Certificate of Calibration.

**Fluke.** *The Most Trusted Tools in the World.*

**Fluke Corporation**  
 PO Box 9090, Everett, WA 98206 U.S.A.

**Fluke Europe B.V.**  
 PO Box 1186, 5602 BD  
 Eindhoven, The Netherlands

**For more information call:**  
 In the U.S.A. (800) 443-5853 or  
 Fax (425) 446-5116  
 In Europe/M-East/Africa +31 (0) 40 2675 200 or  
 Fax +31 (0) 40 2675 222  
 In Canada (800)-36-FLUKE or  
 Fax (905) 890-6866  
 From other countries +1 (425) 446-5500 or  
 Fax +1 (425) 446-5116  
 Web access: <http://www.fluke.com>

©2013 Fluke Corporation.  
 Specifications subject to change without notice.  
 Printed in U.S.A. 7/2013 4347338A\_EN

**Modification of this document is not permitted  
 without written permission from Fluke Corporation.**