



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# Fluke 902

## True-rms HVAC Clamp Meter

### Technical Data



Heating, ventilation, air conditioning (HVAC) technicians require a service tool that can consistently keep up with their demands. The Fluke 902 expands the existing line of quality Fluke clamp meters by delivering the features necessary to diagnose and repair HVAC systems. Combined with True RMS technology and a CAT III 600 V rating, the Fluke 902 helps technicians do their jobs safely and accurately.

#### Use the Fluke 902 to:

- Capture flue gas temperatures
- Conduct flame rod testing
- Measure start and run motor capacitors
- Measure performance of variable frequency drives

#### Features include:

- Capacitance
- DC current to 200 uA
- Contact temperature (K-type thermocouple)
- True-rms
- Min/Max
- Hold

#### Specifications

Feature	Range	Accuracy
Voltage dc	0 to 600.0 V	1 % ± 5 counts
Voltage ac (true-rms)	0 to 600.0 V	1 % ± 5 counts (50/60 Hz)
Current ac (true-rms)	0 to 600.0 A	2.0 % ± 5 counts (50/60 Hz)
Current dc	0 to 200.0 μA	1.0 % ± 5 counts
Resistance	0 to 9999 Ω	1.5 % ± 5 counts
Continuity	≤ 30 Ω	
Temperature* (Type-K thermocouple)	-10 °C to 400 °C (-14 °F to 752 °F) -40 °C to -10 °C (-40 °F to -14 °F)	± 1.0 % + 0.8 °C (± 1.0 % + 1.5 °F) typical ± 5.0 % + 1.5 °C (± 5.0 % + 3.3 °F) typical
Capacitance	1 μF to 1000 μF	1.9 % ± 2 counts
Warranty	Three-years	

\*Error does not include Type-K thermocouple errors





## Ordering Information

### Fluke-902 HVAC Clamp Meter

#### Included

- AA alkaline batteries (2)
- Users manual (w/safety information)
- Soft carrying case
- TL75 Test Leads (1 pair)
- 80BK Integrated DMM Temperature Probe (1)



## Optional accessories



#### H3 Clamp Meter Holster

- Rugged fabric holster includes flap for lead storage and built-in belt loop
- Also used on Fluke 320 and 330 Series Clamp Meters



#### TL223 SureGrip™ Electrical Test Lead Set

- Starter kit for electrical applications
- TP1 has flat blades for wall sockets
- Includes 1 pair: AC220, TP1, TL224
- CAT III 1000 V, CAT IV 600 V, 10 A



#### 80PK-8 Pipe Clamp Probe (for use with 80AK)

- Clamps securely to pipe from 6.4 mm to 34.9 mm (.25 in to 1.375 in)
- Temperature range: -29 °C to 149 °C (-20 °F to 300 °F)
- Probe material: K-type sensor with pvc body
- Cable length: 1 m (39 in)



#### 80AK Thermocouple Adapter

- Adapts Type-K thermocouple mini-connector to dual banana plug inputs
- Measurement range and accuracy is not affected by the 80AK adapter

**Fluke. Keeping your world up and running.™**

**Fluke Corporation**  
PO Box 9090, Everett, WA USA 98206

**Fluke Europe B.V.**  
PO Box 1186, 5602 BD Eindhoven, The Netherlands

**For more information call:**  
In the U.S.A. (800) 443-5853 or Fax (425) 446-5116  
In Europe/M-East/Africa +31 (0) 40 2675 200 or Fax +31 (0) 40 2675 222  
In Canada (800)-36-FLUKE or Fax (905) 890-6866  
From other countries +1 (425) 446-5500 or Fax +1 (425) 446-5116  
Web access: <http://www.fluke.com>

©2006 Fluke Corporation. All rights reserved.  
Printed in U.S.A. 10/2006 2645797 D-EN-N Rev B