



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Fluke 975 AirMeter™

Five powerful tools in one, with simple one-touch air velocity

The Fluke 975 AirMeter test tool raises indoor air monitoring to the next level by combining five powerful tools in one, rugged and easy-to-use hand-held tool. The Fluke 975 AirMeter test tool makes indoor air quality testing easier and faster.



Optional Air Velocity Probe

## Technical Data

### Use the Fluke 975 AirMeter test tool to:

- Respond to comfort-related calls from occupants.
- Verify the operation of building HVAC control systems.
- Determine whether adequate ventilation exists.
- Monitor air flow and velocity.\*
- Test for dangerous carbon monoxide leaks.
- Perform duct traversals.

### Features:

- Simultaneously measures, logs, and displays temperature, humidity, CO<sub>2</sub>, and CO on a bright, backlit LCD display
- One-touch air flow and velocity with available probe\*
- Wet bulb and dew point temperature
- % of outside air calculation
- CO<sub>2</sub> and CO field calibration feature
- Self-test function at startup
- Auto-backlight
- Automatically compensates for barometric pressure changes
- Min/Max/Average on all measured and calculated readings
- Multi-language user interface
- Metric or standard units
- Audible and visual threshold alarms
- Extensive discrete or continuous data logging capacity, downloadable to PC via USB interface
- Keypad lock for security
- Included FlukeView Forms® software

\*Included with Fluke 975V, optional with Fluke 975



## Fluke 975 AirMeter specifications

| Feature   | Range  | Display resolution                   | Accuracy   |
|---|--|--------------------------------------|--|
| <b>Measured specifications</b>                        |  |                                      |  |
| Temperature   | -20 °C to 50 °C<br>(-5 °F to 122 °F)               | 0.1 °F<br>(0.1 °C)                   | ± 0.9 °C/± 1.62°F from 40 °C to 50 °C<br>± 0.5 °C/± 1.00°F from 5 °C to 40 °C<br>± 1.1 °C/± 1.98 °F from -20 °C to 5 °C                  |
| Relative humidity                                     | 10 % to 90 % RH<br>non-condensing                  | 1 %                                  | ± 2 % RH (10 % RH to 90 % RH)  |
| Air velocity  | 0.50 fpm to 3000 fpm<br>0.25 m/sec to<br>15 m/sec  | 1 fpm<br>(0.005m/sec)                | ± 4% or 4 fpm*<br>± 4 % or 0.02 m/sec* whichever is greater<br>*Accuracy specification only valid for velocity readings above 50 fpm.    |
| CO <sub>2</sub>                                       | 0 to 5000 ppm                                      | 1 ppm                                | Warm up time 1 min (5 minutes for full specification)<br>2.75 % + 75 ppm   |
| CO  | 0 to 500 ppm                                       | 1 ppm                                | ± 5 % or ± 3 ppm, whichever is greater, @ 20 °C and 50 % RH  |
| <b>Calculated specifications</b>                      |  |                                      |  |
| Dew point temperature                                 | -44 °C to 50 °C<br>(-47 °F to 122 °F)              | 0.1 °C<br>(0.1 °F)                   | ± 1 °C when temp: -20 °C to 50 °C RH: 40 % to 90 %<br>± 2 °C when temp: -20 °C to 50 °C RH: 20 % to 40 %<br>± 4 °C when RH: 10 % to 20 % |
| Wet bulb temperature                                  | -16 °C to 50 °C<br>(3 °F to 122 °F)                | 0.1 °C<br>(0.1 °F)                   | ± 1.2 °C when RH: 20 % to 90 % temp: -20 °C to 50 °C<br>± 2.1 °C when RH: 10 % to 20 %   |
| Volume flow rate (in a duct)                          | 0 to 3,965 M <sup>3</sup> /m<br>(0 to 140,000 cfm) | 0.001 M <sup>3</sup> /min<br>(1 cfm) | N/A: The volume flow calculation will be a simple average of the data points times the duct area   |
| % outside air (based on temperature)                  | 0 to 100 %   | 0.1 %                                | N/A  |
| % outside air (based on CO <sub>2</sub> )             | 0 to 100 %   | 0.1 %                                | N/A  |
| <b>General specifications</b>                         |  |                                      |  |
| Operating temperature: CO and CO <sub>2</sub> sensors | -20 °C to 50 °C (-4 °F to 122 °F)                  |                                      |  |
| Operating temperature: All other functions            | -20 °C to 50 °C (-4 °F to 122 °F)                  |                                      |  |
| Storage temperature                                   | -20 °C to 50 °C (-4 °F to 122 °F)                  |                                      |  |
| Humidity  | 10 % to 90 % (non-condensing)                      |                                      |  |
| Altitude  | Up to 2000 m (6562 ft)                             |                                      |  |
| Shock and vibration                                   | MIL-PRF-28800F: Class 2                            |                                      |  |
| Multi-language interface                              | English, French, Spanish, Portuguese and German    |                                      |  |
| Battery   | Rechargeable Li-Ion (primary), three-AA (backup)   |                                      |  |
| Data logging  | 25,000 records (continuous), 99 records (discrete) |                                      |  |
| Warranty  | Two-years  |                                      |  |

## Ordering Information

**Fluke-975** AirMeter™  
**Fluke-975V** AirMeter™ with Velocity  
**Included**  
 AA alkaline batteries (3)  
 Users manual (with safety information)  
 Calibration cap  
 Hard carrying case  
 FlukeView® Forms software  
 Power adapter  
 International power plugs  
 Air velocity probe (Fluke 975V only)



**Fluke.** Keeping your world up and running.™

**Fluke Corporation**  
 PO Box 9090, Everett, WA USA 98206

**Fluke Europe B.V.**  
 PO Box 1186, 5602 BD  
 Eindhoven, The Netherlands

**For more information call:**  
 In the U.S.A. (800) 443-5853 or  
 Fax (425) 446-5116  
 In Europe/M-East/Africa +31 (0) 40 2675 200 or  
 Fax +31 (0) 40 2675 222  
 In Canada (800)-36-FLUKE or  
 Fax (905) 890-6866  
 From other countries +1 (425) 446-5500 or  
 Fax +1 (425) 446-5116  
 Web access: <http://www.fluke.com>

## Optional accessories

**ToolPak™** Magnetic Meter Hanging Kit  
**Fluke-975CK** AirMeter Calibration Kit  
**Fluke-975VP** AirMeter Air Velocity Probe