

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Is Now Part of




ON Semiconductor®

To learn more about ON Semiconductor, please visit our website at www.onsemi.com

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any EDA Class 3 medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, emplo



FMB100



NPN Multi-Chip General Purpose Amplifier

This device is designed for general purpose amplifier applications at collector currents to 300 mA. Sourced from Process 10.

Absolute Maximum Ratings* T_A =25°C unless otherwise noted

Symbol	Parameter	Value	Units	
V _{CEO}	Collector-Emitter Voltage	45	V	
V _{CBO}	Collector-Base Voltage	75	V	
V _{EBO}	Emitter-Base Voltage	6.0	V	
Ic	Collector Current - Continuous	500	mA	
T _J , T _{stg}	Operating and Storage Junction Temperature Range	-55 to +150	°C	

 $^{^{\}star}$ These ratings are limiting values above which the serviceability of any semiconductor device may be impaired.

Symbol	Characteristic	Max	Units	
		FMB100		
P _D	Total Device Dissipation	700	mW	
	Derate above 25°C	5.6	mW/°C	
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	180	°C/W	

These ratings are based on a maximum junction temperature of 150 degrees C.
 These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.

NPN Multi-Chip General Purpose Amplifier

(continued)

		•				
 へんせい	1001	r.n	ara	ハナハ	ricti	\sim
	ical		ala	cie	11511	

 $T_A = 25$ °C unless otherwise noted

Symbol	Parameter	Test Conditions	Min	Тур	Max	Units
OFF CHAI	RACTERISTICS					
BV _{CBO}	Collector-Base Breakdown Voltage	$I_C = 10 \mu A, I_B = 0$	75			V
BV _{CEO}	Collector-Emitter Breakdown Voltage*	I _C = 1 mA, I _E = 0	45			V
BV _{EBO}	Emitter-Base Breakdown Voltage	$I_E = 10 \mu A, I_C = 0$	6.0			V
I _{CBO}	Collector Cutoff Current	V _{CB} = 60 V			50	nA
I _{CES}	Collector Cutoff Current	V _{CE} = 40 V			50	nA
I _{EBO}	Emitter Cutoff Current	V _{EB} = 4 V			50	nA
h _{FE}	ACTERISTICS DC Current Gain	$I_C = 100 \mu A, V_{CE} = 1.0 V$	80	1		
h _{FE}	DC Current Gain	$I_C = 100 \mu\text{A}, V_{CE} = 1.0 \text{V}$	80			
		$I_C = 10 \text{ mA}, V_{CE} = 1.0 \text{ V}$	100		450	
		$I_C = 10 \text{ mA}, V_{CE} = 1.0 \text{ V}$ $I_C = 100 \text{ mA}, V_{CE} = 1.0 \text{ V}^*$ $I_C = 150 \text{ mA}, V_{CE} = 5.0 \text{ V}^*$			450 350	
V _{CE(sat)}	Collector-Emitter Saturation Voltage	$I_{C} = 100 \text{ mA}, V_{CE} = 1.0 \text{ V}^{*}$ $I_{C} = 150 \text{ mA}, V_{CE} = 5.0 \text{ V}^{*}$ $I_{C} = 10 \text{ mA}, I_{B} = 1.0 \text{ mA}$	100 100			V
V _{CE(sat)}	Collector-Emitter Saturation Voltage Base-Emitter Saturation Voltage	I _C = 100 mA, V _{CE} = 1.0 V* I _C = 150 mA, V _{CE} = 5.0 V*	100 100		350	
V _{BE(sat)}		$\begin{split} &I_C = 100 \text{ mA}, \ V_{CE} = 1.0 \ V^* \\ &I_C = 150 \text{ mA}, \ V_{CE} = 5.0 \ V^* \\ \\ &I_C = 10 \text{ mA}, \ I_B = 1.0 \text{ mA} \\ &I_C = 200 \text{ mA}, \ I_B = 20 \text{ mA}^* \\ \\ &I_C = 10 \text{ mA}, \ I_B = 1.0 \text{ mA} \end{split}$	100 100		350 0.2 0.4 0.85	V

 $V_{CB} = 5.0 \text{ V}, f = 1.0 \text{ MHz}$

 $I_C = 100 \ \mu A, \ V_{CE} = 5.0 \ V,$


 $R_G=2.0\;k\Omega,\,f=1.0\;kHz$


Noise Figure

C_{obo}

Output Capacitance

Typical Characteristics





3.5

2.5

рF


dB


^{*}Pulse Test: Pulse Width \leq 300 μ s, Duty Cycle \leq 2.0%

NPN Multi-Chip General Purpose Amplifier


(continued)


Typical Characteristics (continued)







Collector-Cutoff Current vs Ambient Temperature








Switching Times vs Collector Current



Power Dissipation vs Ambient Temperature



TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

 $ACEx^{TM}$ $FASTr^{TM}$ PowerTrench® SyncFETTM QFET™ TinyLogic™ Bottomless™ GlobalOptoisolator™ QSTM UHC™ CoolFET™ GTO™ QT Optoelectronics™ **VCXTM** CROSSVOLT™ HiSeC™

DOME™ ISOPLANAR™ Quiet Series™

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
- 2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.

ON Semiconductor and III) are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.

Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor 19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free Europe, Middle East and Africa Technical Support: Phone: 421 33 790 2910 Japan Customer Focus Center

Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative