



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Item # FRX490, UHF Fiberglass Omnidirectional Antenna



UHF Fiberglass Omnidirectional Antenna

FR Series Fiberglass Omnis

[Stock Locator](#)

Laird Technologies' UHF fiberglass series is best suited to base station and talkaround applications. The versatility in frequency and gain selection combined with a highly reliable solid brass radiator provide exceptional value for superior RF performance. The quality design of the integrated pigtail and N-female connector are excellent weather-proofing features. Mounting hardware is included facilitating installation.

SPECIFICATIONS

Band	UHF
Series	FR
Frequency	490 to 512 MHz
Gain	5 dBi
Bandwidth	22 MHz
3dB Beamwidth, E Plane	24 °
Height	42.50 in 107.32 cm
Weight	1.04 lbs 0.42 kg
Wind Surface Area	0.196 m ² 0.018 ft ²
VSWR	1.5:1
Polarization	Vertical
Impedance	50 ohms
Pigtail	12 in (30.5 cm) UltraLink
RF Connector	N (Female)
Wind Survival	125 mph 200 kph

Enclosure Material	Fiberglass
Power	150 watts
Mounting Style	Tube end