

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. WIRE PACKAGE MAX. DIMENSIONS in. [mm²] RANGE PANDUIT QTY. COLOR WIRE WIRE INSTALLATION TOOL PART # (DIN) INSULATION CLASS 0D DIAMETER (PER STRIP) [mm²] Ρ AWG L ID (REF.) * FSD75-8-DSL10 22-20 [0,50] | 500 (50) WHITE B, K, M | 0.60 [15,2] 0.10 [2,6] 0.31 [8,0] 0.04 [1,0] 0.05 [1,4] 0.05 [1,2] FSD76-8-DSL8 18 [0,75] | 500 (50) GRAY 0.11 [2,7] B, K, M 0.60 [15,2] 0.31 [8,0] 0.06 [1,6] FSD77-8-DSL2 [1,00] | 500 (50) RED 0.12 [3,0] B, K, M 0.60 [15,2] 0.31 [8,0] 0.07 [1,8] 0.06 [1,5] CT-1000 FSD78-8-DSL0 [1,50] | 500 (50) 16 BLACK 0.13 [3,2] B, K, M 0.60 [15,2] 0.31 [8,0] 0.08 [2,1] 0.07 [1,8] [2,50] | 500 (50) FSD80-8-DSL6 BLUE 0.16 [4,0] 0.60 [15,2] 0.31 [8,0] 0.10 [2,6] 0.09 [2,3]

-1000

LOCATOR SLOT
(FOR CT-1000)

ID
OD REF.

TIN PLATED
COPPER
FERULE

POLYPROPYLENE
SLEEVE

FUNNELED
WIRE ENTRY

MAX. WIRE
INSUL. DIA.

* UL LISTED WITH 20AWG ONLY, UL486F SCOPE IS 20 - 1/0 AWG ONLY, WHITE IS DIN COLOR FOR 20AWG [0.51

NOTES:

В

- 1. USED FOR:
 - A. UL LISTED WITH STRANDED COPPER WIRE ONLY
 B. 221°F [105°C] MAX. OPERATING TEMPERATURE
- 2. WIRE STRIP LENGTH: 13/32" +1/32 [10,0+0.8]
- 3. MATERIAL:
 - A. STAMPING: COPPER, TIN PLATED
 - B. HOUSING: POLYPROPYLENE, COLOR CODED
 - C. COLOR CODE CONFORMS TO DIN STANDARD
- 4. DIMENSIONS IN BRACKETS ARE METRIC EQUIVALENT


2

5. FOR TOLERANCING REFER TO DIN 46228 PART 4



E472545





	06	12.23.15	TMR	TMR	RGB	ADDED WIRE CLASS, TOOL, STRIP QTY TO TABLE	A41736		l
	05	03.09.15	JHNU	TMR	RGB	FSD76 SIZE WAS 20AWG, FSD77 WAS 18AWG	A41736	TITLE	l
Αĺ	04	12.04.14	JHNU	TMR	RGB	ADDED cULus LOGO REVISED NOTE 1A, ADDED NOTE 4C	A41736	FERRULES WITH SLEEVES ON STRIPS - SINGLE WIRE	1
	03	02.18.13	BDK	вст	VMD	REMOVED FS FERRULES (NON-DIN) FSD77-8-DSL2 REMOVED 18 AWG EXPANDED WIRE RANGE ON FSD75-8-DSL10 UPDATED DRAWING FORMAT TO CURRENT STANDARDS	A41736	CUSTOMER DRAWING ITEM REVISION NAME N41736BA/06 DATASET FILE NAME NATIONAL ROLLS	
	02	02/08	вст	LCA	LCA	ADDED CSA LOGO AND CERTIFICATION NUMBER		N41736BA_DC/06	l
ľ	01	04/07	вст	вст	LCA	LENGTH CHANGED TO 'L'; ID-1 ADDED; CHANGED FSD75 & FSD76 P/NS	TR00250	UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]	
	"	"	"	"	"	ADDED '-8-' TO P/N FOR LENGTH; REMOVED 'D' FROM NON-DIN COLORED PARTS	77	.x ± .xxx ± SEE NOTES .xx ± ANGLES ±	
	00	01/07	DAW	DAW	LCA	RELEASED	TR00208	THIRD ANGLE PROJECTION A41736	
ľ	REV	DATE	BY	СНК	APR	DESCRIPTION	ECN	DRAWN BY DATE CHK SCALE SIZE DAW 01/08 N.T.S. SHT 1 0F 1	l