

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







FSP3 Series

FSP3-277-20KA / FSP3-480-20KA

Patent-pending 3-Pole Fused In-Line Surge Protectors For LED Drivers, with or without Operating Indicator LED



Rev 07-19-2017

Features

FSP3 Surge Protectors are designed for use in conjunction with LED Drivers to provide an additional level of protection against powerline disturbances in industrial or commercial applications.

• UL Certified for Factory or Field Wiring

- FSP3-277-20KA is a 4-leaded device primarily for universal input Phase to Neutral applications and provides protection that includes Line to Neutral, Line to Ground and Neutral to Ground possible couplings
- FSP3-480-20KA is a 5-leaded device for 480VAC Phase to Phase applications and provides protection that includes one Phase to a second Phase, one Phase to Ground, and second Phase to Ground possible couplings
- Provides a positive indication of End-of-Life by opening voltage to the load, and turning off the fixture
- Versions available with and without a green LED indicator when on, it indicates that the FSP3 is fully functional and providing protection and when off, it indicates that the FSP3 has reached End-of-Life and needs to be replaced
- Protects against surges and transients per ANSI C62.41-2002 category C high (10KV, 1.2/50 μ S & 10KA, 8/20 μ S) standard Combo waves and (6KV, 100KHz) Ring wave
- Protects against surges and transients per new ANSI C82.77-5 2015 category C high (20KV, 1.2/50 μ S & 10KA, 8/20 μ S) standard Combo waves and (6KV, 100KHz) Ring wave
- UL Recognized Component in the United States and Canada (UL1449)
- Complies with IEC 61643-11; 8.3.4.3
- High temp, flameproof plastic enclosure with 85°C max surface temp rating
- Operating temperature range: -40°C to +85°C ambient
- · Patent Pending
- 277V Models: Protection for LED drivers capable of operating at 277V input voltage or with universal input range of 120V through 277V. Not optimized for single voltage devices operating at 120V-only or 240V-only.
- 480V Models: Protection for LED drivers capable of operating at 480V input voltage or with universal input ranges of 277V through 480V or 347V through 480V. Not optimized for single voltage devices operating at 277V-only or 347V-only.


C S US E355018	ROHS	P65
-----------------------	------	------------

TEST QUALIFIED FOR TEXAS DOT,
DEPARTMENTAL MATERIALS SPECIFICATION
FOR LED ROADWAY LIGHTING



Model	Mains Voltage	Continuous Max Current	Continuous Max Voltage Rating		Max Clamping Voltage 8/20 μS @ 20kA	UL1449	LED Indicator
voltage Rati	Rating	AC	DC				
FSP3-277-20KA	277V	7.0A	320V	420V	2100V	•	•
FSP3-277-20KA-NI	277V	7.0A	320V	420V	2100V	•	
FSP3-480-20KA	480V	4.0A	550V	745V	3800V	•	•
FSP3-480-20KA-NI	480V	4.0A	550V	745V	3800V	•	


Dimensions



Leads: 6", stripped 0.63" Lead wire AWG #16 stranded Weight: 0.5 lbs / 197g

	Pulse rating (8 x 20 µSec)				
Strikes	Surge				
1	20,000 A				
2	15,000 A				
15	10,000 A				
120	3,000 A				

Wiring



★ MADE IN USA ★ Of Imported And Domestic Components

© 2017 Thomas Research Products. Specifications subject to change without notice.