



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Product Guide

Transceivers, Transponders,
and Active Optical Cables

FINISAR®



Transceivers, Transponders, and Active Optical Cables

SFP (copper and optical; longwave, shortwave and WDM)

DATACOM applications using Fast Ethernet, Gigabit Ethernet, 1x/2x/4x Fibre Channel

TELECOM applications using OC-3/STM-1, OC-12/STM-4, OC-48/STM-16, EPON/GPON and Wireless/CPRI across all reaches

Features

- 3.3 V operating voltage
- Distances from very short links up to 100+ km
- Wide operating temperature range
- Metal enclosure for lower EMI
- Digital diagnostics
- Wireless CPRI compliant



SFP

SFP+ (optical; longwave, shortwave, DWDM and tunable)

DATACOM applications using 10G and 25G Ethernet and 2x/4x/8x/16x/32x Fibre Channel (LW and SW)

TELECOM applications using either OC-192/STM-64, 10G Ethernet, or Wireless/CPRI

Features

- 3.3 V operating voltage
- Supports bit rates up to 28.05 Gb/s (LW, SW, and DWDM) and 11.3 Gb/s (Tunable)
- Distances from short links up to 80 km metro (LW, SW, and DWDM) and 80km (Tunable)
- Wide operating temperature range
- Digital diagnostics
- Wireless CPRI compliant (LW and SW)
- Bi-directional SFP+ transceiver available



SFP+

CFP/CFP2/CFP4 (optical; longwave and shortwave)

DATACOM applications using 40G and 100G Ethernet

TELECOM applications using OTU3 and OTU4

Features

- Hot-pluggable, MSA-compliant CFP, CFP2 and CFP4 form factors
- Supports 39.8 Gb/s to 112 Gb/s aggregate bit rates
- Maximum link length of 100m on OM3 MMF, 150m on OM4 MMF, 10km on SMF, and 500km in Amplified DWDM Applications
- 3.3 V operating voltage



CFP/CFP2/CFP4

QSFP+/QSFP28 (optical; longwave and shortwave)

DATACOM applications using 40G and 100G Ethernet, 128G Fibre Channel and high-density 10G and 25G Ethernet

TELECOM applications using OTU3 and OTU4

Features

- Four-channel full-duplex transceiver module
- Hot-pluggable, MSA-compliant QSFP+ and QSFP28 form factors
- Maximum link length of 300m on OM3 MMF, 400m on OM4 MMF, and 10 km on SMF
- 3.3 V operating voltage



QSFP+/QSFP28

CXP (optical; shortwave)

DATACOM applications using 100G Ethernet and chassis interconnections

Features

- Twelve-channel full-duplex transceiver module
- Hot Pluggable CXP form factor
- Maximum link length of 100m on OM3 MMF and 150m on OM4 MMF
- Multirate capability: supports 1.06 Gb/s to 12.5 Gb/s per channel



CXP

Active Optical Cables

SFPwire 10 Gb/s SFP+ Active Optical Cable for 10G Ethernet

quadwire 40 Gb/s to 100 Gb/s Parallel Active Optical Cable for 40GbE, InfiniBand 4xQDR, Infiniband 4xFDR, and Infiniband 4xEDR

C.wire 150 Gb/s Parallel Active Optical Cable for 100GbE and InfiniBand 12xQDR



Active Optical Cables

Optical Engines (optical; shortwave)

DATACOM applications for inter-chassis connections

Features

- Twelve-channel full-duplex transceiver modules (BOA)
- Twelve-channel transmitter and receiver modules (SNAP12)
- Maximum link length of 100m at 10 Gb/s on OM3 MMF or 70m at 25 Gb/s on OM4 MMF (BOA)
- Maximum link length of 600m at 2.5 Gb/s on OM3 MMF (SNAP12)
- Multirate capability: supports 1 Gb/s up to 28.05 Gb/s per channel




X2 (optical; longwave and shortwave)

DATACOM applications using 10G Ethernet

Features

- Supports bit rates up to 10.5 Gb/s
- Distances up to 10 km
- Digital diagnostics



Coherent (optical; longwave)

TELECOM 100Gb/s and 200Gb/s applications

Features

- Pluggable CFP2-ACO with analog interface
 - Analog host interface is compatible with any external DSP
 - Modulation format independent
- 5"x7" module supporting multiple modulation formats with internal DSP
 - Platform supports DP-BPSK, DP-QPSK, or DP-16QAM at up to 32Gbaud
 - Best in class OSNR performance



Endurance Compact Transceivers (optical; longwave and shortwave)

Features

- Compact form-factor for high-density solutions
- Data rate flexibility including 1G and 10G Ethernet, Fast Ethernet, and 1x/2x/4x/8x Fibre Channel
- Board-mounted for an edge optical interface or internal mounting
- Designed for rugged applications



XFP (optical; longwave, shortwave, DWDM, and tunable)

DATACOM applications using 10G Ethernet and 10x Fibre Channel

TELECOM applications using OC-192/STM-64

Features

- Supports bit rates up to 11.3 Gb/s
- Distances up to 200 km (LW, SW, and DWDM) and 80 km (Tunable)
- Digital diagnostics
- Wide operating temperature range versions available



SFF (optical; longwave and shortwave)

DATACOM applications using Gigabit Ethernet, 1x/2x/4x Fibre Channel

TELECOM applications using OC-3/STM-1, OC-12/STM-4 and OC-48/STM-16 across all reaches

Features

- Distances from very short links up to 80 km
- Wide operating temperature range
- Available in 2x5, 2x7 or 2x10. 2x7 and 2x10 incorporate digital diagnostics



Finisar's Patented Digital Diagnostics

Finisar's transceivers feature a microprocessor and diagnostics interface that provides performance information on the data link. Users can remotely monitor—in real-time—received optical power, transmitted optical power, laser bias current, transceiver input voltage and transceiver temperature of any transceiver in the network. These digital diagnostic functions provide network managers with a highly accurate, cost-effective tool for implementing reliable performance monitoring.



Technology Innovator.
Broad Product Portfolio.
Trusted Partner.

FINISAR[®]

1389 Moffett Park Drive
Sunnyvale, CA 94089-1133
Telephone: +1 408-548-1000
Sales: +1 408-541-5690

Email: sales@finisar.com
Blog: www.finisar.com/blogs/lightspeed
www.finisar.com

