



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





FISHTAPE,NYLON-50'

Nylon Fish Tape 50' × 3/16 (15.2 m × 4.8 mm)

Cat No: FTN536-50

UPC No: 783310127154

### Description

---

- Non-conductive, curl resistant nylon tape for fast, cleanfishing
- Good for fishing in conduit with wire or cable present
- Rugged case design improves drop impact capability
- Advanced comfort handle grip reduces fatigue
- Nylon fish tape is intended for fishing only. Rope or line is recommended for pulling

### Specifications

---

- Application : For Fast, Clean Fishing, For Fishing In Conduit With Wire Or Cable Present
- Length : 50.000 FT (15.200 M)
- Material : Nylon
- Replacement Part : RN536-50 Replacement Nylon Fish Tape 50 FT (NO CASE), 01664 Replacement Tip for 436 Nylon Fish Tape (Requires Greenlee K05 or K09 series crimper or #6 hex crimp to install), 10052 12 IN Case/Handle Replacement Kit
- Sub Brand : MagnumPRO
- Tensile Strength : 250.000 LB (1.100 KN) Maximum Design Strength
- Type : Non Conductive, Curl Resistant
- Weight : 2.900 LB (1.300 KG)
- Width : 3/16 IN (4.800 MM)