



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





GREENLEE.
A Textron Company

MADE FOR THE TRADE!™



FISHTAPE,STAINLESS STEEL-100'

Stainless Steel Fish Tape - 100' × 1/8 (30.5 m × 3.2 mm)

Cat No: FTSS438-100

UPC No: 783310127116

Description

- Corrosion free stainless steel tape for maximum life
- Fish further and faster with Speed Flex leader
- Advanced comfort handle grip reduces fatigue
- Viewing Port gives visibility to remaining tape and ability to remove jobsite debris quickly
- Rugged case design improves drop impact capability
- Flared case with Grip Ridges for no slip handling
- Replacement Speed Flex leader

Specifications

- Length : 100.000 FT (30.500 M)
- Material : Stainless Steel
- Replacement Part : RSS438-100 Replacement Stainless Steel Tape - 100 FT (No Case), 439-2 12 IN (305 MM) SPEED FLEX Leader (solder joints),10052 12 IN Case/Handle Replacement Kit
- Sub Brand : MagnumPRO
- Tensile Strength : 400.000 LB (1.700 KN) MaximumDesign Strength
- Weight : 4.800 LB (2.200 KG)
- Width : 1/8 IN (3.200 MM)