



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





FVA100 Series

100 W ITE Open Frame Power Supply

- High Efficiency: Level V
- Up to 120W with Forced Air
- High Power Density 8.7/in³
- Hold-up Time >60ms at full load
- EISA and CEC Compliant
- Power Factor Correction
- Grounded Output
- Safety Approval - EN60950-1
- CEC Compliant
- Grounded Output
- Safety Approval - EN60950-1

Elpac Part Number	Output Voltage	Output Current	Peak Current	Total Regulation	Typical Efficiency
FVA100012A	12.0V	8.3A	10.0A	±5%	88%
FVA100015A	15.0V	6.7A	8.0A	±5%	88%
FVA100018A	18.0V	5.6A	6.7A	±5%	89%
FVA100024A	24.0V	4.2A	5.0A	±5%	89%


Input	
Input Voltage	85 - 264VAC 100 - 240VAC Nominal
Input Frequency	47 - 63Hz
Input Current	<2A rms
Inrush Current	<37A at 230VAC cold start
Power Factor	>0.96
Zero Load Power Consumption	<0.5W
Touch Leakage Current	<125µA @ 132VAC @ 60Hz <175µA @ 264VAC @ 60Hz

Output	
Output Voltage	See Table
Total Regulation	+/-5%
Minimum Load	No minimum load required
Start-Up Delay	<750ms
Hold-Up Time	>60ms at any input voltage
Ripple & Noise	<1% pk-pk **
Over Voltage Protection	110-135%
Over Temperature Protection	Active - Recoverable; plus Passive - Non Recoverable
Over Current Protection	120 - 180%
Short Circuit Protection	shutdown, auto-restart (hiccup mode)

General	
Efficiency	Avg Efficiency 88.6% @ 115VAC; 89.5% @ 230VAC
MTBF	min. 200,000 hours demonstrated
Size	4.50
Weight	0.66 lbs (.30 kg)
Power Density	8.7W/in ³ (at 120W)

Environmental	
Operating Temperature	0 – 70°C (Full load to 50°C, derate linearly to 50% load at 70°C)
Storage Temperature	-40°C to +85°C
Relative Humidity	5-95%, non-condensing
Cooling	Natural Convection (100W) or Forced Air (120W)
Vibration	All units production tested to 19.6m/s ²

EMC & Safety	
Emissions	FCC class B, CISPR22 class B EN61000-3-2, -3
Immunity	EN61000-4-2, -3, -4, -5, -6, -8, -11

<p>Certified by TUV to the following:</p> 	<p>cTUVus UL 60950-1 CAN/CSA-22.2 No.60950-1 CB per IEC60950-1 CE marked to LVD</p>
---	---

FVA100 | ICCNEXERGY | © 2011 |