



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## G85-23200EU-2



### *Models may vary from the image shown*

The G85-23200 corded keyboard from CHERRY is specially developed for continuous use in the office: Abrasion-proof inscription of key caps, whisper quiet keystroke, splash water-protected and ultra-thin, ergonomic design.

### Key benefits

- Spill resistant – not sensitive to fluids
- Durable abrasion-resistant laser inscribed key caps
- Plug & Play for easy installation
- Ultra-thin ergonomic top-design for fatigue-free work
- Whisper quiet keystroke
- 6 HotKeys for comfortable volume control and the most important Mediaplayer functions
- Standard keyboard layout (including cursor and number block)
- Blue status LED's

### Technical Data:

#### Housing Color:

Black (Pale Gray requires special MOQ)

#### Key Color:

Black (Pale Gray requires special MOQ)

#### Weight (product):

Approx. 936 g/ 2.06 lbs.

#### Total Weight (with packaging):

Approx. 1205 g/ 2.65 lbs.

#### Cable Length:

Approx. 1.80 m/ 5.9ft.

#### Interface:

- USB

#### Storage Temperature:

-20°C to 65°C/ -4°F to 149°F







#### Operating Temperature:

0°C to 40°C/ 32°F to 104°F

#### Current Consumption:

Typ. 15 mA

#### Product Approvals:

- cURus 
- VDE GS 
- c-tick 
- VCCI 
- CE 
- FCC 

#### System Requirements:

- USB

#### Delivery Volume:

- G85-23200
- Operating instructions in hard copy

#### Dimensions (product):

Approx. 472 x 176 x 18 mm/ 18.58" x 6.92" x .70"

#### Reliability:

- MTBF > 80,000 hours

#### Packaging Dimensions:

Approx. 485 x 220 x 30 mm/ 19.09" x 8.66" x 1.18"

#### Keyboard:

- Key technology: SX
- Service life, standard key: > 20 million key operations
- Inscription technology: Laser
- Inscription layout: Standard
- Number of keys: 104 + 6

#### Packaging Unit:

- Number of products in the master package: 6
- Number of master packages per pallet: 28

#### Warranty:

2 years

### Order Description

<i>Product Name</i>	<i>Order Number</i>	<i>EAN code</i>	<i>Interface</i>	<i>Housing Color</i>	<i>Key Color</i>
Stream 3.0	G85-23200EU-2	4025112083198	USB	Black	Black
Stream 3.0	G85-23200EU-0	4025112083259	USB	Pale Gray (MOQ Apply)	Pale Gray (MOQ Apply)



ZF Electronics Corporation Systems Pleasant Prairie, LLC  
 11200 88th Avenue  
 Pleasant Prairie, WI 53158  
 USA

Phone: 262.942.6500

Internet: [www.cherrycorp.com](http://www.cherrycorp.com)

Sales: 262.942.6562

E-Mail: [CEP\\_sales@ZF.com](mailto:CEP_sales@ZF.com)

Fax: 262.942.6566

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice. Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

© 2015 ZF Electronics Corporation, Last update: July 6, 2015 V01