

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









PSE Technology Corporation

SPECIFICATION FOR APPROVAL

CUSTOMER	
NOMINAL FREQUENCY	8.000000 MHz
PRODUCT TYPE	TYPE GC 49S SMD QUARTZ CRYSTAL
PART NUMBER	GC0800044
CUSTOMER P/N	
ISSUE DATE	March 25, 2011
VERSION	A

APPROVED	PREPARED	QA		
Brenda	Vikbi Lu	fillin		
APPROVED BY CUSTOMER				

Please return one copy with approval to PSE-TW

PSE Technology Corporation

No.2, Tzu-Chiang 5th Rd., Chung Li Industrial Park, Chung Li City, Taoyuan County, Taiwan (R.O.C.) TEL:886-3-451-8888 FAX:886-3-461-3865 http://www.saronix-ecera.com.tw/

*RoHS Compliant

*HF-Halogen Free

*REACH Compliant

A Company of PERICOM Semiconductor Corporation

E0-R-4-014 Rev.E

VER.A 25-MAR-11

VERSION HISTORY

Version No.	Version Date	Customer Receipt Date	Supplier Receipt Date	Description	Notes
Α	Mar. 25, 2011			Initial Release	

VER.A 25-MAR-11

ELECTRICAL SPECIFICATIONS

Item	Symbol	Specifications	Units	Notes
Nominal Frequency	Fn	8.000000	MHz	
Mode of Oscillation	МО	AT Cut-Fundamental		
Calibration Load Capacitance	CL	16	pF	
Calibration Tolerance	FL	± 30	ppm	at 25°C±3°C
Operating Temperature Range	TR	-20 to +70	°C	
Frequency Stability(Frequency Deviation over the Operating Temperature Range)	F/T	± 50	ppm	Reference to the Frequency at 25°C
Operating Drive Level		100	μW	
Maximum Drive Level		500	μW	
Equivalent Series Resistance	ESR	40	Ω	Max.
Shunt Capacitance	C0	7	pF	Max.
Aging at 25°C		± 5	ppm	Max, 1st year
Storage Temperature		-55 to +125	°C	
Insulation Resistance		500	ΜΩ	Min

^{**} This product doesn"t include harmful substance that stipulated by SONY SS-00259 Level 1 and S-AT2-001 Level 1 standard. RoHS Compliant (Pb - Free).

VER.A 25-MAR-11

RELIABILITY SPECIFICATIONS

MECHANICAL AND ENVIRONMENTAL RATINGS:

a)FINE LEAK TEST: JESD22-A109 (Condition 1A)

b)GROSS LEAK TEST: JESD22-A109 (Condition C)

c)MOISTURE RESISTANCE: JESD22-A113

d)SHOCK: JESD22-B104 (Condition B)

e)SOLDERABILITY: (RoHS version): J-STD-002

f)VIBRATION: JESD22-B103


g)SOLVENT RESISTANCE: JESD22-B107

h)RESISTANCE TO SOLDERING HEAT (RoHS version): J-STD-020D Table 5.2 Pb free devices (3 cycles max)

Note:

SUGGESTED IR REFLOW PROFILE

*As per IPC-JEDEC J-STD-020D



	Stage	Temperature	Time	
Α	Preheat	150~200°C	60~120 Sec	
_	1/2m/000 1/2m/000		00 450 0	


60~150 Sec Primary Heat 217°C В Peak 260°C 10 Sec

For soldering reflow profile and reliability test ratings go to: http://www.pericom.com/pdf/sre/reflow.pdf

E0-R-4-014 Rev.E Page 2


VER.A 25-MAR-11

MARKING






MECHANICAL DRAWINGS (Scale: None. Dimensions are in mm.)




E0-R-4-014 Rev.E Page 3

VER.A 25-MAR-11



VER.A 25-MAR-11



E0-R-4-014 Rev.E Page 5