imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



muRata Capacitor Data Sheet GCM1885C1H152JA16# "#" indicates a package specification code.

Recommended In Production	Power- train	AEC- Q200	1 <u>ද</u> 5	Reflow OK	FlowOK	RoHS	REACH
---------------------------	-----------------	--------------	--------------	--------------	--------	------	-------

< List of part numbers with package codes >

Shape

GCM1885C1H152JA16D , GCM1885C1H152JA16J

L size	1.6 ±0.1mm
W size	0.8 ±0.1mm
T size	0.8 ±0.1mm
External terminal width e	0.2 to 0.5mm
Distance between external terminals g	0.5mm min.
Size code in inch(mm)	0603 (1608M)

References

Packaging	Specifications	Minimum quantity		
D	ф180mm Paper taping	4000		
J	ф330mm Paper taping	10000		

Mass (typ.)			
1 piece	6.3mg		
φ180mm Reel	144g		

Specifications

Capacitance	1500pF ±5%	
Rated voltage	50Vdc	
Temperature characteristics (complied standard)	C0G(EIA)	
Temperature coefficient	0±30ppm/°C	
Temperature range of temperature characteristics	25 to 125°C	
Operating temperature range	-55 to 125°C	

🔔 Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2. This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.