



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



DWG. NO.	ZONE	REV.	DESCRIPTION	DATE	APPROVED
010-0X3		X1	CUSTOMER APPROVAL	12/22/98	C.V.
		X2	CHANGE RETRACTED LENGTH FROM 13" TO 24"	12/29/98	C.V.
		A	PRODUCTION RELEASE	01/04/99	C.V.
		B	CHAGNE TO ROHS	02/15/06	M.G.

NOTES: UNLESS OTHERWISE SPECIFIED:

- 1.0 MATERIAL AND SPECIFICATIONS
 - 1.01 CONDUCTORS: 26 AWG (12/0.12 mm) STRANDED BARE COPPER.
 - 1.02 INSULATION: POLYPROPYLENE
 - 1.03 COLOR: PER CALLOUT
- 2.0 ELECTRICAL CHARACTERISTICS
 - 2.01 TEMPERATURE & VOLTAGE RATING: 80°C 30 V
 - 2.02 CONDUCTORS RESISTANCE: 148 OHMS/KM MAX. AT 20°C
 - 2.03 INSULATION RESISTANCE: 100 MEGOHMS/KM MIN. AT 20°C
 - 2.04 CAPACITANCE: 15 PF/FT (MAX)
 - 2.05 DIELECTRIC TEST: AC-500V PER 1 MINUTE

- 3.0 PACKAGING SPECIFICATION
 - 3.01 USE CLEAR TAPE TO BUNDLE 25 CABLES TOGETHER AT THE MID SECTION.
 - 3.02 PLACE PLASTIC BAG IN SHIPPING BOX AND LAY 10 BUNDLE OR 250 PIECES MAX. PER SHIPPING BOX. CLOSE PLASTIC BAG AND SEAL BOX ALONG 3 SURFACES WITH TAPE.
 - 3.03 MAX. DIMENSION OUTSIDE SHIPPING BOX IS L=13.00" x W=25.00" x H=9.00".

GLF-121-010-003	10	SILVER SATIN	[0.748 REF.] 19.00 REF.]
GLF-121-010-013	10	BLACK	[0.748 REF.] 19.00 REF.]
GLF-121-010-023	10	WHITE	[0.748 REF.] 19.00 REF.]
I/O INTERCONNECT PART NUMBER	NUMBER OF CONDUCTORS	COLOR	ø "A"

THIRD ANGLE PROJECTION

UNLESS OTHERWISE NOTED: DIMENSIONS ARE IN MILLIMETER (INCHES) TOLERANCES: X.X ± 0.20 [0.008] X.XX ± 6.35 [0.250]

DR. BY: CHAU HAI
TR. CHECKER: [REDACTED]
DATE: 02/15/06

TITLE: 26 AWG (12/0.12 mm) BARE COPPER, 500 FT EXTENDED, 10P 10C NON-UL, UNSHIELDED, MODULAR CABLE

PART NO: GLF-121-010-0X3
DWG NO: GLF-121-010-0X3
CUSTOMER: DIGI KEY
REV: B

SCALE: NONE
SHEET 1 OF 1

THESE DRAWINGS AND SPECIFICATIONS ARE THE SOLE PROPERTY OF I/O INTERCONNECT INC., U.S.A. AND SHALL NOT BE REPRODUCED, COPIED, OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF I/O INTERCONNECT INC. OR ITS AFFILIATED SUBSIDIARIES.

