imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





GN1113 Low Voltage Operation

GN1113 Information Note

GN1113 Low Voltage Operation

This document is an addendum to the GN1113 datasheet, Gennum document ID number 44368, entitled "GN1113, 8.5 Gb/s Fibre Channel Rx Repeater". It is intended to show the performance of the part while it is continuously operated at 2.7V. All data sheet parameters are equivalent to those listed in the standard GN1113 data sheet, with the exception of the deviations show below. Note that some parameters listed here may be equivalent to those in the standard data sheet, but are repeated here for clarity.

Parameter	Symbol	Standard Datasheet Values		Modified Values for 2.7V Continuous Operation		
		Min	Max	Min	Max	Units
Supply Voltage	V _{CC}	2.81	3.47	2.67	2.73	V
Supply Current	I _{CC}	50.0	75.7	50.0	73.0	mA
Output Amplitude	V _{OLS}	600	800	550	780	mVppd
Input Data Rate		8.5	8.5	8.5	8.5	Gb/s
Temperature Range	T _C	-40	+95	-5	+95	°C

Revision History

Version	ECR	Date	Changes and / or Modifications
0	148993	January 2008	New document.



ELECTROSTATIC SENSITIVE DEVICES DO NOT OPEN PACKAGES OR HANDLE EXCEPT AT A STATIC-FREE WORKSTATION



DOCUMENT IDENTIFICATION INFORMATION NOTE

Information relating to this product and the application or design described herein is believed to be reliable, however such information is provided as a guide only and Gennum assumes no liability for any errors in this document, or for the application or design described herein. Gennum reserves the right to make changes to the product or this document at any time without notice.

GENNUM CORPORATION

Mailing Address: P.O. Box 489, Stn. A, Burlington, Ontario, Canada L7R 3Y3 Shipping Address: 970 Fraser Drive, Burlington, Ontario, Canada L7L 5P5 Tel. +1 (905) 632-2996 Fax. +1 (905) 632-5946

GENNUM JAPAN CORPORATION

Shinjuku Green Tower Building 27F, 6-14-1, Nishi Shinjuku, Shinjuku-ku, Tokyo, 160-0023 Japan Tel. +81 (03) 3349-5501, Fax. +81 (03) 3349-5505

GENNUM UK LIMITED

25 Long Garden Walk, Farnham, Surrey, England GU9 7HX Tel. +44 (0)1252 747 000 Fax +44 (0)1252 726 523

Gennum Corporation assumes no liability for any errors or omissions in this document, or for the use of the circuits or devices described herein. The sale of the circuit or device described herein does not imply any patent license, and Gennum makes no representation that the circuit or device is free from patent infringement.

GENNUM, the G logo and ActiveConnect are trademarks or registered trademarks of Gennum Corporation.

© Copyright 2008 Gennum Corporation. All rights reserved. Printed in Canada.

www.gennum.com