mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





GN2470 IGBT



Features

- Low voltage drop at high currents
- Industry standard TO-252 (D-Pak) package
- 700V breakdown voltage rating

Applications

General Description

The Supertex GN2470 is a 700V, 3.5amp insulated gate bipolar transistor (IGBT) that combines the positive aspects of both BJTs and MOSFETs.

The GN2470 IGBT has lower on-state voltage drop with high blocking voltage capabilities and features many desirable properties including a MOS input gate, low conduction voltage drop at high currents.

- White goods
- Small appliances
- Lighting controls
- Motor drives
- Meter readers
- Small off-line power supplies

Ordering Information

Device	Package Option
	TO-252 (D-PAK)
GN2470	GN2470K4-G

-G indicates that the package is RoHS certified ("Green")



Absolute Maximum Ratings

Parameter	Value
Collector-to-emitter voltage	700V
Gate-to-emitter voltage	±20V
Operating junction and storage temperature range	-55°C to +150°C
Soldering temperature*	300°C

Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these conditions is not implied. Continuous operation of the device at the absolute rating level may affect device reliability. All voltages are referenced to device ground.

* Distance of 1.6mm from case for 10 seconds.

Pin Configuration



Pin Configuration



TO-252 (D-PAK) (K4)

GN2470 IGBT

Thermal Characteristics

Package	Ι _c	l _c	Power Dissipation	θ _{jc}	θ _{ja}		
	(continuous)	(pulsed)	@T _A = 25°C	(°C/W)	(°C/W)		
TO-252	1.0A	3.5A	2.5W	10	60†		

Notes:

† Mounted on FR4 board, 25mm x 25mm x 1.57mm

Electrical Characteristics (T_A = 25°C unless otherwise specified)

Sym	Parameter	Min	Тур	Max	Units	Conditions		
BV _{CES}	Collector-to-emitter breakdown voltage	700	-	-	V	$V_{_{\rm GE}}$ = 0V, I $_{_{\rm C}}$ = 250µA		
BV _{ECS}	Emitter-to-collector breakdown voltage	-6.0	-10	-	V	$V_{GE} = 0V, I_{C} = 1.0mA$		
V _{GE(th)}	Gate threshold voltage	1.5	-	3.5	V	$V_{CE} = V_{GE}, I_{C} = 1.0 \text{mA}$		
V _{CE}	Collector-to-emitter voltage drop	-	4.5	5.0	V	I _C = 3.0A, V _{GE} = 13V		
9 _{fe}	Forward transconductance	0.5	0.8	-	mho	V _{CE} = 25V, I _C = 2.0A		
I _{CES}	Zero gate voltage collector current	-	-	100	μA	V _{GE} = 0V, V _{CE} = 600V		
I _{GES}	Gate-to-emitter leakage current	-	-	±100	nA	$V_{_{\rm GE}}$ = ±20V, $V_{_{\rm CE}}$ = 0V		
I _{C(ON)}	On-state collector current	3.0	4.0	-	А	V _{GE} = 10V, V _{CE} = 25V		
t _{d(ON)}	Turn-on delay time	-	8.0	15				
t _r	Rise time	-	400	600	20	$V_{cc} = 25V$		
t _{d(OFF)}	Turn-off delay time	-	20	50	ns	$R_{GEN} = 25\Omega$ $R_{I} = 11\Omega$		
t,	Fall time	-	7000	12000		2		
C _{ISS}	Input capacitance	-	100	150		V _{CE} = 25V		
C _{oss}	Output capacitance	-	12	25	pF	$V_{GE}^{CE} = 0V$		
C _{RSS}	Reverse transfer capacitance	-	2	5				

Notes:

1. All D.C. parameters 100% tested at 25°C unless otherwise stated. (Pulse test: 300µs pulse, 2% duty cycle.)

2. All A.C. parameters sample tested.

Switching Waveforms and Test Circuit



2.5 2.0 1.5 1.0 0.5 0.0 -0.5 -1.00E-05 -5.00E-06 0.00E+00 5.00E-06 1.00E-05 1.00E-05 Time (5µs/div)

Typical Performance Waveform

Equivalent Circuit



Saturation Characteristics



Transfer Characteristics



GN2470 IGBT



$V_{GE(TH)}$ Variation with Temperature





Transconductance vs. Collector Current



GN2470 IGBT

3-Lead TO-252 D-PAK Package Outline (K4)



Note:

1. Although 4 terminal locations are shown, only 3 are functional. Lead number 2 was removed.

Symb	ol	Α	A1	b	b2	b3	c2	D	D1	E	E1	е	н	L	L1	L2	L3	L4	L5	θ	θ1
Dimen-	MIN	.086	.000*	.025	.030	.195	.018	.235	.205	.250	.170		.370	.055			.035	.025*	.045	00	00
sion N((inches) M	NOM	-	-	-	-	-	-	.240	-	-	-	.090 BSC	06	.060	.108 REF	3 .020 BSC	-	-	-	-	-
	MAX	.094	.005	.035	.045	.215	.035	.245	.217*	.265	.182*		.410	.070			.050	.040	.060	10 ⁰	15º

JEDEC Registration TO-252, Variation AA, Issue E, June 2004.

* This dimension is not specified in the original JEDEC drawing. The value listed is for reference only.

Drawings not to scale.

Supertex Doc. #: DSPD-3TO252K4, Version D081408.

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information go to <u>http://www.supertex.com/packaging.html</u>.)

Supertex inc. does not recommend the use of its products in life support applications, and will not knowingly sell them for use in such applications unless it receives an adequate "product liability indemnification insurance agreement." Supertex inc. does not assume responsibility for use of devices described, and limits its liability to the replacement of the devices determined defective due to workmanship. No responsibility is assumed for possible omissions and inaccuracies. Circuitry and specifications are subject to change without notice. For the latest product specifications refer to the Supertex inc. website: http://www.supertex.com.

©2008 Supertex inc. All rights reserved. Unauthorized use or reproduction is prohibited.

Supertex inc.