



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com





Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







## ■ Photocoupler Lineup

### <Phototransistor output type>

| Package type   | Output type                | Features  | Model No. (series)          | Page  |    |
|--|----------------------------|---|-----------------------------|---|----|
| Mini-flat 4-pin<br>Compact, SMT type<br>          | Single phototransistor     | General purpose,<br>High collector-emitter voltage, etc.  | PC35x series / PC451J00000F | 41  |    |
|  |                            | Low input current   | PC367NJ0000F                | 41  |    |
|  |                            | AC input response   | PC354NJ0000F                | 41  |    |
|  | Darlington phototransistor | High sensitivity,<br>High collector-emitter voltage       | Low input current           | PC364NJ0000F                                  | 41 |
|  |                            |   |                             | PC355NJ0000F / PC452J00000F                   | 41 |
|  |                            |   | Low input current           | PC365NJ0000F                                  | 41 |
| Compact, Half pitch<br>(lead space), SMT type<br> | Single phototransistor     | General purpose,<br>High resistance to noise, etc.        | PC3Hx series                | 42  |    |
|  |                            | Reinforced insulation                                     | PC3HU7xYIP0B                | 42  |    |
|  |                            | Low input current   | PC3H71xNIP0F                | 42  |    |
|  |                            | AC input response   | PC3H3J00000F / PC3H4J00000F | 42  |    |
|  | Darlington phototransistor | High sensitivity  | Low input current           | PC3H41xNIP0F                                  | 42 |
|  |                            |   |                             | PC3H5J00000F                                  | 42 |
|  |                            |   | Low input current           | PC3H510NIP0F                                  | 42 |
|  |                            |   |                             |   |    |
| DIP type (4-pin)<br>(4-pin, DIP type)<br>         | Single phototransistor     | Reinforced insulation                                     | PC123XNNSZ0F                | 43  |    |
|  |                            | Low input current   | PC1231xNSZ0X                | 43  |    |
|  | Darlington phototransistor | General purpose,<br>High collector-emitter voltage, etc.  |                             | PC817XNNSZ0F / PC851XNNSZ0F                   | 43 |
|  |                            | Low input current   |                             | PC8171xNSZ0X                                  | 43 |
|  |                            | High sensitivity,<br>High collector-emitter voltage       |                             | PC815XNNSZ0F / PC852XNNSZ0F /<br>PC853XNNSZ0F | 43 |
|  |                            | Low input current   |                             | PC81510NSZ0X                                  | 43 |
| DIP type (6-pin)<br>                            | Single phototransistor     | General purpose,<br>High collector-emitter voltage, etc.  | PC7xxV0NSZXF                | 44  |    |
|  | Darlington phototransistor | High sensitivity,<br>High collector-emitter voltage, etc. | PC7x5V0NSZXF                | 44  |    |

### <OPIC output type>

| Package type  | Output type             | Features  | Model No. (series)  | Page |
|---|-------------------------|---|---|------|
| Compact, SMT type<br>  | Digital output          | General purpose, High response speed, 2ch, etc.                 | PC400J00000F / PC456L0NIP0F▲ /<br>PC410S0NIP0F / PC410L0NIP0F /<br>PC4D10SNIP0F | 45   |
|   | Analog/Digital output   | High CMR  | PC457S0NIP0F / PC457L0NIP0F   | 45   |
| DIP type, SMT type<br> | Digital output          | General purpose   | PC900V0NSZXF  | 46   |
|   | Built-in base amplifier | For inverter control, Built-in short-circuit protection circuit | PC925LxNSZ0F / PC942J00000F▲ /<br>PC928J00000F / PC929J00000F                   | 46   |

The model marked with ▲ may not be available in the near future. Contact with SHARP for details before use.



## ■ Photocouplers

### ◆ Phototransistor Output Type

#### <Compact, SMT type>

○: Approved

(Ta = 25°C)

| Output type                        | Model No.     | Internal connection diagram | Features   | Approved by safety standards*2 | Package         | Absolute maximum ratings            |  |  | Electro-optical characteristics |                     |                     |                          |                     |                    |                     |
|------------------------------------|---------------|-----------------------------|--|--------------------------------|-----------------|-------------------------------------|--|--|---------------------------------|---------------------|---------------------|--------------------------|---------------------|--------------------|---------------------|
|                                    |               |                             |  | UL                             |                 | Forward current I <sub>F</sub> (mA) | Isolation voltage (AC) V <sub>iso</sub> (rms) (kV) | Collector-emitter voltage V <sub>CEO</sub> (V) | Current transfer ratio          |                     |                     | Response time            |                     |                    |                     |
|                                    |               |                             |  |                                |                 |                                     |  |  | CTR (%) MIN.                    | I <sub>F</sub> (mA) | V <sub>CE</sub> (V) | t <sub>r</sub> (μs) TYP. | I <sub>C</sub> (mA) | R <sub>L</sub> (Ω) | V <sub>CE</sub> (V) |
| Single phototransistor output      | PC357NJ0000F  |                             | General purpose  | ○*                             | Mini-flat 4-pin | 50                                  | 3.75   | 80   | 50                              | 5                   | 5                   | 4                        | 2                   | 100                | 2                   |
|                                    | PC352NJ0000F▲ |                             | General purpose, high resistance to noise*1                      | ○                              |                 | 50                                  | 3.75   | 80   | 90                              | 5                   | 5                   | 4                        | 2                   | 100                | 2                   |
|                                    | PC451J0000F   |                             | High collector-emitter voltage                                   | ○*                             |                 | 50                                  | 3.75   | 350  | 40                              | 5                   | 5                   | 4                        | 2                   | 100                | 2                   |
|                                    | PC367NJ0000F  |                             | Low input current, high resistance to noise*1                    | ○                              |                 | 10                                  | 3.75   | 80   | 100                             | 0.5                 | 5                   | 4                        | 2                   | 100                | 2                   |
|                                    | PC354NJ0000F  |                             | AC input response  | ○*                             |                 | ±50                                 | 3.75   | 80   | 20                              | ±1                  | 5                   | 4                        | 2                   | 100                | 2                   |
|                                    | PC364NJ0000F  |                             | Low input current, AC input response, high resistance to noise*1 | ○                              |                 | ±10                                 | 3.75   | 80   | 50                              | ±0.5                | 5                   | 4                        | 2                   | 100                | 2                   |
| Darlington photo-transistor output | PC355NJ0000F  |                             | High sensitivity   | ○*                             | 50              | 3.75                                | 35   | 600  | 1                               | 2                   | 60                  | 2                        | 100                 | 2                  |                     |
|                                    | PC365NJ0000F  |                             | High sensitivity, low input current                              | ○                              | 10              | 3.75                                | 35   | 600  | 0.5                             | 2                   | 60                  | 10                       | 100                 | 2                  |                     |
|                                    | PC452J0000F   |                             | High collector-emitter voltage                                   | ○*                             | 50              | 3.75                                | 350  | 1 000  | 1                               | 2                   | 100                 | 20                       | 100                 | 2                  |                     |

\*1 CMR: MIN.10 kV/μs

\*2 Please refer to Specification Sheets for model numbers approved by safety standards.

\* A VDE approved type is optionally available.

The model marked with ▲ may not be available in the near future. Contact with SHARP for details before use.



#### Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.

Except where specially indicated, models listed on this page comply with the RoHS Directive\*. For details, please contact SHARP.

\*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.

Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.




## ◆ Phototransistor Output Type <Compact, half pitch (lead space) SMT type>

○: Approved

(Ta = 25°C)

| Output type                        | Model No.    | Internal connection diagram                   | Features   | Approved by safety standards*3<br>UL | Package                     | Absolute maximum ratings   |   |                                       | Electro-optical characteristics |         |         |                 |         |        |         |
|------------------------------------|--------------|---|--|--------------------------------------|-----------------------------|----------------------------|---|---------------------------------------|---------------------------------|---------|---------|-----------------|---------|--------|---------|
|                                    |              |   |  |                                      |                             | Forward current<br>IF (mA) | Isolation voltage (AC)<br>Viso (rms) (kV) | Collector-emitter voltage<br>VCEO (V) | Current transfer ratio          |         |         | Response time   |         |        |         |
|                                    |              |   |  |                                      |                             |                            |   |                                       | CTR (%)<br>MIN.                 | IF (mA) | VCE (V) | tr (μs)<br>TYP. | IC (mA) | RL (Ω) | VCE (V) |
| Single phototransistor output      | PC3HU7xYIP0B |   | Reinforced insulation (internal insulation distance: MIN. 0.4 mm), low-profile package | ○*4, 5                               | Low-profile mini-flat 4-pin | 50                         | 3.75                                      | 80                                    | 50                              | 5       | 5       | 4               | 2       | 100    | 2       |
|                                    | PC3H7J00000F |   | Standard   | ○*6                                  | Mini-flat 4-pin             | 50                         | 2.5                                       | 80                                    | 20                              | 1       | 5       | 4               | 2       | 100    | 2       |
|                                    | PC3H71xNIP0F |   | High resistance to noise*1, low input current  | ○                                    |                             | 10                         | 2.5                                       | 80                                    | 100                             | 0.5     | 5       | 4               | 2       | 100    | 2       |
|                                    | PC3H3J00000F | AC input response, high resistance to noise*1 | ○  | ±50                                  |                             | 2.5                        | 80  | 20                                    | ±1                              | 5       | 4       | 2               | 100     | 2      |         |
|                                    | PC3H4J00000F |   | AC input response  | ○*2, 6                               | ±50                         | 2.5                        | 80  | 20                                    | ±1                              | 5       | 4       | 2               | 100     | 2      |         |
|                                    | PC3H41xNIP0F |   | AC input response, high resistance to noise*1, low input current                       | ○                                    | ±10                         | 2.5                        | 80  | 50                                    | ±0.5                            | 5       | 4       | 2               | 100     | 2      |         |
| Darlington photo-transistor output | PC3H5J00000F |   | High sensitivity   | ○                                    | Mini-flat 4-pin             | 50                         | 2.5                                       | 35                                    | 600                             | 1       | 2       | 60              | 2       | 100    | 2       |
|                                    | PC3H510NIP0F |   | High sensitivity, low input current  | ○                                    |                             | 10                         | 2.5                                       | 35                                    | 600                             | 0.5     | 2       | 60              | 2       | 100    | 2       |

- \*1 CMR: MIN.10 kV/μs
- \*2 A VDE approved type is optionally available.
- \*3 Please refer to Specification Sheets for model numbers approved by safety standards.
- \*4 VDE, CSA approved
- \*5 In conformance with BSI, SEMKO, DEMKO, NEMKO, and FIMKO
- \*6 UL, cUL approved



### Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc. Except where specially indicated, models listed on this page comply with the RoHS Directive\*. For details, please contact SHARP. \*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions. Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.



## ◆ Phototransistor Output Type <DIP type (4-pin)>

○: Approved

(Ta = 25°C)

| Output type                       | Model No.                  | Internal connection diagram   | Features   | Approved by safety standards*8 |        |           | Package   | Absolute maximum ratings            |  |  | Electro-optical characteristics |                     |                          |                    |
|-----------------------------------|----------------------------|---|--|--------------------------------|--------|-----------|-----------|-------------------------------------|--|--|---------------------------------|---------------------|--------------------------|--------------------|
|                                   |                            |   |  | UL                             | VDE *2 | Others *3 |           | Forward current I <sub>F</sub> (mA) | Isolation voltage (AC) V <sub>iso</sub> (rms) (kV) | Collector-emitter voltage V <sub>CEO</sub> (V) | CTR (%) MIN.                    | I <sub>F</sub> (mA) | t <sub>r</sub> (μs) TYP. | R <sub>L</sub> (Ω) |
| Single phototransistor output     | PC123XNNSZ0F*1, *5, *6, *7 |   | High isolation voltage, reinforced insulation  | ○                              | ○      | ○         | 4-pin DIP | 50                                  | 5.0  | 70   | 50                              | 5                   | 4                        | 100                |
|                                   | PC1231xNSZ0X*1             |   | High isolation voltage, reinforced insulation, low input current, high resistance to noise*4 | ○                              | ○      | ○         |           | 10                                  | 5.0  | 70   | 50                              | 0.5                 | 4                        | 100                |
|                                   | PC817XNNSZ0F*5, *6, *7     |   | High isolation voltage   | ○                              | —      | ○*9       |           | 50                                  | 5.0  | 80   | 50                              | 5                   | 4                        | 100                |
|                                   | PC8171xNSZ0X*5, *6         | High isolation voltage, low input current, high resistance to noise*4 | ○  | —                              | —      | 10        |           | 5.0                                 | 80   | 100  | 0.5                             | 4                   | 100                      |                    |
|                                   | PC851XNNSZ0F*5, *6         | High isolation voltage, high collector-emitter voltage                | ○  | —                              | —      | 50        |           | 5.0                                 | 350  | 40   | 5                               | 4                   | 100                      |                    |
| Darlington phototransistor output | PC815XNNSZ0F*5, *6         |   | High isolation voltage, high sensitivity   | ○                              | —      | —         | 50        | 5.0                                 | 35   | 600  | 1                               | 60                  | 100                      |                    |
|                                   | PC81510NSZ0X               |   | High isolation voltage, high sensitivity, low input current                                  | ○                              | —      | —         | 10        | 5.0                                 | 35   | 600  | 0.5                             | 60                  | 100                      |                    |
|                                   | PC852XNNSZ0F*5, *6         |   | High isolation voltage, high collector-emitter voltage                                       | ○                              | ○      | —         | 50        | 5.0                                 | 350  | 1 000  | 1                               | 100                 | 100                      |                    |
|                                   | PC853XNNSZ0F*5, *6         |   | High isolation voltage, high collector-emitter voltage                                       | ○                              | ○      | —         | 50        | 5.0                                 | 350  | 1 000  | 1                               | 100                 | 100                      |                    |

\*1 Wide lead spacing type is also available. Creepage distance: 6.4 mm or more, wide lead spacing type: 8 mm or more.

\*2 Optionally available.

\*3 BSI, SEMKO, DEMKO, NEMKO, FIMKO, CSA

\*4 CMR: 10 kV/μs MIN.

\*5 Lead forming type is also available for surface mounting.

\*6 Taped package of lead forming type for surface mounting is also available.

\*7 Wide lead spacing type is also available. Compatible with wide lead spacing type lead-forming models for surface-mount use. Also compatible with taped packages for wide lead spacing type lead-forming models for surface-mount use.

\*8 Please refer to Specification Sheets for model numbers approved by safety standards.

\*9 UL, CSA approved



### Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.

Except where specially indicated, models listed on this page comply with the RoHS Directive\*. For details, please contact SHARP.

\*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.

Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.



## ◆ Phototransistor Output Type <DIP type (6-pin)>

○: Approved, △: Under application

(Ta = 25°C)

| Output type                       | Model No.    | Internal connection diagram | Features  | Approved by safety standards*2 |       | Package      | Absolute maximum ratings                  |   |   | Electro-optical characteristics |                        |                                |                       |
|-----------------------------------|--------------|-----------------------------|---|--------------------------------|-------|--------------|---|---|---|---------------------------------|------------------------|--------------------------------|-----------------------|
|                                   |              |                             |   | UL                             | VDE*1 |              | Forward current<br>I <sub>F</sub><br>(mA) | Isolation voltage<br>(AC)<br>V <sub>iso</sub> (rms)<br>(kV) | Collector-emitter<br>voltage<br>V <sub>CEO</sub><br>(V) | Current transfer ratio          |                        | Response time                  |                       |
|                                   |              |                             |   |                                |       |              |   |   |   | CTR<br>(%)<br>MIN.              | I <sub>F</sub><br>(mA) | t <sub>r</sub><br>(μs)<br>TYP. | R <sub>L</sub><br>(Ω) |
| Single phototransistor output     | PC714V0NSZXF |                             | High isolation voltage  | ○                              | ○     | 6-pin<br>DIP | 50  | 5.0   | 80  | 50                              | 5                      | 4                              | 100                   |
|                                   | PC724V0NSZXF |                             | High isolation voltage,<br>large input current  | ○                              | —     |              | 150                                       | 5.0   | 35  | 20                              | 100                    | 4                              | 100                   |
|                                   | PC713V0NSZXF |                             | High isolation voltage,<br>with base terminal   | ○                              | ○     |              | 50  | 5.0   | 80  | 50                              | 5                      | 4                              | 100                   |
| Darlington phototransistor output | PC715V0NSZXF |                             | High isolation voltage,<br>high sensitivity   | ○                              | ○     | 6-pin<br>DIP | 50  | 5.0   | 35  | 600                             | 1                      | 60                             | 100                   |
|                                   | PC725V0NSZXF |                             | High isolation voltage,<br>high sensitivity,<br>high collector-emitter voltage,<br>high power | ○                              | ○     |              | 50  | 5.0   | 300   | 1 000                           | 1                      | 100                            | 100                   |

\*1 Optionally available.

\*2 Please refer to Specification Sheets for model numbers approved by safety standards.



### Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.  
 Except where specially indicated, models listed on this page comply with the RoHS Directive\*. For details, please contact SHARP.  
 \*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.  
 Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.



◆ **OPIC Output** (“OPIC” (Optical IC) is a trademark of SHARP Corporation. An OPIC consists of a light-detecting element and signal-processing circuit integrated onto a single chip.)

### <Compact, SMT type> (1-1)

○: Approved

(Ta = 25°C)

| Model No.     | Internal connection diagram | Features   | Approved by safety standards*2 |       | Package         | Absolute maximum ratings            |  | Electro-optical characteristics*1 |                     |                      |                         |                            |                            |                    |
|---------------|-----------------------------|--|--------------------------------|-------|-----------------|-------------------------------------|--|-----------------------------------|---------------------|----------------------|-------------------------|----------------------------|----------------------------|--------------------|
|               |                             |  | UL                             | VDE*3 |                 | Forward current I <sub>F</sub> (mA) | Isolation voltage (AC) V <sub>iso</sub> (rms) (kV) | Low level output voltage          |                     |                      | Threshold input current |                            |                            |                    |
|               |                             |  |                                |       |                 |                                     |  | V <sub>OL</sub> (V) MAX.          | T <sub>a</sub> (°C) | I <sub>OL</sub> (mA) | I <sub>F</sub> (mA)     | I <sub>FHL</sub> (mA) MAX. | I <sub>FLH</sub> (mA) MAX. | R <sub>L</sub> (Ω) |
| PC400J00000F  |                             | Digital output, normal-off operation   | ○                              | —     | Mini-flat 5-pin | 50                                  | 3.75   | 0.4                               | 0 to +70            | 16                   | 4                       | 2.0                        | —                          | 280                |
| PC456L0NIP0F▲ |                             | Built-in preamplifier, high speed transmission (2 Mb/s), for flow soldering                  | ○                              | ○     |                 | 25                                  | 3.75   | 0.6                               | −40 to +85          | 2.4                  | 10                      | 5.0                        | —                          | 20 k               |
| PC410L0NIP0F  |                             | High speed (10 Mb/s), High CMR (10 kV/μs), For flow soldering                                | ○                              | ○     |                 | 20                                  | 3.75   | 0.6                               | −40 to +85          | 13                   | 5                       | 5.0                        | —                          | 350                |
| PC410S0NIP0F  |                             | High speed (10 Mb/s), high CMR (10 kV/μs), for flow soldering, Solder heat resistance: 270°C | ○                              | ○     | SOP 8-pin       | 20                                  | 3.75   | 0.6                               | −40 to +85          | 13                   | 5                       | 5.0                        | —                          | 350                |
| PC4D10SNIP0F  |                             | High speed (10 Mb/s), for flow soldering, Solder heat resistance: 270°C<br>2ch output        | ○                              | —     | SOP 8-pin       | 20                                  | 3.75   | 0.6                               | −40 to +85          | 13                   | 5                       | 5.0                        | —                          | 350                |

A: Rated voltage circuit

\*1 Each item is measured at V<sub>CC</sub>=5V. (PC400)

\*2 Please refer to Specification Sheets for model numbers approved by safety standards.

\*3 Optionally available.

The model marked with ▲ may not be available in the near future. Contact with SHARP for details before use.

### <Compact, SMT type> (1-2)


○: Approved

(Ta = 25°C)

| Model No.    | Internal connection diagram | Features  | Approved by safety standards*1 |       | Package         | Absolute maximum ratings            |  | Electro-optical characteristics |                     |                    |                        |                            |                            |                    |                     |
|--------------|-----------------------------|---|--------------------------------|-------|-----------------|-------------------------------------|--|---------------------------------|---------------------|--------------------|------------------------|----------------------------|----------------------------|--------------------|---------------------|
|              |                             |   | UL                             | VDE*2 |                 | Forward current I <sub>F</sub> (mA) | Isolation voltage (AC) V <sub>iso</sub> (rms) (kV) | Current transfer ratio          |                     |                    | Propagation delay time |                            |                            |                    |                     |
|              |                             |   |                                |       |                 |                                     |  | CTR (%) MIN.                    | I <sub>F</sub> (mA) | V <sub>O</sub> (V) | V <sub>CC</sub> (V)    | t <sub>PHL</sub> (μs) TYP. | t <sub>PLH</sub> (μs) TYP. | R <sub>L</sub> (Ω) | I <sub>F</sub> (mA) |
| PC457L0NIP0F |                             | High speed (1 Mb/s), high CMR (15 kV/μs), for flow soldering                                | ○                              | ○     | Mini-flat 5-pin | 25                                  | 3.75   | 19                              | 16                  | 0.4                | 4.5                    | 0.2                        | 0.4                        | 1 900              | 16                  |
| PC457S0NIP0F |                             | High speed (1 Mb/s), high CMR (15 kV/μs), for flow soldering, Solder heat resistance: 270°C | ○                              | ○     | SOP 8-pin       | 25                                  | 3.75   | 19                              | 16                  | 0.4                | 4.5                    | 0.2                        | 0.3                        | 1 900              | 16                  |

\*1 Please refer to Specification Sheets for model numbers approved by safety standards.

\*2 Optionally available.



PC400J00000F  
(Mini-flat 5-pin)

PC410S0NIP0F  
(SOP 8-pin)

#### Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.

Except where specially indicated, models listed on this page comply with the RoHS Directive\*. For details, please contact SHARP.  
\*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.

Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.



◆ **OPIC Output** ( "OPIC" (Optical IC) is a trademark of SHARP Corporation. An OPIC consists of a light-detecting element and signal-processing circuit integrated onto a single chip. )

**<DIP type, digital output>**

○: Approved

(Ta = 25°C)

| Model No.          | Internal connection diagram | Features                             | Approved by safety standards*5 |        | Package   | Absolute maximum ratings            |  | Electro-optical characteristics*1 |                     |                      |                         |                            |                            |                    |
|--------------------|-----------------------------|--------------------------------------|--------------------------------|--------|-----------|-------------------------------------|--|-----------------------------------|---------------------|----------------------|-------------------------|----------------------------|----------------------------|--------------------|
|                    |                             |                                      | UL                             | VDE *4 |           | Forward current I <sub>F</sub> (mA) | Isolation voltage (AC) V <sub>iso</sub> (rms) (kV) | Low level output voltage          |                     |                      | Threshold input current |                            |                            |                    |
|                    |                             |                                      |                                |        |           |                                     |  | V <sub>OL</sub> (V) MAX.          | T <sub>a</sub> (°C) | I <sub>oL</sub> (mA) | I <sub>F</sub> (mA)     | I <sub>FHL</sub> (mA) MAX. | I <sub>FLH</sub> (mA) MAX. | R <sub>L</sub> (Ω) |
| PC900V0NSZXF*2, *3 |                             | Digital output, normal-off operation | ○                              | ○      | 6-pin DIP | 50                                  | 5.0  | 0.4                               | 0 to +70            | 16                   | 4                       | 2.0                        | -                          | 280                |

A: Rated voltage circuit


\*1 Each item is measured at V<sub>cc</sub>=5V.

\*2 Lead forming type is also available for surface mounting.

\*3 Taped package of lead forming type for surface mounting is also available.

\*4 Optionally available.

\*5 Please refer to Specification Sheets for model numbers approved by safety standards.



◆ **OPIC Output** ( "OPIC" (Optical IC) is a trademark of SHARP Corporation. An OPIC consists of a light-detecting element and signal-processing circuit integrated onto a single chip. )

**<DIP type, Gate drive type>**

○: Approved

(Ta = 25°C)


| Model No.      | Internal connection diagram | Features   | Approved by safety standards*3 |        | Package                      | Absolute maximum ratings            |  | Electro-optical characteristics |                            |                     |                     |                     |                     |
|----------------|-----------------------------|--|--------------------------------|--------|------------------------------|-------------------------------------|--|---------------------------------|----------------------------|---------------------|---------------------|---------------------|---------------------|
|                |                             |  | UL                             | VDE *2 |                              | Forward current I <sub>F</sub> (mA) | Isolation voltage (AC) V <sub>iso</sub> (rms) (kV) | Propagation delay time          |                            |                     |                     |                     |                     |
|                |                             |  |                                |        |                              |                                     |  | t <sub>PHL</sub> (μs) TYP.      | t <sub>PLH</sub> (μs) TYP. | V <sub>CC</sub> (V) | I <sub>F</sub> (mA) | R <sub>L1</sub> (Ω) | R <sub>L2</sub> (Ω) |
| PC925LxNSZ0F*1 |                             | <ul style="list-style-type: none"> <li>Built-in drive circuit directly connectable to MOS-FET and IGBT</li> <li>Peak output current: 2.5 A</li> <li>Low dissipation current (I<sub>cc</sub> = TYP. 2.5 mA)</li> <li>High resistance to noise (CMR: MIN. 15 kV/μs)</li> </ul> | ○                              | ○      | 8-pin DIP                    | 25                                  | 5.0  | MAX.                            | MAX.                       | 15 to 30            | 7 to 16             | R <sub>G</sub> = 10 | -                   |
| PC942J00000F▲  |                             | For controlling inverter-controlled air-conditioner  | ○                              | ○      |                              |                                     |  | 25                              | 5.0                        | 2.0                 | 2.0                 | 6                   | 5                   |
| PC928J00000F   |                             | For driving inverter IGBT, built-in short protection circuit   | ○                              | ○      | 14-pin SMT (Half pitch lead) | 25                                  | 4.0  | 1.0                             | 1.0                        | 24                  | 10                  | R <sub>G</sub> = 47 | -                   |
| PC929J00000F   |                             | For driving inverter IGBT, high speed, built-in short protection circuit   | ○                              | ○      |                              |                                     |  | 20                              | 4.0                        | 0.3                 | 0.3                 | 24                  | 5                   |

\*1 Lead forming type is also available for surface mounting. Taped package of lead forming type for surface mounting is also available.

\*2 A VDE approved type is optionally available.

\*3 Please refer to Specification Sheets for model numbers approved by safety standards.

The model marked with ▲ may not be available in the near future. Contact with SHARP for details before use.



**Notice**

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.

Except where specially indicated, models listed on this page comply with the RoHS Directive\*. For details, please contact SHARP.




\*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.

Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.





## ■ Phototriac Coupler Lineup

| Package  | Applied voltage                                     | ON-state current (rms) | Features                    | Model No.   | Page |
|--|---|------------------------|-----------------------------|---|------|
| Mini-flat (SMD)<br>                             | AC 200 V lines<br>(V <sub>DRM</sub> = 600V)         | 0.05 A                 | General purpose             | S2S3000F*3 / S2S5A00F*3 / S2S5FA0F*3  | 48   |
|  |   |                        | Built-in zero-cross circuit | S2S4000F*3  | 49   |
| DIP type<br>(4-pin)<br>                         | AC 200 V lines<br>(V <sub>DRM</sub> = 600V)         | 0.1 A                  | General purpose             | PC3ST11NSZAX*3  | 48   |
|  |   |                        | Built-in zero-cross circuit | PC3ST21NSZBX*2  | 49   |
|  |   |                        | Reinforced isolation        | PC3SH11YFZAX*3 / PC3SH13YFZAX*3   | 48   |
|  |   |                        | Built-in zero-cross circuit | PC3SH21YFZBX*2  | 49   |
| DIP type<br>(6-pin package,<br>5th-pin cut)<br> | AC 100 V lines<br>(V <sub>DRM</sub> = 400V)         | 0.1 A                  | General purpose             | PC2SD11NTZAF*3 / PC1S3021NTZF*4   | 48   |
|  | AC 200 V lines<br>(V <sub>DRM</sub> = 600V)         | 0.1 A                  | General purpose             | PC3SD12NTZAF*3 / PC3SD12NTZBF*2 /<br>PC3SD12NTZCF*1 / PC1S3052YTZF*3 /<br>PC3SD11NTZCF*1 / PC3SD13NTZBF*2 | 48   |
|  |   |                        | Built-in zero-cross circuit | PC3SD21NTZAF*3 / PC3SD21NTZBF*2 /<br>PC3SD21NTZCF*1 / PC3SD21NTZDF*5 /<br>PC3SD23YTZCF*1 / PC1S3063YTZF*1 | 49   |
|  |   |                        | Reinforced isolation        | PC3SF11YVZAF*3 / PC3SF11YVZBF*2 /<br>PC3SF13YVZBF*2   | 48   |
|  |   |                        | Built-in zero-cross circuit | PC3SF21YVZAF*3 / PC3SF21YVZBF*2 /<br>PC3SF23YVZSF*2   | 49   |
|  |   |                        | General purpose             | PC4SD11NTZBF*2 / PC4SD11NTZCF*1   | 48   |
|  |   |                        | Built-in zero-cross circuit | PC4SD21NTZCF*1 / PC4SD21NTZDF*5   | 49   |
|  |   |                        | Reinforced isolation        | PC4SF11YVZAF*3 / PC4SF11YVZBF*2   | 48   |
|  |   |                        | Built-in zero-cross circuit | PC4SF21YVZBF*2 / PC4SF21YVZCF*1 /<br>PC4SF21YWPSF*2   | 49   |
|  | AC 200 V lines<br>(V <sub>DRM</sub> = 800V)         | 0.1 A                  | General purpose             | PC4SD11NTZBF*2 / PC4SD11NTZCF*1   | 48   |
| Built-in zero-cross circuit  | PC4SD21NTZCF*1 / PC4SD21NTZDF*5                     | 49                     |                             |   |      |
| Reinforced isolation   | PC4SF11YVZAF*3 / PC4SF11YVZBF*2                     | 48                     |                             |   |      |
| Built-in zero-cross circuit  | PC4SF21YVZBF*2 / PC4SF21YVZCF*1 /<br>PC4SF21YWPSF*2 | 49                     |                             |   |      |

Minimum trigger current: \*1 I<sub>FT</sub> ≦ 5 mA, \*2 I<sub>FT</sub> ≦ 7 mA, \*3 I<sub>FT</sub> ≦ 10 mA, \*4 I<sub>FT</sub> ≦ 15 mA, \*5 I<sub>FT</sub> ≦ 3 mA



## Phototriac Couplers

○: Approved

(Ta = 25°C)

| Model No.    | Internal connection diagram | Features   | Approved by safety standards*4 |     |        | Package         | Absolute maximum ratings                  |  |  | Electro-optical characteristics |
|--------------|-----------------------------|--|--------------------------------|-----|--------|-----------------|---|--|--|---------------------------------|
|              |                             |  | UL, CSA                        | VDE | Others |                 | ON-state current I <sub>T</sub> (rms) (A) | Repetitive peak OFF-state voltage V <sub>DRM</sub> (V) | Isolation voltage (AC) V <sub>iso</sub> (rms) (kV) |                                 |
| S2S3000F     |                             | 200 V lines, compact   | ○                              | ○*6 | —      | Mini-flat 4-pin | 0.05                                      | 600  | 3.75   | 10                              |
| S2S5A00F     |                             | 200 V lines, compact   | ○                              | ○*6 | —      |                 |   |  |  | 10                              |
| S2S5FA0F     |                             | High impulse noise product   | ○                              | ○*6 | —      |                 |   |  |  | 10                              |
| PC3ST11NSZAX |                             | 200 V lines, compact   | ○                              | ○*6 | —      | 4-pin DIP       | 0.1                                       | 5.0  | 10   | 10                              |
| PC3SH11YFZAX |                             | 200 V lines, compact, reinforced isolation                           | ○                              | ○   | ○*2    |                 |   |  |  | 10                              |
| PC3SH13YFZAX |                             | 200 V lines, compact, reinforced isolation, high noise resistance    | ○                              | ○   | ○*2    |                 |   |  |  | 10                              |
| PC2SD11NTZAF |                             | 100 V lines  | ○                              | —   | —      | 6-pin DIP*1,3   | 0.1                                       | 5.0  | 10   | 10                              |
| PC1S3021NTZF |                             | 100 V lines  | ○                              | —   | ○*2    |                 |   |  |  | 10                              |
| PC3SD12NTZAF |                             | 200 V lines  | ○                              | ○*6 | —      |                 |   |  |  | 10                              |
| PC1S3052YTZF |                             | 200 V lines  | ○                              | ○*6 | ○*2    |                 |   |  |  | 10                              |
| PC3SD12NTZBF |                             | 200 V lines  | ○                              | ○*6 | —      |                 |   |  |  | 7                               |
| PC3SD13NTZBF |                             | High impulse noise product   | ○                              | ○*6 | —      |                 |   |  |  | 7                               |
| PC3SD12NTZCF |                             | 200 V lines  | ○                              | ○*6 | —      |                 |   |  |  | 5                               |
| PC4SD11NTZBF |                             | 200 V lines, repetitive peak-OFF-state voltage                       | ○                              | ○*6 | —      |                 |   |  |  | 7                               |
| PC3SD11NTZCF |                             | 200 V lines  | ○                              | ○*6 | —      |                 |   |  |  | 5                               |
| PC4SD11NTZCF |                             | 200 V lines, repetitive peak-OFF-state voltage                       | ○                              | ○*6 | —      |                 |   |  |  | 5                               |
| PC3SF11YVZAF |                             | 200 V lines, reinforced isolation                                    | ○                              | ○   | ○*2    |                 |   |  |  | 10                              |
| PC3SF11YVZBF |                             | 200 V lines, reinforced isolation                                    | ○                              | ○   | ○*2    |                 |   |  |  | 7                               |
| PC3SF13YVZBF |                             | 200 V lines, reinforced isolation, high noise resistance             | ○                              | ○   | ○*2    |                 |   |  |  | 7                               |
| PC4SF11YVZAF |                             | 200 V lines, reinforced isolation, repetitive peak-OFF-state voltage | ○                              | ○   | ○*2    |                 |   |  |  | 10                              |
| PC4SF11YVZBF |                             | 200 V lines, reinforced isolation, repetitive peak-OFF-state voltage | ○                              | ○   | ○*2    |                 |   |  |  | 7                               |

For the notes \*1 to \*6, see next page.

### Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc. Except where specially indicated, models listed on this page comply with the RoHS Directive\*. For details, please contact SHARP. \*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions. Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.




## Phototriac Couplers (Built-in zero-cross circuit type)

○: Approved

(Ta = 25°C)

| Model No.    | Internal connection diagram | Features   | Approved by safety standards*4 |     |        | Package         | Absolute maximum ratings                  |  |  | Electro-optical characteristics |  |
|--------------|-----------------------------|--|--------------------------------|-----|--------|-----------------|---|--|--|---------------------------------|--|
|              |                             |  | UL, CSA                        | VDE | Others |                 | ON-state current I <sub>T</sub> (rms) (A) | Repetitive peak OFF-state V <sub>DRM</sub> (V) | Isolation voltage (AC) V <sub>iso</sub> (rms) (kV) |                                 | Min. trigger current I <sub>FT</sub> (mA) MAX. V <sub>D</sub> = 4 V, R <sub>L</sub> = 100Ω |
| S2S4000F     |                             | 200 V lines, compact   | ○                              | ○*6 | —      | Mini-flat 4-pin | 0.05                                      | 600  | 3.75   | 10*5                            |  |
| PC3ST21NSZBX |                             | 200 V lines, compact   | ○                              | ○*6 | —      | 4-pin DIP       | 0.1                                       | 600  | 5.0  | 7                               |  |
| PC3SH21YFZBX |                             | 200 V lines, compact, reinforced isolation                           | ○                              | ○   | ○*2    |                 |   |  |  | 7                               |  |
| PC3SD21NTZAF |                             | 200 V lines, low zero-cross voltage: MAX. 20 V                       | ○                              | ○*6 | —      | 6-pin DIP*1,3   | 0.1                                       | 600  | 5.0  | 10                              |  |
| PC3SD21NTZBF |                             | 200 V lines, low zero-cross voltage: MAX. 20 V                       | ○                              | ○*6 | —      |                 |   |  |  | 7                               |  |
| PC3SD21NTZCF |                             | 200 V lines, low zero-cross voltage: MAX. 20 V                       | ○                              | ○*6 | —      |                 |   |  |  | 5                               |  |
| PC1S3063YTZF |                             | 100 V lines, low zero-cross voltage: MAX. 20 V                       | ○                              | ○*6 | ○*2    |                 |   |  |  | 5                               |  |
| PC3SD23YTZCF |                             | 200 V lines, high pulse/noise resistance (TYP. 2 kV)                 | ○                              | ○   | —      |                 |   |  |  | 5                               |  |
| PC3SD21NTZDF |                             | 200 V lines, low zero-cross voltage: MAX. 20 V                       | ○                              | ○*6 | —      |                 |   |  |  | 3                               |  |
| PC4SD21NTZCF |                             | 200 V lines, repetitive peak-OFF-state voltage                       | ○                              | ○*6 | —      |                 |   |  |  | 5                               |  |
| PC4SD21NTZDF |                             | 200 V lines, repetitive peak-OFF-state voltage                       | ○                              | ○*6 | —      |                 |   |  |  |                                 | 3  |
| PC3SF21YVZAF |                             | 200 V lines, reinforced isolation                                    | ○                              | ○   | ○*2    |                 |   |  |  | 10                              |  |
| PC3SF21YVZBF |                             | 200 V lines, reinforced isolation                                    | ○                              | ○   | ○*2    |                 |   |  |  |                                 | 7  |
| PC3SF23YVZSF |                             | High impulse noise product   | ○                              | ○   | ○*2    |                 |   |  |  | 7                               |  |
| PC4SF21YVZBF |                             | 200 V lines, reinforced isolation, repetitive peak-OFF-state voltage | ○                              | ○   | ○*2    |                 |   |  |  | 7                               |  |
| PC4SF21YVZCF |                             | 200 V lines, reinforced isolation, repetitive peak-OFF-state voltage | ○                              | ○   | ○*2    |                 |   |  |  |                                 | 5  |
| PC4SF21YWPSF |                             | High impulse noise product   | ○                              | ○   | ○*2    |                 |   |  |  | 6-pin DIP*3                     | 7  |

\*1 Lead forming type for surface mounting is also available.  
 \*2 In conformance with BSI, SEMKO, DEMKO, and FIMKO  
 \*3 These are molded pin No. 5.  
 \*4 Please refer to Specification Sheets for model numbers approved by safety standards.  
 \*5 V<sub>D</sub> = 6 V, R<sub>L</sub> = 100Ω  
 \*6 Optionally available







### Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc. Except where specially indicated, models listed on this page comply with the RoHS Directive\*. For details, please contact SHARP. \*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions. Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.



## ■ Solid State Relay Lineup

| Package  | Applied voltage | ON-state current (rms) | Features  | Model No.   | Page  |
|--|-----------------|------------------------|---|---|-------|
| <br>DIP 6-pin   | AC 100 V lines  | 0.15 A                 | General purpose                                 | PR22MA11NTZF  | 51    |
|  |                 | 0.06 A                 | General purpose                                 | PR31MA11NTZF  | 51    |
|  | AC 200 V lines  | 0.15 A                 | General purpose                                 | PR32MA11NTZF  | 51    |
|  |                 | 0.3 A                  | General purpose                                 | PR33MA series   | 51    |
| <br>DIP 8-pin   | AC 100 V lines  | 0.3/0.6/0.9 A          | General purpose                                 | PR23MF11NSZF / PR26MF series / PR29MF series                        | 51    |
|  |                 | 0.6/0.9 A              | Built-in zero-cross circuit                     | PR26MF21NSZF / PR29MF21NSZF   | 51    |
|  | AC 200 V lines  | 0.3/0.6/0.9/1.2 A      | General purpose                                 | PR33MF5 series / PR39MF5 series / PR36MF5 series / PR3BMF5 series   | 51    |
|  |                 | 0.6/0.9/1.2 A          | Built-in zero-cross circuit                     | PR36MF2 series / PR39MF2 series / PR3BMF21NSZF                      | 51    |
| <br><br>SIP 4-pin<br>Low profile | AC 100 V lines  | 2/8 A<br>3 to 16 A     | General purpose                                 | S102T01F*1 / S108T01F*1 / S101S05F / S102S01F / S112S01F / S116S01F | 52    |
|  |                 | 2/8 A<br>3 to 16 A     | Built-in zero-cross circuit                     | S102T02F*1 / S108T02F*1 / S101S06F / S102S02F / S116S02F            | 52    |
|  |                 | 8 A                    | Built-in snubber circuit                        | S102S11F  | 52    |
|  |                 | 3/8 A                  | Built-in snubber circuit/<br>zero-cross circuit | S101S16F / S102S12F   | 52    |
|  | AC 200 V lines  |                        | General purpose                                 | S202T01F*1 / S208T01F*1 / S202S01F / S212S01F / S216S01F            | 52    |
|  |                 | 2/8 A<br>3 to 16 A     | Built-in zero-cross circuit                     | S202T02F*1 / S208T02F*1 / S201S06F / S202S02F / S216S02F            | 52/53 |
|  |                 | 8/8 A                  | Built-in snubber circuit                        | S202S15F / S202S11F   | 53    |
|  |                 | 8 A                    | Built-in snubber circuit/<br>zero-cross circuit | S202S12F  | 53    |

\*1 Low profile

## Solid State Relays

<DIP type>


○: Approved

(Ta = 25°C)

| Model No.      | Internal connection diagram   | Features   | Approved by safety standards*1 |     |       | Package   | Absolute maximum ratings                  |  |  | Electrical characteristics<br>Min. trigger current I <sub>FT</sub> (mA) MAX. V <sub>D</sub> = 6 V, R <sub>L</sub> = 100Ω |
|----------------|---|--|--------------------------------|-----|-------|-----------|---|--|--|--|
|                |   |  | UL                             | CSA | VDE*2 |           | ON-state current I <sub>T</sub> (rms) (A) | Repetitive peak OFF-state voltage V <sub>DRM</sub> (V) | Isolation voltage (AC) V <sub>iso</sub> (rms) (kV) |  |
| PR22MA11NTZF   |   | 100 V lines, 150 mA model in a small package       | ○                              | ○   | ○     | 6-pin DIP | 0.15                                      | 400  | 5.0  | 10   |
| PR31MA11NTZF   |   | 200 V lines, compact                               | ○                              | ○   | ○     |           | 0.06                                      |  |  | 10   |
| PR32MA11NTZF   |   | 200 V lines, 150 mA model in a small package       | ○                              | ○   | ○     |           | 0.15                                      | 600  |  | 10   |
| ☆PR33MA series |   | 200 V lines, 300 mA model in a small package       | ○                              | ○   | ○     |           | 0.3                                       |  |  | 15   |
| PR23MF11NSZF   |   | 100 V lines, compact                               | ○                              | ○   | —     | 8-pin DIP | 0.3                                       | 400  | 4.0  | 10   |
| PR26MF11NSZF   |   | 100 V lines, compact                               | ○                              | ○   | —     |           | 0.6                                       |  |  | 10   |
| PR26MF12NSZF   |   | 100 V lines, compact, low input current            | ○                              | ○   | —     |           |   |  |  | 0.9  |
| PR29MF11NSZF   |   | 100 V lines, compact                               | ○                              | ○   | —     |           | 0.3                                       |  |  |  |
| PR29MF12NSZF   |   | 100 V lines, compact, low input current            | ○                              | ○   | —     |           |   | 600  |  | 5  |
| PR33MF51NSLF   |   | 200 V lines, compact                               | ○                              | ○   | ○     |           | 0.6                                       |  |  | 10   |
| PR33MF52NSLF   |   | 200 V lines, compact                               | ○                              | ○   | ○     |           |   |  |  | 0.9  |
| PR36MF51NSLF   |   | 200 V lines, compact                               | ○                              | ○   | ○     |           | 1.2                                       |  |  |  |
| PR36MF12NSZF   |   | 200 V lines, compact, low input current            | ○                              | ○   | ○     |           |   | 600  |  | 10   |
| PR39MF51NSLF   |   | 200 V lines, compact                               | ○                              | ○   | ○     |           | 0.6                                       |  |  | 5  |
| PR39MF12NSZF   |   | 200 V lines, compact, low input current            | ○                              | ○   | ○     |           |   |  |  | 0.9  |
| PR3BMF51NSLF   |   | 200 V lines, compact                               | ○                              | ○   | ○     |           | 1.2                                       |  |  |  |
| PR3BMF52NSZF   |   | 200 V lines, compact, low input current            | ○                              | ○   | ○     |           |   | 600  |  | 10   |
| PR26MF21NSZF   |   | 100 V lines, compact (built-in zero-cross circuit) | ○                              | ○   | —     |           | 0.9                                       |  |  | 10   |
| PR29MF21NSZF   |   | 100 V lines, compact (built-in zero-cross circuit) | ○                              | ○   | —     |           |   |  |  | 0.6  |
| PR36MF21NSZF   |   | 200 V lines, compact (built-in zero-cross circuit) | ○                              | ○   | ○     |           | 0.9                                       |  |  |  |
| PR36MF22NSZF   | 200 V lines, compact (built-in zero-cross circuit), low input current | ○  | ○                              | ○   | 1.2   | 10        |   |  |  |  |
| PR39MF21NSZF   | 200 V lines, compact (built-in zero-cross circuit)                    | ○  | ○                              | ○   |       | 0.6       | 5   |  |  |  |
| PR39MF22NSZF   | 200 V lines, compact (built-in zero-cross circuit), low input current | ○  | ○                              | ○   | 0.9   |           | 10  |  |  |  |
| PR3BMF21NSZF   | 200 V lines, compact (built-in zero-cross circuit)                    | ○  | ○                              | ○   |       | 1.2       | 5   |  |  |  |

\*1 Please refer to Specification Sheets for model numbers approved by safety standards.

\*2 Optionally available.



PR22MA11NTZF  
(6-pin DIP)

PR26MF21NSZF  
(8-pin DIP)

**Notice**

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.

Except where specially indicated, models listed on this page comply with the RoHS Directive\*. For details, please contact SHARP. \*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.

Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.



<SIP type> (1)

○: Approved

(Ta = 25°C)

| Model No. | Internal connection diagram | Features  | Approved by safety standards*6 |     | Package               | Absolute maximum ratings                  |  |  | Electrical characteristics                     |                    |                    |
|-----------|-----------------------------|---|--------------------------------|-----|-----------------------|---|--|--|--|--------------------|--------------------|
|           |                             |   | UL                             | CSA |                       | ON-state current I <sub>T</sub> (rms) (A) | Repetitive peak OFF-state voltage V <sub>DRM</sub> (V) | Isolation voltage (AC) V <sub>iso</sub> (rms) (kV) | Min. trigger current I <sub>FT</sub> (mA) MAX. | V <sub>D</sub> (V) | R <sub>L</sub> (Ω) |
| S102T01F  |                             | 100 V lines, low profile  | ○                              | ○   | Low profile 4-pin SIP | 2   | 3.0  | 3.0  | 8  | 12                 | 30                 |
| S108T01F  |                             | 100 V lines, low profile  | -                              | -   |                       | 8*2                                       |  |  | 8  | 12                 | 30                 |
| S102T02F  |                             | 100 V lines, low profile (built-in zero-cross circuit)              | ○                              | ○   |                       | 2   |  |  | 8  | 12                 | 30                 |
| S108T02F  |                             | 100 V lines, low profile (built-in zero-cross circuit)              | -                              | -   |                       | 8*2                                       |  |  | 8  | 12                 | 30                 |
| S101S05F  |                             | 100 V lines   | ○                              | ○   | 4-pin SIP             | 3*3                                       | 400  | 4.0  | 15   | 12                 | 30                 |
| S102S01F  |                             | 100 V lines   | ○                              | ○   |                       | 8*2                                       |  |  | 8  | 12                 | 30                 |
| S112S01F  |                             | 100 V lines   | ○                              | ○   |                       | 12*4                                      |  |  | 8  | 12                 | 30                 |
| S116S01F  |                             | 100 V lines   | ○                              | ○   |                       | 16*5                                      |  |  | 8  | 12                 | 30                 |
| S101S06F  |                             | 100 V lines (built-in zero-cross circuit)                           | ○                              | ○   |                       | 3*3                                       |  | 3.0  | 15   | 6                  | 30                 |
| S102S02F  |                             | 100 V lines (built-in zero-cross circuit)                           | ○                              | ○   |                       | 8*2                                       |  | 4.0  | 8  | 6                  | 30                 |
| S116S02F  |                             | 100 V lines (built-in zero-cross circuit)                           | ○                              | ○   |                       | 16*5                                      |  |  | 8  | 6                  | 30                 |
| S102S11F  |                             | 100 V lines (built-in snubber circuit)                              | ○                              | ○   |                       | 8*1                                       |  | 3.0  | 4.0  | 8                  | 12                 |
| S101S16F  |                             | 100 V lines (built-in snubber circuit, built-in zero-cross circuit) | ○                              | ○   | 3*3                   | 15  | 6  |  |  | 30                 |                    |
| S102S12F  |                             | 100 V lines (built-in snubber circuit, built-in zero-cross circuit) | ○                              | ○   | 8*1                   | 8   | 6  |  |  | 30                 |                    |
| S202T01F  |                             | 200 V lines, low profile  | ○                              | ○   | Low profile 4-pin SIP | 2   | 600  |  |  | 3.0                | 8                  |
| S208T01F  |                             | 200 V lines, low profile  | -                              | -   |                       | 8*2                                       |  | 8  | 12   |                    | 30                 |
| S202T02F  |                             | 200 V lines, low profile (built-in zero-cross circuit)              | ○                              | ○   |                       | 2   |  | 8  | 12   |                    | 30                 |
| S208T02F  |                             | 200 V lines, low profile (built-in zero-cross circuit)              | -                              | -   |                       | 8*2                                       |  | 8  | 12   |                    | 30                 |
| S202S01F  |                             | 200 V lines   | ○                              | ○   | 4-pin SIP             | 8*2                                       | 4.0  | 4.0  | 8  | 12                 | 30                 |
| S212S01F  |                             | 200 V lines   | -                              | -   |                       | 12*4                                      |  |  | 8  | 12                 | 30                 |
| S216S01F  |                             | 200 V lines   | -                              | -   |                       | 16*5                                      |  |  | 8  | 12                 | 30                 |

For the notes \*1 to \*6, see next page.

**Notice**

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.  
 Except where specially indicated, models listed on this page comply with the RoHS Directive\*. For details, please contact SHARP.  
 \*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.  
 Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.



## <SIP type> (2)

○: Approved

(Ta = 25°C)

| Model No. | Internal connection diagram | Features  | Approved by safety standards*6 |     | Package   | Absolute maximum ratings                  |  |  | Electrical characteristics                     |                    |                    |    |
|-----------|-----------------------------|---|--------------------------------|-----|-----------|---|--|--|--|--------------------|--------------------|----|
|           |                             |   | UL                             | CSA |           | ON-state current I <sub>T</sub> (rms) (A) | Repetitive peak OFF-state voltage V <sub>DRM</sub> (V) | Isolation voltage (AC) V <sub>iso</sub> (rms) (kV) | Min. trigger current I <sub>FT</sub> (mA) MAX. | V <sub>D</sub> (V) | R <sub>L</sub> (Ω) |    |
| S201S06F  |                             | 200 V lines (built-in zero-cross circuit)                           | ○                              | ○   | 4-pin SIP | 3*3                                       | 600  | 3.0  | 15   | 6                  | 30                 |    |
| S202S02F  |                             | 200 V lines (built-in zero-cross circuit)                           | ○                              | ○   |           | 8*2                                       |  |  | 4.0  | 8                  | 6                  | 30 |
| S216S02F  |                             | 200 V lines (built-in zero-cross circuit)                           | —                              | —   |           | 16*5                                      |  | 8  |  | 6                  | 30                 |    |
| S202S15F  |                             | 200 V lines (built-in snubber circuit)                              | —                              | —   |           | 8*2                                       |  | 600  | 3.0  | 15                 | 12                 | 30 |
| S202S11F  |                             | 200 V lines (built-in snubber circuit)                              | ○                              | ○   |           | 8*1                                       |  |  |  | 4.0                | 8                  | 12 |
| S202S12F  |                             | 200 V lines (built-in snubber circuit, built-in zero-cross circuit) | ○                              | ○   |           | 8*1                                       |  |  | 8  |                    | 6                  | 30 |

\*1 T<sub>c</sub> ≤ 88°C

\*2 T<sub>c</sub> ≤ 80°C

\*3 T<sub>c</sub> ≤ 100°C

\*4 T<sub>c</sub> ≤ 70°C

\*5 T<sub>c</sub> ≤ 60°C

\*6 Please refer to Specification Sheets for model numbers approved by safety standards.



**Notice**

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc. Except where specially indicated, models listed on this page comply with the RoHS Directive\*. For details, please contact SHARP. \*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions. Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.



## ■ Photointerrupter Lineup

### <Transmissive type>

| Output type                | Package type   | Outline                             | Mounting method                         | Model No. (series)  | Page |
|----------------------------|----------------|-------------------------------------|---|---|------|
| Single phototransistor     | Compact        | High resolution                     | PWB mounting type                       | GP1S396HCP0F / GP1S09xHCZ0F / GP1S19xHCZ0F                | 55   |
| High response speed        | Case type      | High resolution                     | Surface-mount type/<br>Soldering reflow | GP1S396HCPSF / GP1S296HCPSF / GP1S092HCPIF / GP1S19xHCxSF | 55   |
|                            |                |                                     | PWB mounting type, etc.                 | GP1S5x series   | 56   |
|                            |                | Horizontal slit,<br>High resolution | PWB mounting type                       | GP1S59J0000F  | 56   |
|                            | With connector | General purpose                     | Snap-in                                 | GP1S173LCS2F / GP1S273LCS1F                               | 56   |
| Darlington phototransistor | Case type      | General purpose                     | PWB mounting type, etc.                 | GP1L5x series   | 57   |
| High sensitivity           |                | Wide gap                            | PWB mounting type                       | GP1L57J0000F  | 57   |
| Digital output             | Compact        | High voltage                        | PWB mounting type                       | GP1A98HCZ0F   | 57   |
| (OPIC output)              |                |                                     | Surface-mount type                      | GP1A98HCPSF   | 57   |
|                            | Case type      | High resolution                     | With screw hole/<br>PWB mounting type   | GP1A5x series   | 58   |
|                            |                | Wide gap                            | PWB mounting type                       | GP1A57HRJ00F  | 58   |
|                            | With connector | General purpose                     | Screw mounting type/Snap-in             | GP1A173LCS3F / GP1A173LCS2F / GP1A173LCSVF / GP1A273LCS1F | 59   |

### <Reflective type>

| Output type            | Package type                | Outline  | Mounting method  | Model No. (series)  | Page |
|------------------------|-----------------------------|--|--|---|------|
| Single phototransistor | Leadless                    | Long focal distance                            | Surface-mount type   | GP2S700HCP  | 59   |
| High response speed    | Compact,<br>thin (leadless) | General purpose                                | Surface-mount type   | GP2S60  | 59   |
| OPIC output            | With connector              | Light modulation type,<br>Sensitivity adjusted | Screw mounting type/<br>Compact snap-in/<br>Inverter light countermeasures | GP2A25 series / GP2A28 series / GP2A200LCS0F / GP2A230LRS0F / GP2A231LRS0F / GP2A230LRS0F / GP2A240LCS0F / GP2A250LCS0F | 60   |

### <Application-specific photointerrupter lineup>

| Detection type    | Outline (Output type etc.)  | Mounting method  | Model No. (series)   | Page                                  |              |
|-------------------|---|--|--|---------------------------------------|--------------|
| Transmissive type | Case type<br>With encoder function<br>Digital 2 output<br>(phase A/B) | Resolution: 45 LPI<br>Linear scale slit pitch:<br>0.56 mm                      | PWB mounting type  | GP1A057SGKLF                          | 61           |
|                   |   | Resolution: 150 LPI<br>Linear scale slit pitch:<br>0.17 mm                     | PWB mounting type  | GP1A057RBKLF                          | 61           |
|                   |   | Resolution: 180 LPI<br>Linear scale slit pitch:<br>0.14 mm                     | With screw hole/<br>PWB mounting type  | GP1A058SCK0F                          | 61           |
|                   |   | Resolution: 300 LPI<br>Linear scale slit pitch:<br>0.0847 mm                   | With screw hole/<br>PWB mounting type  | GP1A054RDKLF                          | 61           |
|                   |   | Case type<br>With encoder function<br>Digital 2 output<br>(Multiplying output) | Resolution for reading:<br>180 LPI<br>Pitch: 0.14 mm<br>Output resolution: 360 LPI | With screw hole/<br>PWB mounting type | GP1A101C2KSF |
|                   | For amusement use   |  | Screw mounting   | GP1A204HCS0                           | 61           |
| Reflective type   | Injection<br>For prism system (Single phototransistor)                |  | Screw mounting   | GP2S29SVJ00F                          | 61           |
|                   | For amusement use (Pachinko ball sensor)                              |  | –  | GP2A222HCKA                           | 62           |





### ■ Photointerrupters

<Transmissive type>

◆ Single Phototransistor Output


<Compact type>

(Ta = 25°C)

| Model No.                    | Internal connection diagram | Features  | Detecting and emitting gap (mm) | Slit width (mm) | Electro-optical characteristics |         |         |               |         |         |         |
|------------------------------|-----------------------------|---|---------------------------------|-----------------|---------------------------------|---------|---------|---------------|---------|---------|---------|
|                              |                             |   |                                 |                 | Current transfer ratio          |         |         | Response time |         |         |         |
|                              |                             |   |                                 |                 | CTR (%) MIN.                    | If (mA) | VCE (V) | tr (μs) TYP.  | Ic (mA) | RL (kΩ) | VCE (V) |
| GP1S092HCPIF                 |                             | Wide gap, for soldering reflow, surface mount compatible, with positioning boss (4.5 × 2.6 × 2.9 [height] mm) | 2.0                             | 0.3             | 2.0                             | 5       | 5       | 50            | 0.1     | 1       | 5       |
| GP1S093HCZ0F                 |                             | Wide gap (4.5 × 2.6 × 2.9 [height] mm)  | 2.0                             | 0.3             | 2.0                             | 5       | 5       | 50            | 0.1     | 1       | 5       |
| GP1S094HCZ0F                 |                             | Wide gap, with positioning pin, (5.5 × 2.6 × 4.8 [height] mm)   | 3.0                             | 0.3             | 0.8                             | 5       | 5       | 50            | 0.1     | 1       | 5       |
| GP1S096HCZ0F                 |                             | Narrow gap (3.5 × 2.6 × 2.9 [height] mm)  | 1.0                             | 0.3             | 2.0                             | 5       | 5       | 50            | 0.1     | 1       | 5       |
| GP1S194HCZ0F                 |                             | Compact, wide gap, size: 3.6 × 2.0 × 2.7 (height) mm  | 1.7                             | 0.3             | 3.0                             | 5       | 5       | 50            | 0.1     | 1       | 5       |
| GP1S195HCZSF<br>GP1S195HCPSF |                             | Compact, wide gap, surface mount compatible, size: 3.4 × 2.0 × 2.7 (height) mm                                | 1.5                             | 0.3             | 3.0                             | 5       | 5       | 50            | 0.1     | 1       | 5       |
| GP1S196HCZ0F                 |                             | Compact, low profile (3.1 × 2.0 × 2.7 [height] mm)  | 1.1                             | 0.3             | 2.0                             | 5       | 5       | 50            | 0.1     | 1       | 5       |
| GP1S196HCZSF<br>GP1S196HCPSF |                             | Surface mount, for soldering reflow, compact, low profile (3.1 × 2.0 × 2.7 [height] mm)                       | 1.1                             | 0.3             | 2.0                             | 5       | 5       | 50            | 0.1     | 1       | 5       |
| GP1S296HCPSF                 |                             | Surface mount, for soldering reflow, compact, low profile (2.5 × 1.8 × 1.9 [height] mm)                       | 1.0                             | 0.2             | 3.0                             | 5       | 5       | 50            | 0.1     | 1       | 5       |
| GP1S396HCP0F                 |                             | Straight lead type, compact, low profile (2.26 × 1.4 × 1.6 [height] mm)                                       | 1.2                             | 0.12            | 2.0                             | 5       | 5       | 30            | 0.1     | 1       | 5       |
| GP1S396HCPSF                 |                             | Surface mount, for soldering reflow, compact, low profile (2.26 × 1.4 × 1.6 [height] mm)                      | 1.2                             | 0.12            | 2.0                             | 5       | 5       | 30            | 0.1     | 1       | 5       |
| GP1S097HCZ0F                 |                             | High resolution, wide gap, with mounting hole (4.5 × 2.6 × 4.5 [height] mm)                                   | 2.0                             | 0.3             | 2.0                             | 5       | 5       | 50            | 0.1     | 1       | 5       |

\* Topr: -25 to +85°C

\*\* GP1SxxxHCZxF: Sleeve package, GP1SxxxHCPxF: Taped package



#### Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.  
 Except where specially indicated, models listed on this page comply with the RoHS Directive\*. For details, please contact SHARP.  
 \*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.  
 Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.




### <Case type>

(Ta = 25°C)

| Model No.    | Internal connection diagram | Features  | Detecting and emitting gap (mm) | Slit width (mm) | Electro-optical characteristics |         |         |               |         |        |         |
|--------------|-----------------------------|---|---------------------------------|-----------------|---------------------------------|---------|---------|---------------|---------|--------|---------|
|              |                             |   |                                 |                 | Current transfer ratio          |         |         | Response time |         |        |         |
|              |                             |   |                                 |                 | CTR (%) MIN.                    | IF (mA) | VCE (V) | tr (μs) TYP.  | Ic (mA) | RL (Ω) | VCE (V) |
| GP1S50J000F  |                             | High resolution, both-side mounting type                                  | 3.0                             | 0.5             | 2.5                             | 20      | 5       | 3             | 2       | 100    | 2       |
| GP1S51VJ000F |                             | High resolution, side mounting type                                       | 3.0                             | 0.5             | 2.5                             | 20      | 5       | 3             | 2       | 100    | 2       |
| GP1S52VJ000F |                             | High resolution, PWB mounting type  | 3.0                             | 0.5             | 2.5                             | 20      | 5       | 3             | 2       | 100    | 2       |
| GP1S53VJ000F |                             | High resolution, PWB mounting type  | 5.0                             | 0.5             | 2.5                             | 20      | 5       | 3             | 2       | 100    | 2       |
| GP1S54J0000F |                             | High resolution, with positioning pin, PWB mounting type                  | 3.0                             | 0.5             | 2.5                             | 20      | 5       | 3             | 2       | 100    | 2       |
| GP1S56TJ000F |                             | High resolution, with positioning pin, PWB mounting type                  | 2.0                             | 0.15            | 2.0                             | 20      | 5       | 38            | 0.5     | 1 000  | 2       |
| GP1S58VJ000F |                             | High resolution, with positioning pin, PWB mounting type                  | 5.0                             | 0.5             | 2.5                             | 20      | 5       | 3             | 2       | 100    | 2       |
| GP1S59J0000F |                             | High resolution, horizontal slit, with positioning pin, PWB mounting type | 4.2                             | 0.5             | 2.5                             | 20      | 5       | 3             | 2       | 100    | 2       |

\* Topr: -25 to +85°C




### <With connector>

(Ta = 25°C)

| Model No.    | Internal connection diagram | Features  | Detecting and emitting gap (mm) | Slit width (mm) | Electro-optical characteristics |         |         |               |         |        |         |
|--------------|-----------------------------|---|---------------------------------|-----------------|---------------------------------|---------|---------|---------------|---------|--------|---------|
|              |                             |   |                                 |                 | Current transfer ratio          |         |         | Response time |         |        |         |
|              |                             |   |                                 |                 | CTR (%) MIN.                    | IF (mA) | VCE (V) | tr (μs) TYP.  | Ic (mA) | RL (Ω) | VCE (V) |
| GP1S173LCS2F |                             | Snap-in mounting integrated connector type<br>Applicable to 3 kinds of thickness of mounting boards   | 5.0                             | 0.5             | 2.5                             | 20      | 5       | 3             | 2       | 100    | 2       |
| GP1S273LCS1F |                             | Snap-in mounting integrated connector type<br>Applicable to 3 kinds of thickness of mounting boards<br>Compact (Compatible with 1.5 mm pitch connector) | 5.0                             | 0.7             | 2.5                             | 20      | 5       | 3             | 2       | 100    | 2       |

\* Topr: -25 to +85°C, -30 to +95°C (GP1S173LCS2F, GP1S273LCS1F)



#### Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.  
 Except where specially indicated, models listed on this page comply with the RoHS Directive\*. For details, please contact SHARP.  
 \*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.  
 Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.



### ◆Darlington Phototransistor Output <Case type>

(Ta = 25°C)

| Model No.    | Internal connection diagram | Features                                      | Detecting and emitting gap (mm) | Slit width (mm) | Electro-optical characteristics |         |         |               |         |        |         |
|--------------|-----------------------------|---|---------------------------------|-----------------|---------------------------------|---------|---------|---------------|---------|--------|---------|
|              |                             |   |                                 |                 | Current transfer ratio          |         |         | Response time |         |        |         |
|              |                             |   |                                 |                 | CTR (%) MIN.                    | IF (mA) | VCE (V) | tr (μs) TYP.  | IC (mA) | RL (Ω) | VCE (V) |
| GP1L50J0000F |                             | High sensitivity, both-side mounting type     | 3.0                             | 0.5             | 50                              | 1       | 2       | 80            | 2       | 100    | 2       |
| GP1L51J0000F |                             | High sensitivity, side mounting type          | 3.0                             | 0.5             | 50                              | 1       | 2       | 80            | 2       | 100    | 2       |
| GP1L52VJ000F |                             | High sensitivity, PWB mounting type           | 3.0                             | 0.5             | 50                              | 1       | 2       | 80            | 2       | 100    | 2       |
| GP1L53VJ000F |                             | High sensitivity, PWB mounting type           | 5.0                             | 0.5             | 30                              | 1       | 2       | 80            | 2       | 100    | 2       |
| GP1L57J0000F |                             | High sensitivity, wide gap, PWB mounting type | 10.0                            | 1.8             | 70                              | 1       | 2       | 130           | 2       | 100    | 2       |

\* Topr: -25 to +85°C




### ◆OPIC Type ( "OPIC" (Optical IC) is a trademark of SHARP Corporation. An OPIC consists of a light-detecting element and signal-processing circuit integrated onto a single chip. ) <Compact type>

(Ta = 25°C)

| Model No.   | Internal connection diagram | Features               | Detecting and emitting gap (mm) | Slit width (mm) | Electro-optical characteristics |                |           |           |                        |                |         |           |           |
|-------------|-----------------------------|------------------------|---------------------------------|-----------------|---------------------------------|----------------|-----------|-----------|------------------------|----------------|---------|-----------|-----------|
|             |                             |                        |                                 |                 | Threshold input current         |                |           |           | Propagation delay time |                |         |           |           |
|             |                             |                        |                                 |                 | IFLH (mA) MAX.                  | IFHL (mA) MAX. | VCC (V)   | RL (kΩ)   | tPLH (μs) TYP.         | tPHL (μs) TYP. | IF (mA) | RL (kΩ)   | VCC (V)   |
| GP1A98HCZ0F |                             | Compact, PWB mounting  | 3.2                             | 0.5             | 8                               | -              | 3.3 to 24 | 3.9 to 20 | 2.0                    | 10.0           | 10      | 3.9 to 20 | 3.3 to 24 |
| GP1A98HCPSF |                             | Compact, surface mount | 3.2                             | 0.5             | 8                               | -              | 3.3 to 24 | 3.9 to 20 | 2.0                    | 10.0           | 10      | 3.9 to 20 | 3.3 to 24 |

\* Topr = -25 to +85°C



#### Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.  
 Except where specially indicated, models listed on this page comply with the RoHS Directive\*. For details, please contact SHARP.  
 \*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.  
 Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.



### <Case type>

(Ta = 25°C)

| Model No.    | Internal connection diagram | Features                                | Detecting and emitting gap (mm) | Slit width (mm) | Electro-optical characteristics |                |         |                        |                |         |        |         |
|--------------|-----------------------------|---|---------------------------------|-----------------|---------------------------------|----------------|---------|------------------------|----------------|---------|--------|---------|
|              |                             |   |                                 |                 | Threshold input current         |                |         | Propagation delay time |                |         |        |         |
|              |                             |   |                                 |                 | IFLH (mA) MAX.                  | IFHL (mA) MAX. | VCC (V) | tPLH (μs) TYP.         | tPHL (μs) TYP. | IF (mA) | RL (Ω) | VCC (V) |
| GP1A50HRJ00F |                             | Both-side mounting, with screw hole     | 3.0                             | 0.5             | 5                               | –              | 5       | 3                      | 5              | 5       | 280    | 5       |
| GP1A51HRJ00F |                             | Side mounting, with screw hole          | 3.0                             | 0.5             | 5                               | –              | 5       | 3                      | 5              | 5       | 280    | 5       |
| GP1A52HRJ00F |                             | PWB mounting type                       | 3.0                             | 0.5             | 5                               | –              | 5       | 3                      | 5              | 5       | 280    | 5       |
| GP1A53HRJ00F |                             | PWB mounting type                       | 5.0                             | 0.5             | 8                               | –              | 5       | 3                      | 5              | 8       | 280    | 5       |
| GP1A57HRJ00F |                             | PWB mounting type, with positioning pin | 10.0                            | 1.8             | 7                               | –              | 5       | 3                      | 5              | 7       | 280    | 5       |
| GP1A58HRJ00F |                             | PWB mounting type, with positioning pin | 5.0                             | 0.5             | 8                               | –              | 5       | 3                      | 5              | 8       | 280    | 5       |
| GP1A52LRJ00F |                             | PWB mounting type                       | 3.0                             | 0.5             | –                               | 5              | 5       | 5                      | 3              | 5       | 280    | 5       |

\* Topr = –25 to +85°C



GP1A50HRJ00F

GP1A51HRJ00F

GP1A52LRJ00F  
(GP1A52HRJ00F)

GP1A53HRJ00F  
(GP1A58HRJ00F  
with positioning pin)

GP1A57HRJ00F

#### Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.  
 Except where specially indicated, models listed on this page comply with the RoHS Directive\*. For details, please contact SHARP.  
 \*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.  
 Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.

◆OPIC Type ( "OPIC" (Optical IC) is a trademark of SHARP Corporation. An OPIC consists of a light-detecting element and signal-processing circuit integrated onto a single chip. )

<With 3-pin connector terminal>

(Ta = 25°C)

| Model No.     | Internal connection diagram | Features  | Detecting and emitting gap (mm) | Slit width (mm) | Electro-optical characteristics    |      |                          |                          |                      |                     |
|---------------|-----------------------------|---|---------------------------------|-----------------|------------------------------------|------|--------------------------|--------------------------|----------------------|---------------------|
|               |                             |   |                                 |                 | Supply voltage V <sub>CC</sub> (V) |      | V <sub>OL</sub> (V) MAX. | Low level output voltage |                      |                     |
|               |                             |   |                                 |                 | MIN.                               | MAX. |                          | Light cut-off            | I <sub>oL</sub> (mA) | V <sub>CC</sub> (V) |
| ☆GP1A173LCS3F | <p>with 3-pin connector</p> | Snap-in mounting integrated connector type*1  | 5.0                             | 0.5             | 2.7                                | 5.5  | 0.35                     | No                       | 4                    | 3.3                 |
| GP1A173LCS2F  |                             | Snap-in mounting integrated connector type*1  | 5.0                             | 0.5             | 4.5                                | 5.5  | 0.35                     | No                       | 4                    | 5                   |
| GP1A173LCSVF  |                             | Snap-in mounting integrated connector type*1, enforced electrostatic discharge (ESD) type | 5.0                             | 0.5             | 4.5                                | 5.5  | 0.35                     | No                       | 4                    | 5                   |
| GP1A273LCS1F  |                             | Integrated connector, compatible with 1.5 mm pitch connector, snap-in mounting type*1     | 5.0                             | 0.7             | 4.5                                | 5.5  | 0.35                     | No                       | 4                    | 5                   |
| GP1A75EJ000F▲ |                             | Either-side mounting type<br>Screw mounting type  | 5.0                             | 0.5             | 4.5                                | 5.5  | 0.35                     | Yes                      | 16                   | 5                   |

\* Topr: -20 to +75°C, -30 to +95°C (GP1A173LCS3F, GP1A173LCS2F, GP1A173LCSVF, GP1A273LCS1F)

\*1 Applicable to 3 kinds of thickness of mounting boards.

The model marked with ▲ may not be available in the near future. Contact with SHARP for details before use.



GP1A173LCS3F,  
GP1A173LCS2F,  
GP1A173LCSVF

GP1A273LCS1F

GP1A75EJ000F▲

## Photointerrupters

### <Reflective type>


#### ◆Single Phototransistor Output

#### <Compact>

(Ta = 25°C)

| Model No.  | Internal connection diagram | Features   | Optimum detecting distance (mm) | Electro-optical characteristics |                     |                     |                          |                     |                     |                     |
|------------|-----------------------------|--|---------------------------------|---------------------------------|---------------------|---------------------|--------------------------|---------------------|---------------------|---------------------|
|            |                             |  |                                 | Current transfer ratio          |                     |                     | Response time            |                     |                     |                     |
|            |                             |  |                                 | CTR (%) MIN.                    | I <sub>F</sub> (mA) | V <sub>CE</sub> (V) | t <sub>r</sub> (μs) TYP. | I <sub>C</sub> (mA) | R <sub>L</sub> (kΩ) | V <sub>CE</sub> (V) |
| GP2S700HCP |                             | Compact (4 × 3 × 2 [height] mm), long focal distance, surface mounting leadless type | 4                               | 1.5                             | 4                   | 2                   | 20                       | 0.1                 | 1                   | 2                   |
| GP2S60     |                             | Thin (3.2 × 1.7 × 1.1 [height] mm), surface mounting leadless type                   | 1                               | 1.0                             | 4                   | 2                   | 20                       | 0.1                 | 1                   | 2                   |

\* Topr: -25 to +85°C



GP2S700HCP

GP2S60

#### Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.

Except where specially indicated, models listed on this page comply with the RoHS Directive\*. For details, please contact SHARP. \*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.

Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.



◆ **OPIC Output** (“OPIC” (Optical IC) is a trademark of SHARP Corporation. An OPIC consists of a light-detecting element and signal-processing circuit integrated onto a single chip.)

<With 3-pin connector terminal>

(Ta = 25°C)

| Model No.     | Internal connection diagram | Features  | Optimum detecting distance (mm) | Electro-optical characteristics    |      |   |                          |                          |                     |
|---------------|-----------------------------|---|---------------------------------|------------------------------------|------|---|--------------------------|--------------------------|---------------------|
|               |                             |   |                                 | Supply voltage V <sub>CC</sub> (V) |      | Dissipation current I <sub>CC</sub> (mA) MAX. | Low level output voltage |                          |                     |
|               |                             |   |                                 | MIN.                               | MAX. |   | V <sub>CC</sub> (V)      | V <sub>OL</sub> (V) MAX. | V <sub>CC</sub> (V) |
| GP2A200LCS0F  | (Following diagram [A])     | Multi types of paper detectable, light modulation type, with connector, sensitivity adjusted  | 5 to 15                         | 4.75                               | 5.25 | 30*1  | 5                        | 0.4                      | 5                   |
| GP2A240LCS0F  |                             | Applicable to inverter fluorescent lamp, light modulation type, with connector, sensitivity adjusted  | 5 to 15                         | 4.75                               | 5.25 | 30*1  | 5                        | 0.4                      | 5                   |
| GP2A250LCS0F  |                             | Static electricity resistant, applicable to inverter fluorescent lamp, light modulation type, with connector, sensitivity adjusted  | 2.5 to 12.5                     | 4.75                               | 5.25 | 30*1  | 5                        | 0.4                      | 5                   |
| GP2A25J0000F  | (Following diagram [B])     | Multi types of paper detectable, light modulation type, with connector, sensitivity adjusted  | 3 to 7                          | 4.75                               | 5.25 | 30*1  | 5                        | 0.4                      | 5                   |
| GP2A230LRS0F  |                             | Compact, hook type (GP2A231LRSAF), multi types of paper detectable, light modulation type, with connector   | 3 to 7                          | 4.75                               | 5.25 | 20*1  | 5                        | 0.4                      | 5                   |
| GP2A230LRSAF  |                             |   |                                 |                                    |      |   |                          |                          |                     |
| GP2A231LRSAF▲ |                             |   |                                 |                                    |      |   |                          |                          |                     |
| GP2A25NJJ00F  | (Following diagram [A])     | Multi types of paper detectable, light modulation type, sensitivity adjusted, improved light-resistance characteristic for inverter lighting, built-in visible light cut filter | 3 to 7                          | 4.75                               | 5.25 | 30*1  | 5                        | 0.4                      | 5                   |
| GP2A25DJ000F  |                             | Multi types of paper detectable, light modulation type, with connector, sensitivity adjusted  | 3 to 7                          | 4.75                               | 5.25 | 30*1  | 5                        | 0.4                      | 5                   |
| GP2A28AJ000F  |                             | Multi types of paper detectable, light modulation type, with connector, sensitivity adjusted, hook type   | 3 to 7                          | 4.75                               | 5.25 | 30*1  | 5                        | 0.4                      | 5                   |

\* Topr: -10 to +60°C (GP2A25J0000F, etc.)


-10 to +70°C (GP2A200LCS0F, GP2A240LCS0F, GP2A250LCS0F, GP2A230LRS0F, GP2A230LRSAF, GP2A231LRSAF)

\*1 Smoothing value R<sub>L</sub> = ∞



The model marked with ▲ may not be available in the near future. Contact with SHARP for details before use.

[Internal connection diagram]

[A]



[B]



**Notice**

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc. Except where specially indicated, models listed on this page comply with the RoHS Directive\*. For details, please contact SHARP. \*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions. Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.



## Photointerrupters for Specific Applications


### ◆ Transmissive Type

#### <Case type, with encoder function>

(Ta = 25°C)

| Model No.    | Absolute maximum ratings |            |                                | Electro-optical characteristics       |  |                                 |         |   |
|--------------|--------------------------|------------|--------------------------------|---------------------------------------|--|---------------------------------|---------|---|
|              | Vcc (V)                  | Topr (°C)  | Operating voltage Vcc (V) TYP. | Output signal                         | Resolution   | Response frequency f (kHz) MAX. | If (mA) | Dissipation current (output side) Icc (mA) MAX. |
| GP1A057RBKLF | 6                        | -10 to +70 | 3.3                            | Digital 2 output (Phase A/B)          | Linear scale slit pitch 0.17 (mm) (150LPI)                                     | 60                              | 20      | 7   |
| GP1A054RDKLF | 6                        | -10 to +70 | 3.3                            |                                       | Linear scale slit pitch 0.0847 (mm) (300LPI)                                   | 60                              | 20      | 5.5   |
| GP1A057SGKLF | 6                        | -10 to +70 | 3.3                            |                                       | Linear scale slit pitch 0.56 (mm) (45LPI)                                      | 25                              | 20      | 5.5   |
| GP1A058SCK0F | 6                        | -10 to +70 | 3.3                            |                                       | Linear scale slit pitch 0.14 (mm) (180LPI)                                     | 60                              | 20      | 5.5   |
| GP1A101C2KSF | 6.5                      | -10 to +70 | 3.3                            | Digital 2 output (Multiplying output) | Resolution for reading: 180 LPI (Pitch: 0.14 mm)<br>Output resolution: 360 LPI | 120                             | 20      | 20  |

\* High precision read and low affection of angle error from vibration thanks to the multi-segment PD system.  
Duty ratio: 50±15%, phase difference: 90±45°



#### <For amusement use>

(Ta = 0 to +40°C)

| Model No.   | Internal connection diagram | Features  | Detecting and emitting gap (mm) | Slit width (mm) | Electro-optical characteristics |      |                          |               |          |            |
|-------------|-----------------------------|---|---------------------------------|-----------------|---------------------------------|------|--------------------------|---------------|----------|------------|
|             |                             |   |                                 |                 | Operating voltage Vcc (V)       |      | Low level output voltage |               |          |            |
|             |                             |   |                                 |                 | MIN.                            | MAX. | Vol (V) MAX.             | Light cut-off | IOL (mA) | VCC (V)    |
| GP1A204HCS0 |                             | Connector with lock, screw mounting type, high resistant to noise | 4.0                             | 0.5             | 10.8                            | 24   | 0.4                      | Yes           | 5        | 10.8 to 24 |



### ◆ Reflective Type

#### <Case type, phototransistor output>

(Ta = 25°C)

| Model No.    | Internal connection diagram | Features  | Electro-optical characteristics |         |         |               |         |         |         |
|--------------|-----------------------------|---|---------------------------------|---------|---------|---------------|---------|---------|---------|
|              |                             |   | Peak photocurrent               |         |         | Response time |         |         |         |
|              |                             |   | ICP (mA)                        | If (mA) | VCE (V) | tr (μs) TYP.  | Ic (mA) | RL (kΩ) | VCE (V) |
| GP2S29SVJ00F |                             | Long focal distance (with prism system*1), compact, screw mounting type | 0.4 to 3.0*1                    | 20      | 5       | 38            | 0.5     | 1       | 2       |

\* Topr: -25 to +85°C

\*1 Space between prism and sensor is 8 mm.



#### Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.  
Except where specially indicated, models listed on this page comply with the RoHS Directive\*. For details, please contact SHARP.  
\*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.  
Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.



### <For amusement use>

(Ta = 25°C)

| Model No.   | Features   | Electro-optical characteristics |                                 |                              |
|-------------|--|---------------------------------|---------------------------------|------------------------------|
|             |  | Supply voltage<br>Vcc (V)       | Dissipation current<br>Icc (mA) | Response frequency<br>f (Hz) |
| GP2A222HCKA | Employs reflective type, pinball detector, connector with lock<br>In conjunction with an IC, detects beam interruption*1 | 4.5 to 16.5                     | MAX. 12                         | MAX. 500                     |

\*1 Used together with interface IC for control (IR3N184)



### ■ Proximity Sensor

(Ta = 25°C)

| Model No.    | Features  | Absolute maximum ratings |            | Electro-optical characteristics         |  |   |                                     |
|--------------|---|--------------------------|------------|---|--|---|-------------------------------------|
|              |   | Vcc (V)                  | Topr (°C)  | Dissipation current<br>Icc (μA)<br>TYP. | Detecting distance<br>Lon (mm)<br>MIN. | Non-detecting distance<br>Loff (mm)<br>MAX. | Peak emission wavelength<br>λp (nm) |
| GP2AP002S00F | Compact size (4.0 × 2.0 × 1.25 t mm)<br>Drastically reduced LED current consumption by employing a light modulation system<br>Built-in LEDs for simple optical design and I <sup>2</sup> C output | 3.8                      | -25 to +85 | 240                                     | 25                                     | 150   | 940                                 |

#### Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.  
 Except where specially indicated, models listed on this page comply with the RoHS Directive\*. For details, please contact SHARP.  
 \*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.  
 Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.



## ■ Proximity Sensor with Integrated Ambient Light Sensor

(Ta = 25°C)

| Model No.     | Features  | Absolute maximum ratings |            | Electro-optical characteristics   |                                  |                                       |                                  |  |                                     |                       |                  |
|---------------|---|--------------------------|------------|-----------------------------------|----------------------------------|---------------------------------------|----------------------------------|--|-------------------------------------|-----------------------|------------------|
|               |   | Vcc (V)                  | Topr (°C)  | Dissipation current Icc (μA) TYP. | Proximity sensor portion         |                                       |                                  | Ambient light sensor portion               |                                     | Output current        |                  |
|               |   |                          |            |                                   | Detecting distance Lon (mm) MIN. | Non-detecting distance Loff (mm) MAX. | Peak emission wavelength λp (nm) | Recommended illuminance range Ev (lx) MIN. | Peak sensitivity wavelength λp (nm) | Io1 (μA) TYP.         | Io2 (μA) MAX.    |
| GP2AP002A00F▲ | LED and ambient light sensor combined in a single package (5.6 × 2.1 × 1.25 t mm)<br>Drastically reduced LED current consumption by employing a light modulation system<br>Built-in LEDs for simple optical design<br>Proximity sensor: I <sup>2</sup> C output<br>Ambient light sensor: logarithmic current output | 3.8                      | -25 to +85 | 270                               | 25                               | 150                                   | 940                              | 3 to 55 000                                | 555                                 | 30 (at Ev = 1 000 lx) | 1 (at Ev = 0 lx) |

The model marked with ▲ may not be available in the near future. Contact with SHARP for details before use.

(Ta = 25°C)

| Model No.     | Features   | Absolute maximum ratings |            | Electro-optical characteristics   |                                  |                                  |                                       |                         |                                    |  |
|---------------|--|--------------------------|------------|-----------------------------------|----------------------------------|----------------------------------|---------------------------------------|-------------------------|------------------------------------|--|
|               |  | Vcc (V)                  | Topr (°C)  | Dissipation current Icc (μA) TYP. | Proximity sensor portion         |                                  | Ambient light sensor portion          |                         |                                    |  |
|               |  |                          |            |                                   | Detecting distance Lon (mm) TYP. | Peak emission wavelength λp (nm) | Recommended illuminance range Ev (lx) | Output resolution (bit) | ADC conversion time Tint (ms) TYP. |  |
| ☆GP2AP030A00F | LED and ambient light sensor combined in a single package (4.0 × 2.1 × 1.25 t mm)<br>Built-in LEDs for simple optical design<br>Illuminance output: digital 16-bit output (Minimum detectable illuminance: 0.02 lx)<br>I <sup>2</sup> C output compatible (proximity sensor, ambient light sensor) | 5.5                      | -35 to +85 | 65                                | 100                              | 940                              | 0.02 to 10 000                        | 16                      | 100                                |  |



GP2AP002S00F

GP2AP002A00F▲

GP2AP030A00F

### Notice

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.  
Except where specially indicated, models listed on this page comply with the RoHS Directive\*. For details, please contact SHARP.  
\*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.  
Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.

## ■ Proximity/Gesture Sensor with Integrated Ambient Light Sensor

(Ta = 25°C)

| Model No.     | Features  | Absolute maximum ratings |            | Electro-optical characteristics   |   |                                  |                                  |                                       |                         |                                    |
|---------------|---|--------------------------|------------|-----------------------------------|---|----------------------------------|----------------------------------|---------------------------------------|-------------------------|------------------------------------|
|               |   | Vcc (V)                  | Topr (°C)  | Dissipation current Icc (μA) TYP. | Dissipation current Icc (Gesture) (μA) TYP. | Proximity/gesture sensor portion |                                  | Ambient light sensor portion          |                         |                                    |
|               |   |                          |            |                                   |   | Detecting distance Lon (mm) TYP. | Peak emission wavelength λp (nm) | Recommended illuminance range Ev (lx) | Output resolution (bit) | ADC conversion time Tint (ms) TYP. |
| ☆GP2AP052A00F | LED and ambient light sensor combined in a single package (5.6 × 2.1 × 1.25 t mm)<br>Built-in LEDs for simple optical design<br>Illuminance output: digital 16-bit output (Minimum detectable illuminance: 0.02 lx)<br>I <sup>2</sup> C output compatible<br>Gesture recognition: directional hand movements detected without touching the screen | 5.5                      | -35 to +85 | 65                                | 200   | 100                              | 940                              | 0.02 to 10 000                        | 16                      | 100                                |



**Notice**

In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in equipment using any SHARP devices shown in catalogs, data books, etc.  
Except where specially indicated, models listed on this page comply with the RoHS Directive\*. For details, please contact SHARP.  
\*RoHS Directive: Prohibits use of lead, cadmium, hexavalent chromium, mercury and specific brominated flame retardants (PBBs and PBDEs), with certain exceptions.  
Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device.