



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Semtech GS1671A

HD-, SD-SDI and DVB-ASI Receiver, with Integrated Adaptive Cable Equalizer and Audio Processing

### Overview

The GS1671A is a multi-rate SDI integrated Receiver which includes complete SMPTE processing, as per SMPTE 292M and SMPTE 259M-C. The SMPTE processing features can be bypassed to support signals with other coding schemes.

The GS1671A integrates Gennum's next-generation state-of-the-art adaptive cable equalizer technology, achieving unprecedented cable lengths and jitter tolerance. It features DC restoration to compensate for the DC content of SMPTE pathological signals.

The device features an Integrated Reclocker with an internal VCO and a wide Input Jitter Tolerance (IJT) of 0.7UI. A serial digital loop through output is provided, which can be configured to output either reclocked or non-reclocked serial digital data. The Serial Digital Output can be connected to an external Cable Driver.

The device operates in one of four basic modes: SMPTE mode, DVB-ASI mode, Data-Through mode or Standby mode.

In SMPTE mode, the GS1671A performs SMPTE de-scrambling and NRZI to NRZ decoding and word alignment. Line-based CRC errors, line number errors, TRS errors and ancillary data check sum errors can all be detected. The GS1671A also provides ancillary data extraction. The entire ancillary data packet is extracted, and written to host-accessible registers. Other processing functions include H:V:F timing extraction, Luma and Chroma ancillary data indication, video standard detection, and SMPTE 352M packet detection and decoding. All of the processing features are optional, and may be enabled or disabled via the Host Interface.

In DVB-ASI mode, 8b/10b decoding is applied to the received data stream.

In Data-Through mode, all forms of SMPTE and DVB-ASI decoding are disabled, and the device can be used as a simple serial to parallel converter.

The device can also be placed in a lower power Standby mode. In this mode, no signal processing is carried out and the parallel output is held static. Placing the Receiver in Standby mode will automatically place the integrated equalizer in power down mode as well.

Parallel data outputs are provided in 20-bit or 10-bit multiplexed format for HD and SD video rates. The associated Parallel Clock input signal operates at 148.5 or 148.5/1.001MHz (for all HD 10-bit multiplexed modes), 74.25 or 74.25/1.001MHz (for HD 20-bit mode), 27MHz (for SD 10-bit mode) and 13.5MHz (for SD 20-bit mode).

Up to eight channels, in two groups, of serial digital audio may be extracted from the video data stream, in accordance with SMPTE 272M and SMPTE 299M. The output signal formats supported by the device include AES/EBU and three other industry standard serial digital formats. 16, 20 and 24-bit audio formats are supported at 48kHz synchronous for SD modes and 48kHz synchronous or asynchronous in HD mode. Additional audio processing features include group selection, channel swapping, ECC error detection and correction (HD mode only), and audio channel status extraction. Audio clock and control signals provided by the device include Word Clock (fs), Serial Clock (64fs), and Audio Master Clock at user-selectable rates of 128fs, 256fs or 512fs.

### Features

- Operation at 1.485Gb/s, 1.485/1.001Gb/s and 270Mb/s

- Supports SMPTE 292M, SMPTE 259M-C and DVB-ASI

- Integrated adaptive cable equalizer

- Typical equalized length of Belden 1694A cable:

- 250m at 1.485Gb/s

- 480m at 270Mb/s

- Integrated Reclocker with low phase noise, integrated VCO

- Serial digital reclocked, or non-reclocked output

- Integrated audio de-embedder for 8 channels of 48kHz audio



Integrated audio clock generator  
Ancillary data extraction  
Parallel data bus selectable as either 20-bit or 10-bit  
Comprehensive error detection and correction features  
Output H, V, F or CEA 861 Timing Signals  
1.2V digital core power supply, 1.2V and 3.3V analog power supplies, and selectable 1.8V or 3.3V I/O power supply  
GSPI Host Interface  
-20°C to +85°C operating temperature range  
Low power operation (typically 480mW)  
Small 11mm x 11mm 100-ball BGA package  
Pb-free and RoHS compliant

## Applications

Monitors  
Camera control units  
Multiviewers  
Production switchers  
Master control switchers  
VTRs  
Video servers  
Encoders/decoders  
Up/down/cross converters  
Audio de-embedders  
Format detectors  
Test and measurement equipment

## Order Codes

GS1671AIBTE3: Lead-Free, RoHS Compliant, Tape and Reel-250 Pieces  
GS1671AIBE3: Lead-Free, RoHS Compliant, Tray-168 Pieces

### About Semtech

[Company Overview](#)  
[Management](#)  
[Investors](#)  
[Careers](#)  
[Worldwide Locations](#)

### Media Center

[Product Announcements](#)  
[Business Announcements](#)  
[Upcoming Events](#)  
[Graphics / Collateral](#)  
[Newsletter](#)

### Sites / Access

[mySemtech](#)  
[m.semtech.com \(Mobile\)](#)  
[C-SIM Design Simulation](#)  
[Partner Portal](#)  
[Site Map](#)

### Connect With Us

[Contact Us](#)  
[Sign Up for Newsletter](#)  
[Leave Website Feedback](#)

Follow: [!\[\]\(b792654f2cef9719eabeb6c5be00811e\_img.jpg\)](#) [!\[\]\(7da9a585536d56657fa124d7eaae44e7\_img.jpg\)](#) [!\[\]\(16657531f18b089b0efe8565e1d0533c\_img.jpg\)](#)

Semtech is a Leading Analog & Mixed Signal Products Company

[Privacy Policy](#) | [Terms of Use](#) | [CA Transparency in Supply Chains Act](#)

©2015 Semtech Corporation. All rights reserved.