



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Graphic VFD Module GU112x16G-7003


[CLICK HERE FOR COMMANDS LIST](#)

Ref: MC-015 Dec.02

- Character Graphic, Transformerless display
- Size compatible with LCD Module (U-Version)
- Single 5V power supply
- High Brightness Blue Green display
- Operating temp -40°C to +85°C
- Proportional and scalable fonts
- Screen saver & window definition function
- 8 level brightness control function
- CMOS serial Interface

The module includes the Vacuum Fluorescent Display glass, driver and micro-controller lcs with refresh RAM, character generator and interface logic. This module have CMOS sync or asyn serial interface. The module can simultaneously display graphic pattern and / or characters on screen.

Sample software available



Unit : mm

ELECTRICAL SPECIFICATION

Parameter	Symbol	Value
Power Supply Voltage	VCC	5.0VDC
Power Supply Current	ICC	260mADC typ.
Logic High Input	VIH	0.8VDC min. Vcc max.
Logic Low Input	VIL	0VDC min. 0.2VDC max.
Logic High Output	VOH	3.5VDC min. 3.8VDC min.
Logic Low Output	VOL	0VDC min. 0.6 DC max.

OPTICAL and ENVIRONMENTAL SPECIFICATIONS

Parameter	Value
PCB Size (X x Y mm)	80.00 x 36.00
Display Area (X x Y mm)	52.5 x 11.45
Dot size / Pitch (X x Y mm)	0.33 x 0.58 / 0.47 x 0.73
Luminance	700 cd/m ² Typ.
Color of Illumination	Blue Green (Filter for more colors)
Operating Temperature	-40°C to +85°C
Operating Humidity	20 to 80 % RH (non condensing)

SOFTWARE COMMANDS - Popular codes, more includec

Command	Code
Write Character to Display	20H~FFH
Cursor Set	1FH 24H xL xH yL yH
Initialize Display	1BH 40H
Specify International Font	1BH 52H n
Vertical / Horizontal Scroll Mode	1FH 02H / 1FH 03H
Screen Saver	1FH 28H 61H 40H p
Display Blink	1FH 28H 61H 11H p t1 t2 c
Bit Image Display Group	1FH 28H 66H 11H xL xH
Font Magnified Display	1FH 28H 67H 40H x y
Brightness Level Setting	1FH 58H n

COMMON FONT

	2	3	4	5	6	7
x0H	0	1	2	3	4	5
x1H	6	7	8	9	A	B
x2H	C	D	E	F	G	H
x3H	I	J	K	L	M	N
x4H	O	P	Q	R	S	T
x5H	U	V	W	X	Y	Z
x6H	[\]	^	_	`
x7H	{		}	~		
x8H						
x9H						
xAH						
xBH						
xCH						
xDH						
xEH						
xFH						

INTERNATIONAL FONTS

	8	9	A	B	C	D	E	F	n=0
x0H									
x1H									
x2H									
x3H									
x4H									
x5H									
x6H									
x7H									
x8H									
x9H									
xAH									
xBH									
xCH									
xDH									
xEH									
xFH									n=19

CMOS Serial Interface - CN2

Pin	Asyn. Sig	Syn. Sig
1	Vcc	Vcc
2	SIN	SIN
3	GND	GND
4	SBUSY	SBUSY
5	NC	SCK
6	/RESET	/RESET

CN1 is not used on this Module

Please inquire for full specification.

** Subject to change without notice **