



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Atom Prototyping Module

The Helium Atom is the heart of the connectivity solution. EU Model coming soon, contact us to be notified.

Product Details

The Helium Atom Prototyping Module is the prototyping version of our secure, low-power, dual-band wireless module. The pin layout is compatible with many existing embedded devices, including Raspberry Pi, Arduino, and mbed. Some embedded devices some may require an additional adapter, contact us at human@helium.com if you have any questions before purchasing.

The Atom is the only dual-band, long range, low-power, hardware-secured IEEE-standards compliant module available today. Each Atom has a uniquely provisioned hardware root of trust to help ensure that you can always trust the device and its data to be authentic at all times.

Atom devices connect to the nearest Element out of the box using Helium's wireless technology that allows devices to communicate long distances with little interference and requiring no device-level configuration.

Technical Specifications

Networking Standards	IEEE 802.15.4
Wireless Connectivity	802.15.4 IEEE Standard on dual-band radios 915 MHz & 2.4 GHz (US) 868 MHz & 2.4GHz (EU)
Security	Hardware-based encryption, authentication, and authorization
Environmental Range	Operating Temperature -40° to 185°F (-40° to 85°C)
Product Dimensions	Length: 1.06" (27mm) Width: 1.1" (28mm)
Certifications	FCC ID: 2ADMK-1 IC ID: 12590A-1
Voltage Range	2.0 to 3.6V (3.3V typical; 2.4V recommended minimum for full TX power at 915MHz)