



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



SPECIFICATION CONTROL DRAWING

HC1B-7008-XXXX

TITLE	OPTIMIZED SHIELDED, JACKETED CONDUIT, LIGHT WEIGHT	Date	2-9-05	Revision	F
-------	--	------	--------	----------	---



CABLE CONSTRUCTION DETAILS

PART NUMBER ^{1/}	CONDUIT SIZE (inches)	SHIELD SIZE (AWG)	NOMINAL JACKET THICKNESS (inches)	NOMINAL DIAMETER (inches)	NOMINAL WEIGHT (lb/1000 ft.)
HC1B-7008-0187-0	3/16	36	.035	.381	55.6
HC1B-7008-0281-0	9/32	36	.035	.479	71.9
HC1B-7008-0312-0	5/16	36	.035	.517	81.8
HC1B-7008-0375-0	3/8	36	.035	.591	92.8
HC1B-7008-0437-0	7/16	36	.035	.652	105.
HC1B-7008-0500-0	1/2	36	.035	.730	126.
HC1B-7008-0625-0	5/8	36	.035	.847	151.
HC1B-7008-0750-0	3/4	34	.035	1.01	198.
HC1B-7008-0875-0	7/8	34	.040	1.16	243.
HC1B-7008-1000-0	1	34	.040	1.31	278.

ADDITIONAL REQUIREMENTS

CABLE JACKET: Tensile Strength, 2000 lbf/in² (minimum)
Elongation, 300% (minimum)

D.C. SHIELD RESISTANCE: 3 ohms/1000 ft. (maximum)

JACKET FLAWS:

Spark Test, 2.5 kV (rms) at 60 Hz

JACKET MARK: " RAYCHEM - Part Number - Year of Manufacture" at 12 inch
(nominal) intervals in contrasting ink

SURFACE TRANSFER IMPEDANCE: See Page 2

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.

^{1/} COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "Axxx".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.

DIMENSIONS ARE IN INCHES, AND UNLESS OTHERWISE DESIGNATED ARE NOMINAL.

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.
REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.



Raychem Wire & Cable
501 Oakside Avenue
Redwood City, CA 94063-3800
Phone: 1-800-227-8816
Fax: 1-650-361-6297

**Typical Surface Transfer Impedance (Zt) Curve, 1 Hz - 100 KHz
For HCIB-7008-0312-0**

