



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





# Data Logging Sound Level Meter

**High accuracy datalogging of up to 20,000 records**

Meets ANSI and IEC61672-1 Type 2 standards

## Features:

- Three ranges from 30 to 130dB
- Datalogging capability up to 20,000 records
- Capture up to 10 readings/sec when connected to a PC
- Records readings with real date and time stamp
- Min/Max and Data Hold functions
- Heavy Duty rugged double molded housing
- USB port includes software
- Auto power off with disable capability
- Includes Windows<sup>®</sup> compatible software, USB cable, wind cover, tripod, hard carrying case, AC adaptor, and 9V battery



Meets new IEC 61672-1 Class 2 accuracy standard for OSHA and other local and national noise ordinances



Meter and accessories are packaged in a rugged hard carrying case for added protection



USB port includes PC Software included



Specifications	
Range	30 to 130dB
Basic accuracy	±1.4dB
Weighting	A and C
Response Time	Fast/Slow
Analog Output	AC/DC
Datalogging	20,000 points
PC Interface	USB
Dimensions	10.9 x 3 x 2" (278 x 76 x 50mm)
Weight	12.3oz (350g)

## Ordering Information:

- HD600 .....Data Logging Sound Level Meter  
 HD600-NIST ..Data Logging Sound Level Meter with NIST Certificate  
 407744 .....94dB Sound Calibrator for 0.5" and 1" microphones  
 407766 .....94/114dB Sound Calibrator for 0.5" and 1" microphones

