# imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



### Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




## **3**M

## Heat Shrink Heavy Duty Breakout Boot, 5-Way Outlet 3M Part Number HDBB-505

### **Typical Applications**

These breakout boots provide strain relief and environmental/mechanical protection for breakouts in multiconductor armored or sheathed cables. This style is designed for five breakouts.

### **Expanded part (as supplied)**





PART	Cable E H DIA			tor Legs DIA	P ±10% R	R ±10% R	HW <u>+</u> 20% R
NUMBER	MIN X	MAX R	MIN X	MAX R			
HDBB-505-1-250	2.36	0.96	1.18	0.29	7.08	1.18	0.14
	(59.94)	(24.38)	(29.97)	(7.37)	(179.83)	(29.97)	(3.56)

J DIA

#### Notes:

H DIA

All dimensions in both inches and metric, all angles in degrees
Dimensions in table: X = Expanded (Minimum) R = Recovered (Maximum)

Color: Black3M CAGE Code: 20999

Materials Available	Standard Part Supplied v		
<ul> <li>Semi-rigid Flame Retardant Polyolefin</li> <li>Flexible Polyolefin, Halogen Free</li> <li>Flexible Flame Retardant Polyolefin</li> </ul>	Adhesive (Part #)	Factory Applied	<b>Description</b>
	TTS-250	-250	Thermoplastic 80°C

#### Fully recovered part (after heating)

#### **Important Notice**

All statements, technical information and recommendations related to the Seller's products are based on information believed to be reliable, but the accuracy or completeness thereof is not guaranteed. Before utilizing the product, the user should determine the suitability of the product for its intended use. The user assumes all risks and liability whatsoever in connection with such use.

Any statements or recommendations of the Seller which are not contained in the Seller's current publications shall have no force or effect unless contained in an agreement signed by an authorized officer of the Seller. The statements contained herein are made in lieu of all warranties, expressed or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose which warranties are hereby expressly disclaimed.

SELLER SHALL NOT BE LIABLE TO THE USER OR ANY OTHER PERSON UNDER ANY LEGAL THEORY, INCLUDING BUT NOT LIMITED TO NEGLIGENCE OR STRICT LIABILITY, FOR ANY INJURY OR FOR ANY DIRECT, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES SUSTAINED OR INCURRED BY REASON OF THE USE OF ANY OF THE SELLER'S PRODUCTS.

#### **3M**

**Electrical Products Division** 6801 River Place Blvd. Austin, TX 78726-9000