



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Product Information

HES10GM Series

10G-Port Din-rail Full Gigabit Managed Ethernet Switches



Features

- RingOn and RingOpen (recovery time < 15ms), RSTP for network redundancy
- SNMPv1/v2c/v3 for network management of different levels
- IGMP snooping and GMRP for filtering multicast traffic
- QoS (IEEE 802.1p/1Q) and TOS/DiffServ to increase determinism
- -40 to +75°C operating temperature range (W models)
- IP30 DIN Rail or Panel Mount



Henrich Electronics Corporation

Main Office

Tel: 860-487-9869

Fax: 860-487-9478

www.henrich-inc.com

Introduction

The HES10GM series is equipped with 8 Gigabit Ports, making it ideal for upgrading an existing network to Gigabit speed or building a new full Gigabit backbone. Gigabit transmission increases bandwidth for higher performance and transfers large amounts of triple-play services across a network quickly. Redundant Ethernet RingOpen, RingOn, RSTP, and MSTP increase system reliability and the availability of your network backbone. The HES10GM series is designed especially for communication demanding applications, such as video and process monitoring, ITS, and DCS systems, all of which can benefit from a scalable backbone construction.

Specifications

Technology		Power Requirements	
Standard :	IEEE802.3, 802.3u, 802.3x, 802.3z	Input Voltage :	12~36VDC @ 24W MAX 10~24VAC @ 24VA MAX
Flow Control :	IEEE802.3x flow control, back pressure flow control	Input Connection :	Grid panel terminal blocks Standard 4 pin input connection (optional)
Protocols :	IGMP Snooping, GMRP, SNMPv1/v2c/v3, DHCP Client, HTTP, HTTPS, Telnet, NTP Client	Physical Characteristics	
	L2 Functions	Case :	Slim Metal Case, IP30 Design
	<ul style="list-style-type: none"> • IEEE 802.1Q Static VLAN and VLAN Label • Link Layer Management Protocol (LLDP) • IEEE 802.1w Rapid Spanning Tree Protocol (RSTP) • IGMP SNOOPING • RingOn™ Redundant Technology, recovery time <15ms • RingOpen Redundancy 	Dimensions :	64.2×183.1×155.1mm
	Management Tools	Installation :	DIN Rail or Panel Mounting
Software functions :	<ul style="list-style-type: none"> • Web Interface (HTTP and HTTPS) • Console port and Command Line Interface(CLI) controlled by SSHv2 • SNMPv1/v2c/v3 • Flexible configuration and log file management • Managing local file through HTTP, FTP and TFTP • Syslog(System log file and remote syslog server) • SNTP(NTP Client) • Software Online Upgrading 	Environment Limits	
		Operating Temp. :	Standard Models: -10 to 60°C Wide Temp. Models: -40 to 75°C
		Storage Temp. :	-40 to 85°C
		Ambient Relative Humidity :	5 to 95%(Non-condensing)
		Standards and Certifications	
		EMI :	FCC Part15, CISPR(EN55022) Class A
		EMS :	EN61000-4-2(ESD) Level 3, EN61000-4-3(RS) Level 3, EN61000-4-4(EFT) Level 3, EN61000-4-5(Surge) Level 3, EN61000-4-6(CS) Level 3, EN61000-6-2
		Shock :	IEC 60068-2-27
		Freefall :	IEC 60068-2-32
		Vibration :	IEC 60068-2-6
		Warranty	
		Warranty Period :	3 years
Switch Properties			
MAC Table Size :	16K		
Priority Queues :	8		
Max. Number VLANs :	64		
VLAN ID Range :	VID 1 to 4094		
IGMP Groups :	256		
Interface			
Fiber Port :	1000M Gigabit SFP slots.		
LED Indicators :	Power, Port Status, 10/100/1000M		
Output Warning :	Relay, Standard 2 Pin @30V		
Console Port :	RS-232 (RJ45 connector)		

Ordering Information

HES10GM Series

HES10GM-2SFP-VL	Din-rail Managed, 8 Gigabit Ports, 2 x Gigabit SFP Slots, Industrial Temperature -10°C to +60°C, Power Input 12~36VDC or 10~24VAC
HES10GM-2SFP-VLW	Din-rail Managed, 8 Gigabit Ports, 2 x Gigabit SFP Slots, Industrial Wide Temperature -40°C to +75°C, Power Input 12~36VDC or 10~24VAC