



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Product Information

HES16C/26C Series

16 and 26-Port Rackmount Unmanaged Ethernet Switches



Features

- ❖ Up to 10 100Mbps Fiber ports
- ❖ 10/100BaseT(X) auto-negotiation and auto-MDI/MDI-X
- ❖ -40 to +75°C Operating Temperature Range (W models)
- ❖ IP40 aluminum housing
- ❖ CE/FCC, EN60959 certifications



Henrich Electronics Corporation

Main Office

Tel: 860-487-9869

Fax: 860-487-9478

www.henrich-inc.com

Introduction

The HES16C/26C industrial rackmount Ethernet switches are designed to meet the demands of industrial application networks such as traffic control systems, and maritime applications. The HES16C/26C are 16 and 26-port industrial 19"rackmount unmanaged Ethernet switch series that provides a rugged and economical solution for your industrial Ethernet connections. A universal power supply range of 110/220VDC/VAC give users greater flexibility in choosing power inputs. The Ethernet switches comply with FCC, CE standards and support a wide operating temperature range from -40 to +75°C. All models undergo a 100% burn-in test to ensure that they fulfill the special needs of industrial automation control applications.

Specifications

Technology		
Standard :	IEEE802.3, 802.3u, 802.3x	
Processing Type :	Store and forward	
Broadcast Storm :	Automatic Broadcast Storm Control	
Flow Control :	Full Duplex Flow Control, Half Duplex Back Pressure Control	
Protocols :	CSMA/CD (Carrier Sense Multiple Access/Collision Direct)	
Switch Properties		
MAC Table Size :	8K	
Interface		
RJ45 Port :	10/100BaseT(X) auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection	
Fiber Port :	100BaseFX ports (SC/ST connector)	
LED Indicators :	Power, Port Status, 10/100M	
Power Requirements		
Input Voltage :	HES16C: 120~370VDC @ 15W MAX 85~264VAC @ 15VA MAX HES26C: 120~370VDC @ 25W MAX 85~264VAC @ 25VA MAX	
Input Connection :	Barrier type terminal blocks	
Physical Characteristics		
Case :	Slim Metal Case, IP40 Design	
Dimensions :	443×44×260mm	
Installation :	Rack mounting	
Environment Limits		
Operating Temp. :	Standard Models: -10 to 60°C Wide Temp. Models: -40 to 75°C	
Storage Temp. :	-40 to 85°C	
Ambient Relative Humidity :	5 to 95%(Non-condensing)	
Optical Fiber		
Mode	Multi-mode	Single Mode
Transmission Distance	2km	20km
Centre Wavelength	1310nm	1310nm
Cable Size	62.5/125um	9/125um
TX Power(dBm)	-20~-10dBm	-15~-8dBm
RX Power(dBm)	< -32dBm	< -32dBm
Transmission Rate	100Mbps	100Mbps
Standards and Certifications		
EMI :	FCC Part15, CISPR(EN55022) Class A	
EMS :	EN61000-4-2(ESD) Level 3, EN61000-4-3(RS) Level 3, EN61000-4-4(EFT) Level 3, EN61000-4-5(Surge) Level 3, EN61000-4-6(CS) Level 3, EN61000-6-2	
Shock :	IEC 60068-2-27	
Freefall :	IEC 60068-2-32	
Vibration :	IEC 60068-2-6	
Warranty		
Warranty Period :	3 years	

Ordering Information

HES16C

HES16C-VH	Rackmount Unmanaged, 16 x 100Mbps Copper Port, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES16C-VHW	Rackmount Unmanaged, 16 x 100Mbps Copper Port, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES16C-2SC-VH	Rackmount Unmanaged, 14 x 100Mbps Copper Port, 2 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES16C-2SC-VHW	Rackmount Unmanaged, 14 x 100Mbps Copper Port, 2 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES16C-2SSC-VH	Rackmount Unmanaged, 14 x 100Mbps Copper Port, 2 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES16C-2SSC-VHW	Rackmount Unmanaged, 14 x 100Mbps Copper Port, 2 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES16C-4SC-VH	Rackmount Unmanaged, 12 x 100Mbps Copper Port, 4 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES16C-4SC-VHW	Rackmount Unmanaged, 12 x 100Mbps Copper Port, 4 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES16C-4SSC-VH	Rackmount Unmanaged, 12 x 100Mbps Copper Port, 4 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES16C-4SSC-VHW	Rackmount Unmanaged, 12 x 100Mbps Copper Port, 4 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC

Note: All of the Above Products SC Connector can be replaced by ST Connector

HES26C

HES26C-VH	Rackmount Unmanaged, 26 x 100Mbps Copper Port, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26C-VHW	Rackmount Unmanaged, 26 x 100Mbps Copper Port, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES26C-2SC-VH	Rackmount Unmanaged, 24 x 100Mbps Copper Port, 2 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26C-2SC-VHW	Rackmount Unmanaged, 24 x 100Mbps Copper Port, 2 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES26C-2SSC-VH	Rackmount Unmanaged, 24 x 100Mbps Copper Port, 2 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26C-2SSC-VHW	Rackmount Unmanaged, 24 x 100Mbps Copper Port, 2 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES26C-4SC-VH	Rackmount Unmanaged, 22 x 100Mbps Copper Port, 4 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26C-4SC-VHW	Rackmount Unmanaged, 22 x 100Mbps Copper Port, 4 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES26C-4SSC-VH	Rackmount Unmanaged, 22 x 100Mbps Copper Port, 4 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26C-4SSC-VHW	Rackmount Unmanaged, 22 x 100Mbps Copper Port, 4 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES26C-6SC-VH	Rackmount Unmanaged, 20 x 100Mbps Copper Port, 6 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26C-6SC-VHW	Rackmount Unmanaged, 20 x 100Mbps Copper Port, 6 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES26C-6SSC-VH	Rackmount Unmanaged, 20 x 100Mbps Copper Port, 6 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26C-6SSC-VHW	Rackmount Unmanaged, 20 x 100Mbps Copper Port, 6 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES26C-8SC-VH	Rackmount Unmanaged, 18 x 100Mbps Copper Port, 8 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26C-8SC-VHW	Rackmount Unmanaged, 18 x 100Mbps Copper Port, 8 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC

HES26C-8SSC-VH	Rackmount Unmanaged, 18 x 100Mbps Copper Port, 8 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26C-8SSC-VHW	Rackmount Unmanaged, 18 x 100Mbps Copper Port, 8 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES26C-10SC-VH	Rackmount Unmanaged, 16 x 100Mbps Copper Port, 10 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26C-10SC-VHW	Rackmount Unmanaged, 16 x 100Mbps Copper Port, 10 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES26C-10SSC-VH	Rackmount Unmanaged, 16 x 100Mbps Copper Port, 10 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26C-10SSC-VHW	Rackmount Unmanaged, 16 x 100Mbps Copper Port, 10 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC

Note: All of the Above Products SC Connector can be replaced by ST Connector