



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Product Information

HES16MC/26MC Series

16 and 26-Port Rackmount Managed Ethernet Switches



Features

- ❖ RingOn (recovery time < 15ms), RSTP for network redundancy
- ❖ Port Mirror and Port Trunk with LACP
- ❖ QoS (IEEE 802.1p/1Q) and TOS/DiffServ to increase determinism
- ❖ -40 to +75°C Operating Temperature Range (W models)



Henrich Electronics Corporation

Main Office

Tel: 860-487-9869

Fax: 860-487-9478

www.henrich-inc.com

Introduction

The HES16MC/26MC are standalone 16 and 26-port Rackmount managed Ethernet switches. With their advanced RingOn technology (recovery time < 15 ms) and RSTP/STP, the HES16MC/26MC switches increase the reliability and availability of your industrial Ethernet network. Models with an wide operating temperature range from -40 to +75°C are also available, and the switches support several reliable and intelligent functions, including SNMP Inform, QoS, IGMP snooping, VLAN, IEEE 802.1X, HTTPS, SNMPv3, and SSH, making the HES16MC/26MC switches suitable for any harsh industrial environment.

Specifications

Technology		
Standard :	IEEE802.3, 802.3u, 802.3x, 802.1Q, 802.1p	
Processing Type :	Store and forward	
Broadcast Storm :	Automatic Broadcast Storm Control	
Management :	by Web Browser	
RingOn :	Recovery Time within 15ms	
Flow Control :	Full Duplex Flow Control, Half Duplex Back Pressure Control	
Protocols :	SNMP V1/V2c/V3, RingOn/RingOpen, HTTP/HTTPS, LLDP, DHCP Client, IGMP Snooping/GMRP, Telnet, Syslog	
Switch Properties		
MAC Table Size :	8K	
Priority Queues :	4	
Max. Number VLANs :	64	
VLAN ID Range :	VID 1 to 4094	
IGMP Groups :	256	
Interface		
RJ45 Port :	10/100BaseT(X) auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection	
Fiber Ports :	100BaseFX ports (SC/ST connector)	
LED Indicators :	Power, Port Status	
Console port :	DB9 male	
Output Warning :	Relay, Standard 2 Pin	
Power Requirements		
Input Voltage :	HES16MC: 120~370VDC @ 20W MAX 85~265VAC @ 20VA MAX HES26MC: 120~370VDC @ 30W MAX 85~265VAC @ 30VA MAX	
Input Connection :	Barrier type terminal blocks	
Physical Characteristics		
Case :	Slim Metal Case, IP30 Design	
Dimensions :	443×44×260mm	
Installation :	DIN Rail or Panel Mounting	
Optical Fiber		
Mode	Multi-mode	Single Mode
Transmission Distance	2km	20km
Centre Wavelength	1310nm	1310nm
Cable Size	62.5/125um	9/125um
TX Power(dBm)	-20~-10dBm	-15~-8dBm
RX Power(dBm)	< -32dBm	< -32dBm
Transmission Rate	100Mbps	100Mbps
Environment Limits		
Operating Temp. :	Standard Models: -10 to 60°C Wide Temp. Models: -40 to 75°C	
Storage Temp. :	-40 to 85°C	
Ambient Relative Humidity :	5 to 95%(Non-condensing)	
Standards and Certifications		
EMI :	FCC Part15, CISPR(EN55022) Class A	
EMS :	EN61000-4-2(ESD) Level 3, EN61000-4-3(RS) Level 3, EN61000-4-4(EFT) Level 3, EN61000-4-5(Surge) Level 3, EN61000-4-6(CS) Level 3, EN61000-6-2	
Shock :	IEC 60068-2-27	
Freefall :	IEC 60068-2-32	
Vibration :	IEC 60068-2-6	
Warranty		
Warranty Period :	3 years	

Ordering Information

HES16MC

HES16MC-VH	Rackmount Managed, 16 x 100Mbps Copper Port, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES16MC-VHW	Rackmount Managed, 16 x 100Mbps Copper Port, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES16MC-2SC-VH	Rackmount Managed, 14 x 100Mbps Copper Port, 2 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES16MC-2SC-VHW	Rackmount Managed, 14 x 100Mbps Copper Port, 2 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES16MC-2SSC-VH	Rackmount Managed, 14 x 100Mbps Copper Port, 2 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES16MC-2SSC-VHW	Rackmount Managed, 14 x 100Mbps Copper Port, 2 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES16MC-4SC-VH	Rackmount Managed, 12 x 100Mbps Copper Port, 4 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES16MC-4SC-VHW	Rackmount Managed, 12 x 100Mbps Copper Port, 4 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES16MC-4SSC-VH	Rackmount Managed, 12 x 100Mbps Copper Port, 4 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES16MC-4SSC-VHW	Rackmount Managed, 12 x 100Mbps Copper Port, 4 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC

Note: All of the Above Products SC Connector can be replaced by ST Connector

HES26MC

HES26MC-VH	Rackmount Managed, 26 x 100Mbps Copper Port, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26MC-VHW	Rackmount Managed, 26 x 100Mbps Copper Port, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES26MC-2SC-VH	Rackmount Managed, 24 x 100Mbps Copper Port, 2 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26MC-2SC-VHW	Rackmount Managed, 24 x 100Mbps Copper Port, 2 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES26MC-2SSC-VH	Rackmount Managed, 24 x 100Mbps Copper Port, 2 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26MC-2SSC-VHW	Rackmount Managed, 24 x 100Mbps Copper Port, 2 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES26MC-4SC-VH	Rackmount Managed, 22 x 100Mbps Copper Port, 4 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26MC-4SC-VHW	Rackmount Managed, 22 x 100Mbps Copper Port, 4 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES26MC-4SSC-VH	Rackmount Managed, 22 x 100Mbps Copper Port, 4 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26MC-4SSC-VHW	Rackmount Managed, 22 x 100Mbps Copper Port, 4 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES26MC-8SC-VH	Rackmount Managed, 18 x 100Mbps Copper Port, 8 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26MC-8SC-VHW	Rackmount Managed, 18 x 100Mbps Copper Port, 8 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES26MC-8SSC-VH	Rackmount Managed, 18 x 100Mbps Copper Port, 8 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26MC-8SSC-VHW	Rackmount Managed, 18 x 100Mbps Copper Port, 8 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC
HES26MC-10SC-VH	Rackmount Managed, 16 x 100Mbps Copper Port, 10 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26MC-10SC-VHW	Rackmount Managed, 16 x 100Mbps Copper Port, 10 x 100Mbps Multi-Mode Fiber Port with SC connectors, 2KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC

HES26MC-10SSC-VH	Rackmount Unmanaged, 16 x 100Mbps Copper Port, 10 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Temperature -10°C to +60°C, Power Input 120~370VDC or 85~264VAC
HES26MC-10SSC-VHW	Rackmount Unmanaged, 16 x 100Mbps Copper Port, 10 x 100Mbps Single-Mode Fiber Port with SC connectors, 20KM, Industrial Wide Temperature -40°C to +75°C, Power Input 120~370VDC or 85~264VAC

Note: All of the Above Products SC Connector can be replaced by ST Connector