



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Product Information

HES6GM-4E Series

6G-port full Gigabit Managed Ethernet switches with
4 IEEE 802.3af/at PoE+ ports



Features

- ❖ 4 10/100/1000BaseTX RJ-45 Ports (All ports support IEEE 802.3af/at PoE+)
- ❖ -40°C to +75°C Operating Temperature
- ❖ Smart PoE+ over current, over temperature and short circuit protection
- ❖ Redundant Power Input (24~52VDC)
- ❖ Store-and-forward Technology
- ❖ 4k MAC Addresses

Introduction

The HES6GM-4E Series are full gigabit managed PoE+ Ethernet switches that come standard with 4 10/100/1000BaseT(X), 802.3af (PoE), and 802.3at (PoE+)-compliant Ethernet ports, and up to 2 Gigabit SFP fiber ports. Each POE+ port is able to offer up to 30 watts power for PD device. The power input ranges from 24~52VDC. The switch is installed with Din-rail or panel mount.

The HES6GM-4E Ethernet switches are highly versatile, and the SFP fiber ports can transmit data up to 120 km from the device to the control center with high EMI immunity. The Ethernet switches support a variety of management functions, including STP/RSTP, RingOpen, RingOn, PoE power management, PoE device auto-checking, PoE power scheduling, IGMP, VLAN, QoS, bandwidth management.

Specifications

Technology	
Standard :	IEEE802.3af/at, 802.3, 802.3u, 802.3x, 802.3ab, 802.3z, 802.1w, 802.1Q, 802.1p
Processing Type :	Store and forward
Broadcast Storm :	Automatic Broadcast Storm Control
Flow Control :	Full Duplex Flow Control, Half Duplex Back Pressure Control
Protocols :	SNMP V1/V2c/V3, RingOn/RingOpen, HTTP/HTTPS, LLDP, DHCP Client, IGMP Snooping/GMRP, Telnet, Syslog
Software Functions :	<ul style="list-style-type: none"> • RingOn Redundant Ring Technology: Recovery time less than 15ms • VLAN: Port Based VLAN, IEEE 802.1Q Tag VLAN • Port Trunking • Built-in Web Server, remote management and configuration through browser • Quality of Service : Determined by port, tag(CoS), and IPv4 different service(DSCP) • IGMP Snooping /GMRP • Static MAC Address Forwarding • SNMP V1/V2c/V3 • RSTP • LLDP • On-line Software Upgrading • Automatic warning by exception through e-mail or relay output • System Log • DHCP Client • Port Mirror: Supports TX, RX, and both packet • Broadcast storm control and Port-Based traffic control • IP Security: 10 IP address entries for permission to access management functions
Switch Properties	
MAC Table Size :	4K
Packet Buffer Size :	128K
Jumbo Frame Size :	Supports up to 9720 byte
Interface	
RJ45 Port :	Auto-negotiation 10/100/1000Base-T, Full/Half Duplex, Auto-MDI/MDIX
Fiber Ports :	100/1000Base-X SFP interface. SFP module is MSA-compliant.
PoE+ Pin out :	V+, V+, V-, V-, for pin 4, 5, 7, 8 (Midspan)
Console port :	RJ45
DIP Switch :	Dial switch
LED Indicators :	P1, P2, Link, State, MAX, POE+ (1~4)
Alarm :	Relay, Email
Relay output :	Standard 2-pin terminal blocks
Power Requirements	
Input Voltage :	24~52VDC
Power budget :	180W MAX
Input Connection :	Standard four terminal power input
Physical Characteristics	
Case :	Slim Metal Case, IP30 Design
Dimensions :	45×145×108mm (W*H*D)
Installation :	DIN Rail or Panel Mounting
Optical Fiber	
Mode	Single Mode
Transmission Distance	20km
Centre Wavelength	1310nm
Cable Size	9/125um
TX Power(dBm)	-8~-2dBm
RX Power(dBm)	< -24dBm
Transmission Rate	1000Mbps
Environment Limits	
Operating Temp. :	Standard Models: -10 to 60°C Wide Temp. Models: -40 to 75°C
Storage Temp. :	-40 to 85°C
Ambient Relative Humidity :	5 to 95%(Non-condensing)

Standards and Certifications	
Safety :	EN60950, UL60950, IEC60950
EMI :	FCC Part15, CISPR(EN55022) Class A
EMS :	EN61000-4-2(ESD) Level 3,
	EN61000-4-3(RS) Level 3,
	EN61000-4-4(EFT) Level 3,
	EN61000-4-5(Surge) Level 3,
	EN61000-4-6(CS) Level 3,
	EN61000-6-2
Shock :	IEC 60068-2-27
Freefall :	IEC 60068-2-32
Vibration :	IEC 60068-2-6

Environment Limits	
Operating Temp. :	Standard Models: -10 to 60°C
	Wide Temp. Models: -40 to 75°C
Storage Temp. :	-40 to 85°C
Ambient Relative Humidity :	5 to 95%(Non-condensing)
Warranty	
Warranty Period :	3 years

Ordering Information

HES6GM-4E

HES6GM-4E-2SFP-VL	Din-rail Managed, 4 x 1000Mbps POE+ Copper Port, 2 x 1000Mbps SFP Fiber Port, Industrial Temperature -10 to +60 °C, Power Input 24~52VDC
HES6GM-4E-2SFP-VLW	Din-rail Managed, 4 x 1000Mbps POE+ Copper Port, 2 x 1000Mbps SFP Fiber Port, Industrial Wide Temperature -40 to +75 °C, Power Input 24~52VDC